



SikaTile®-101 Overspray

UNDERLAYMENT PRIMER AND BONDING AGENT

- Reduces porosity factor, allowing proper open time for adhesive
- Enhances adhesive bond
- Adds strength and durability to the underlayment
- Increases abrasion resistance
- Provides temporary wear surface for construction traffic
- Easy, one-coat application

Attributes Include:



BUILDING TRUST



SikaTile®-101 Overspray

UNDERLAYMENT PRIMER AND BONDING AGENT

WHERE TO USE

- Interior and exterior use
- Porous Substrates
- Cement Backer Board
- Mortar Beds (cured)
- Ceramic Tile and Stone
- Concrete
- Exterior Grade Plywood
- Gypsum Drywall
- Gypsum Mortar Bed
- Gypsum Oriented Strand Board
- Gypsum-based Underlayments

Note: Always refer to current PDS and SDS for detailed performance specifications prior to use.

Coverage: 250–300 ft²/gal (23–28 m²/gal)*

*Coverage may vary based on substrate porosity.

FEATURES AND BENEFITS

- Solvent-free formulation
- Reduces outgassing and minimizes bubble formation in underlayment
- Prevents premature water loss from underlayment into the substrate
- Provides excellent bond strength across a range of application temperatures
- Cost-effective solution for sealing concrete surfaces



FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.SikaTile.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225



BUILDING TRUST

