

PRODUCT DATA SHEET

Sarnatape[®]-200

Aluminium Butyl Rubber Adhesive Tape

PRODUCT DESCRIPTION

Sarnatape[®]-200 with one-side adhesion is a butyl rubber sealing tape with aluminium laminated membrane as top layer and liner with finger-lift (polypropylene).

USES

Sarnatape[®]-200 is applied to the yellow smooth membrane side of SikaProof[®] A at the transition between SikaProof[®] A and SikaBit[®] S-60.

CHARACTERISTICS / ADVANTAGES

- Polypropylene liner with finger-lift
- Very high tack and long-term adhesive bond
- Solvent-free
- Volume resistant
- Very high durability

PRODUCT INFORMATION

Packaging	1 roll, packed in cardboard box
	Coverage: 200 mm (.66 ft) x 20 m (65.6 lf) roll
Appearance / Color	Gray
Shelf Life	2 years if stored properly in unopened, undamaged, original packaging, in a horizontal position, protected from direct sunlight and at temperatures between +5°C (+40°F) and +25°C (+77°F).
Storage Conditions	Store rolls in horizontal position on a smooth surface and protected from direct sunlight, rain and snow between +5°C (+40°F) and +25°C (+77°F).
Length	20 m (65.6 lf)
Width	200 mm (0.66 ft)
Thickness	1.10 mm (0.043 in)

TECHNICAL INFORMATION

Tensile Strength	> 100 N / 25 mm	(EN 14410)
-------------------------	-----------------	------------

SYSTEM INFORMATION

System Structure

Compatible system products:

- Sarnafil® MT sub-roof membranes
- Sarnavap® PE vapour control layer
- Sarnavap®-5000E SA

Ancillary products:

- Primer-130

Compatibility

Not compatible in direct contact with PVC, tar, asphalt, hot bitumen, wood preservatives with surfactants and substances containing oil, solvents or wetting agents. These materials could adversely affect the product properties.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surfaces must be sturdy, dry, clean and free from dust, grease and other materials that impair adhesion.

SUBSTRATE PREPARATION

Porous contact surfaces must first be primed with Primer 130.

APPLICATION

Sarnatape®-200 is a cold-applied self-adhesive tape to act as a protection layer between the membrane surface side of the SikaProof® A membrane system and the bitumen surface side of the SikaBit® S-60.

LIMITATIONS

Not compatible in direct contact with PVC, tar, asphalt, hot bitumen, wood preservatives with surfactants and substances containing oil, solvents or wetting agents.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety

Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD**

BY OTHERS.

Sale of Sika products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Sarnafil

100 Dan Road
Canton, MA 02021
Phone: +1 800-451-2504
Fax: +1 781-828-5365
usa.sika.com/sarnafil
webmaster.sarnafil@us.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet

Sarnatape®-200
November 2018, Version 01.01
020945051200000006

Sarnatape-200-en-US-(11-2018)-1-1.pdf

