

MEMBRANE WATERPROOFING SYSTEMS: SIKAPROOF

BRUCE ZHU ENGINEERED WATERPROOFING SIKA <u>ZHU.BRUCE@US.SIKA.COM</u> – 314-706-8259



SIKA IN WATERPROOFING HISTORY AND NOW



Sika was founded in Switzerland in 1910.

The first key project:

- Waterproofing of the Gotthard Tunnel (at the time, longest railway tunnel in the world) with the waterproofing admixture Sika-1.
- Over 100 year of experience in below grade concrete waterproofing.



In 2025, global leader of construction chemicals

Key Figures:

- Broad range of product from basement to roof
- Over 25,000 employees
- Local subsidiaries in over 100 countries
- Over 300 plants worldwide



PRODUCTS WE OFFER

▲ Sarnafil Roofing – PVC & Liquid Applied

▲ Concrete – Admixtures, shrinkage reducers, crystalline waterproofing

▲ CRSB – Sealants, Concrete Repair & Protection

▲ Balconies and Parking Garages – Epoxy and Urethane

▲ Industrial Flooring – Epoxy, Urethane, Underlayments

▲ Waterproofing - Sheet Membranes, Greenstreak Waterstops, Injections

▲ Decorative Concrete – Scofield, Butterfield Color

▲ Insulation – RMAX

▲ Emseal

- ▲ Fibermesh (Propex)
- American Hydrotech
- ▲ MBCC



WATERTIGHT BASEMENTS WHY FULLY BONDED MEMBRANE SYSTEMS?



BUILDING TRUST

SHEET WATERPROOFING SYSTEMS WATERTIGHT BASEMENT – FULLY BONDED SYSTEMS







SHEET WATERPROOFING SYSTEMS WATERTIGHT BASEMENT – FULLY BONDED SYSTEMS



No Lateral Water Migration

- The fully bonded systems prevents lateral water migration in case of puncture or damage.
- Potential water ingress is contained in a small area and can be repaired cost-efficiently.
- Risk and Damage Control







SHEET WATERPROOFING SYSTEMS FULLY BONDED MEMBRANE SYSTEM TESTING

FUNCTION TESTS PER ASTM D 5385 MOD.





No lateral water migration tested up 7 bar (~101 psi) water pressure



WATERTIGHT BASEMENTS SikaProof[®] A+ SYSTEM – SYSTEM DURABILITY









Durability Testing System Testing

- System tested up to 5 bar / 72 psi
- 2 mm (1/16 in) crack width
- Simulated damage: 3 in x 1 in
- 28 days exposure

Accelerated Ageing Testing

Exposure test of material to different chemicals

- 5% H₂SO₃ (sulfurous acid)
- 50% H₂SO₄ (sulfuric acid)
- Saturated Ca(OH)₂ (calcium hydroxide)
- 10% Na⁺Cl⁻ (sodium chloride / salt water)



SHEET WATERPROOFING SYSTEMS WATERTIGHT BASEMENT – FULLY BONDED SYSTEMS



WHAT IS SikaProof A+[®] ?



SikaProof[®] A+ System

The second generation of fully bonded, pre-applied waterproofing membranes from Sika

Soiling during installation

• Easily washable **bonding layer** with up to **90 days UV Exposure**

Seams and details

• Fully tested self-adhesive Tape OR Thermal jointing with hot air welding equipment

Dual Bond Technology

Chemical and Mechanical Bond



SIKAPROOF[®] A+ TECHNOLOGY





WATERTIGHT BASEMENTS SikaProof[®] A+ SYSTEM – PRODUCTS



SikaProof[®] A+ 12

Membrane rolls in two widths:

- 6.5 ft x 65.6 ft (430 sqft) / 2 m x 20 m (40 m²)
- 3.2 ft x 65.6 ft (215 sqft) / 1 m x 20 m (20 m²)



SikaProof[®] Tape A+ N

Tape roll dimension in two widths:

A+N: 4.70 in x 82.0 ft / 0.20 m x 25 m



WATERTIGHT BASEMENTS SikaProof® A+ PRE-APPLIED SYSTEM – SEAMS AND DETAILS



Self-Adhesive Edge

Taping

Welding



WATERTIGHT BASEMENTS SikaProof® A+ PRE-APPLIED SYSTEM – SEAMS AND DETAILS





WATERTIGHT BASEMENTS SikaProof[®] A+ PRE-APPLIED SYSTEM – SEAMS AND DETAILS





WATERTIGHT BASEMENTS SikaProof[®] A+ PRE-APPLIED SYSTEM – SEAMS AND DETAILS





SikaProof[®] PRE-APPLIED SYSTEM – SEAMS AND DETAILS



Inside Corners



SikaProof[®] PRE-APPLIED SYSTEM – SEAMS AND DETAILS



Outside Corners



SikaProof[®] A+ PRE-APPLIED SYSTEM – SEAMS AND DETAILS



Membrane Damage $\leq 1/2$ "

• Patch with A+ Tape

Membrane Damage $\geq 1/2$ "

- Cover Damaged area with membrane
 Patch
- Overlap edges by 2"
- Seal and Bond Repair Patch with SikaProof Tape A+ on all sides.



1

SikaProof[®] A+ PRE-APPLIED SYSTEM – SEAMS AND DETAILS





WATERTIGHT BASEMENTS SikaProof® A+ PRE-APPLIED SYSTEM – SEAMS AND DETAILS









SikaProof[®] A+ PRE-APPLIED SYSTEM – SEAMS AND DETAILS





WATERTIGHT BASEMENTS SikaProof® A+ PRE-APPLIED SYSTEM – SEAMS AND DETAILS



2

4





WATERTIGHT BASEMENTS SikaProof® A+ SYSTEM – WALL APPLICATION



SikaProof[®] A+ PRE-applied

- Simply install the membrane on the vertical area
- Continuous application with the same material
- No compatibility concerns
- For exposure to constant water pressure
- Suitable for Shotcrete application



SikaProof[®] A+ POST-applied

- Green concrete application providing scheduling flexibility
- One membrane for pre- and post-application
- No compatibility concerns
- For exposure to constant water head pressure



25

WHERE TO USE SikaProof[®] Adhesive-22 WHY DO WE NEED A POST APPLIED SOLUTION

Existing situation / issues:

- Slab wall protrusion / footing
- Tunnel Lid (Cut/Cover)
- Vertical Horizontal Transitions



Drained Conditions (Above Water Table): SikaBit® S-60

or Sikalastic HLM 5000 GC



Below Water Table: SikaProof [®] A+ with SikaProof [®]

Adhesive-22





WATERTIGHT BASEMENTS SikaShield[®] S-60



SikaShield[®] S-60

Membrane roll:

3.0 ft x 66.7 ft (200 sqft)

Packaging:

- Single roll packaged
- Delivered on pallets

SikaShield[®] Primer AW

Primer:

1 gallon or 5 galon

Packaging:

Containers



Primer Application

- Apply the primer with a brush or roller on to cured and dry concrete
- Allow primer to dry (approx. 60 min)
- Reprime if area is contaminated by drust or other debris



SikaShield[®] S-60

- Cut the membrane at the required length
- Check if the primer is dry
- Take of the release liner
- Apply the membrane



WATERTIGHT BASEMENTS Sikalastic[®] HLM 5000 GC



What is Sikalastic HLM 5000 GC?

 A single component, bitumen-modified polyurethane waterproofing membrane

Key Attributes:

- Applies to green and damp concrete
- Roller Grade
- Low VOC & low odor
- Meets ASTM C836





BUILDING TRUST

WHERE TO USE SikaProof[®] Adhesive-22 WHY DO WE NEED A POST APPLIED SOLUTION



- Slab wall protrusion / footing
- Tunnel Lid (Cut/Cover)
- Vertical Horizontal Transitions



Drained Conditions (Above Water Table): SikaShield[®] S-60 or Sikalastic HLM 5000 GC



Below Water Table: SikaProof [®] A+ with SikaProof [®] Adhesive-22





WATERTIGHT BASEMENTS SikaProof[®] A+ POST-APPLIED – INSTALLATION



Adhesive Application

- Mix the **1-component adhesive** with water
- Apply adhesive on to green or cured concrete
- Evenly distribute the adhesive with a ¼ in v-notched trowel



Membrane Application

- Cut the membrane to the required length
- Roll the membrane sheet into the adhesive
 - Butt join the subsequent sheet

Seal the seam with the SikaProof[®] ExTape-100



WATERTIGHT BASEMENTS SikaProof[®] A+ SYSTEM COMPONENTS



SikaProof[®] A+ 12

Membrane rolls in two widths:

- 6.5 ft x 65.6 ft (430 sqft) / 2 m x 20 m (40 m²)
- 3.2 ft x 65.6 ft (215 sqft) / 1 m x 20 m (20 m²)



SikaProof[®] Adhesive-22

1-component adhesive

50 lbs bag



SikaProof[®] ExTape-100



WATERTIGHT BASEMENTS SikaProof[®] A+ POST-APPLIED – SPRAY INSTALLATION



SikaProof[®] Adhesive-22

+

2.2 gal of water



SPRAY APPLICATION



TexSpray FastFinish Pro System





WATERTIGHT BASEMENTS SikaProof® A+ SYSTEM – REFERENCE PROJECTS





WATERTIGHT BASEMENTS SikaProof® A+ SYSTEM – REFERENCE PROJECTS









NDA Project – Byhalia, MS





WATERTIGHT BASEMENTS SikaProof® A+ SYSTEM – REFERENCE PROJECTS



BUILDING TRUST

41













BUILDING TRUST

WATERTIGHT BASEMENTS LOW RISK PROJECTS



Drained Condition

- e.g. Water Drainage System

Low Head Pressure

Temporary Head Pressure Exposure

Limited Warranty - 10 year Material max.



WATERTIGHT BASEMENTS SikaProof[®]-808



PRE-Applied, SikaProof® -808

Membrane rolls in two widths:

6.5 ft x 82 ft (530 sqft) / 2 m x 25 m (50 m²)

Packaging:

Single roll packaged and delivered on pallets



- 1. Highly flexible FPO membrane
 - Thickness: 40 mil
- 2. <u>Adhesively</u> bonding layer
 - Only taped seams
- 3. Structural concrete



WATERTIGHT BASEMENTS SikaProof[®] 808 SYSTEM – WHAT IS IT?

- Flexible TPO based, pre-applied sheet membrane
- Fully Bonds to Fresh Concrete
- Overlapped and Taped Seams
- Fully Bonded System:
 - No Lateral Water Migration







SikaProof® 808 SYSTEM VS BENTONITE PANEL WATERPROOFING

BENTONITE PANEL WATERPROOFING

- Time Delayed Performance
- Must Be Replaced after Rain
- Reduced Swell from Salt Water
- Easily Damaged by Other Trades
- Requires Constant Water Contact
- Not a Vapor barrier
 - Not for Wet/Dry Cycling
- Does not Prevent Water from Migrating
- Up to 10 year Material Warranty



SIKAPROOF ®808

- Flexible TPO based, pre-applied sheet membrane
- Weather Resistant
 - Not Affected by Rain
 - 90 day UV Exposure
- Overlapped and Taped Seams
- Fully Bonded System:
 - No Lateral Water Migration
- Class A Vapor Barrier
- Up to 10 year Material Warranty



WATERTIGHT BASEMENTS SikaProof[®] A+ VS 808 SYSTEM

SIKAPROOF ®A+

- Flexible TPO based, pre-applied sheet membrane
- Fully Bonds to Fresh Concrete
- Overlapped and Taped Seams
- Fully Bonded System:
 - No Lateral Water Migration
- 1.75mm Thick
- Up to 20 year Material & Labor Warranty
- Resists up to 100psi Head Pressure
- Can be used as Post-Applied with Sikaproof 22 Adhesive
- Can be Hot-Air Welded



SIKAPROOF ®808

- Flexible TPO based, pre-applied sheet membrane
- Fully Bonds to Fresh Concrete
- Overlapped and Taped Seams
- Fully Bonded System:
 - No Lateral Water Migration
- 1mm Thick
- 10 year Material Only Warranty
- Drained and Low Head Pressure Applications
- Pre-Applied Only
- Can be used as Post-Applied with Sikaproof 22 Adhesive

NC TO

~40% less per sqft vs Sikaproof A+12

WATERTIGHT BASEMENTS ADDITIONAL PRODUCTS



Sika Greenstreak® PVC Waterstops

- Industry standard for flexible waterstops
- Broad design selection
- Accepted under ACI 350
- Excellent inherent elasticity
- Resistant to many waterborne chemicals



Sika Hydrotite

- Hydrophilic, strip-applied waterstop
- Comprised of modified chloroprene rubber (non-bentonite)
- Offered with an adhesive back
- Available in multitude of sizes and shapes

Sika Fuko VT-1/VT-2

Re-Injectable Grout Tube Hose composed of a perforated PVC Core surrounded by mesh to allow for Waterproofing Resins to be injected directly into the construction joint without needing to drill any ports



Leakmaster LV-Z

- 1-component water-swelling sealant
- Approx. 2 times in volume
- General-use caulking guns for application





STRIP APPLIED HYDROPHILIC RUBBER/ACRYLATE WATERSTOP (HYDROTITE)



- Swells upon contact w/ water to provide a compression seal
- Contains NO bentonite
- 2+" concrete coverage required VERIFY
- Durability Excellent
- Consider swell time & degree of swell for chemical applications
- Should not be specified as "equal" to bentonite waterstop









days of immersion

JOINT WATERPROOFING - INJECTABLE FUKO HOSE

- Solid Core PVC Hose
- Re-Injectable
 - Available in Single and Multi Injection Hoses
- No Additional Formwork Required
- Ideal for critical Applications
- Delivery System for Joint Waterproofing
 - Hose Itself is NOT a Waterstop





JOINT WATERPROOFING INJECTABLE FUKO HOSE



- Injection Materials:
 - Polyurethanes
 - Acrylate Resins
 - Microfine Cements
 - Epoxy Resins
- Not All Materials Are Suitable
 - Avoid Highly Viscous and Fast Curing Injection Materials
- Injection Materials Should Have Following Properties:
 - Curing Time Longer than 15-20 Minutes
 - Viscosity Lower than 200cps



WATERTIGHT BASEMENTS INJECTION CHALLENGES

CRACK INJECTION CURTAIN WALL INJECTION d/2 d/2 d

BUILDING TRUST

PU FOAMS - SIKAFIX HH+ AND SIKA INJECTION 101US

- Reacts with water and foams rapidly to seal leak path
- Expands approximately 35-40 times
- Expansion starts less than 20 seconds after contact with water
- Considered a temporary solution
- Should be used for active leaks with high water pressure

ACRYLATE RESINS - SIKAINJECT 215, 307 & 310US

- Set reaction time
- Does not need contact with water to react once mixed
- Very low viscosity similar to water
- Considered a permanent solution

Should be **NOT** used for active leaks with high water pressure

AVAILABLE SIKA WATERPROOFING INJECTION PRODUCTS

Polyurethane foams

- Sika[®]Fix HH, HH+, and HH LV Quick foaming material with homogeneous cell structure
- Sika[®] Injection-101 US Quick foaming material with homogeneous cell structure

Acrylic resins

- Sika[®] Injection-307: Flexible material, steel passivation
- Sika[®] Injection-310 US: 1-C-Powder based, Easy to use
- Sika[®] Injection-215: 2-15 min standard acrylate resin

ACRYLATE PRODUCTS LOCALLY PRODUCED IN AMERICAS

	SI-215	SI-307	SI-310 US
# Comp.	3	3	1 (Powder)
Reaction time	2-15 min	5-50 min	20 min @ RT
Note	Fast	Steel-passivating	All-in-one

THANK YOU FOR YOUR INTEREST IN SIKA PRODUCTS!

SikaProof[®] A+ Resource Center **BRUCE ZHU** Product Engineer – Waterproofing

SIKA CORPORATION 3400 Tree Court Industrial Blvd. St. Louis, MO 63122 United States

Mobile: +1 314-706-8259 Zhu.Bruce@us.sika.com· <u>usa.sika.com</u>

