



PRODUCT DATA SHEET

Sikacryl® Ready-Mix Stucco Patch

ACRYLIC-BASED, TEXTURED STUCCO PATCH FOR REPAIRING SPALLS/LARGE CRACKS IN STUCCO

PRODUCT DESCRIPTION

Sikacryl® Ready-Mix Stucco Patch is an easy to use, acrylic-based, textured stucco patch for repairing spalls and cracks in stucco that cures to a tough and durable finish.

USES

Sikacryl® Ready-Mix Stucco Patch can be used on a masonry surface, exterior finish, foundation, and more. Any location a stucco finish has been used.

CHARACTERISTICS / ADVANTAGES

- Easy to tool
- Textured to blend with stucco finish
- Easy water clean up
- Won't shrink or crack
- Paintable
- Moisture resistant
- Interior / Exterior use
- VOC Compliant

PRODUCT INFORMATION

Packaging	1 qt. (.94 L) plastic container, 12/case
Appearance / Color	off white
Shelf Life	12 months in original, unopened containers
Storage Conditions	Store away from extreme heat or cold. Store in original container between 40 to 90 °F (4 to 32 °C)

APPLICATION INFORMATION

Coverage	1 quart cover approximately 20 sq. ft. at 1/32 in. (.8 mm.)
Ambient Air Temperature	40 to 90 °F (4 to 32 °C)
Waiting Time / Overcoating	Tack Free: 2-4 hours Full Cure: Minimum of 1 day at 1/4 in. (6.3 mm) depth depending on temperature

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Surface should be clean, sound, dry, and free from dirt and loose particles. For best results, use a wire brush to clean off any loose particles or excess dirt or dust. Area to be repaired should accept moisture penetration.

MIXING

Stir material thoroughly until a uniform appearance and consistency is achieved prior to use.

APPLICATION

Use a putty knife or trowel to apply product to surface. Ensure that enough product is pushed into crack or hole to provide coverage. Tool as required. Areas greater than 1/4 in. (6.3 mm) deep will require two or more applications. For applications greater than 1/4 in. (6.3 mm) depth, allow the material to dry between applications. Apply at a minimum thickness of 1/32 in. (0.8 mm). Allow repaired area to dry and fully cure for at least 24 hours, depending on temperature, humidity and depth of repair.

CLEANING OF TOOLS

Clean tools immediately after use with water.

LIMITATIONS

- Substrate must be dry prior to application (minimum 48 h)
- Check color before using, will not change once cured
- Protect from freezing
- Do not apply at temperatures below 40 °F (4 °C)
- Allow the material to dry between applications
- Cracks or spalls deeper than 1/4 in. (6.3 mm), will require two or more applications
- Allow to dry before subjected to water
- Not recommended for areas exposed to vehicular traffic
- **Do not apply if rain is in the forecast**
- **Do not apply over 1/4 in. in one application**

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LOCAL RESTRICTIONS

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at <http://usa.sika.com/> or by calling Sika's Technical Service Department at 800.933.7452 nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instructions for each Sika product for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.

ECOLOGY, HEALTH AND SAFETY

Keep container tightly closed. Keep out of reach of children. Not for internal consumption. For industrial use only. For professional use only. For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety related data. Read the current actual Safety Data Sheet before using the product. In case of emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL NOTES

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at <http://usa.sika.com/> or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use. Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. No other warranties express or implied shall apply including any warranty of merchantability or fitness for a particular purpose. Sika shall not be liable under any legal theory for special or consequential damages. Sika shall not be responsible for the use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. Sale of Sika products are subject to Sika's terms and conditions of sale available at <http://usa.sika.com/> or by calling 201-933-8800.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225

Sika Canada Inc.

601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet
Sikacryl® Ready-Mix Stucco Patch
June 2018, Version 01.01
020405030010000094

SikacrylReady-MixStuccoPatch-en-US-(06-2018)-1-1.pdf

