

PRODUCT DATA SHEET

Sikafloor® SCO Color Additive

Concentrated Castor Oil Based Color Additives

PRODUCT DESCRIPTION

Sikafloor® SCO Color Additive concentrated castor oil based color additives for selected Sikafloor urethane floor coating products. Use only with Sikafloor- 316 N and Sikafloor- 511. Do not use with any other Sikafloor products.

USES

Sikafloor® SCO Color Additive Use as color additive in conjunction only with Sikafloor- 316 N and Sikafloor- 511.

CHARACTERISTICS / ADVANTAGES

100% solids; VOC compliant
Eliminates stability problems inherent in solvent based pigmented systems

PRODUCT INFORMATION

Packaging	Packaged in one quart metal can. 4 cans per carton	
Appearance / Color	Jet Black Traffic Blue Oxide Red Signal Yellow Light Gray Basalt Gray Beige Rose Raffia Beige Gray Beige	Signal White Pale Green Traffic Red Window Gray Traffic Gray Silver Gray Tan Beige
Shelf Life	24 months in original unopened container under proper storage conditions.	
Storage Conditions	Store dry between 40° - 90°F (4°- 32°C).	

APPLICATION INSTRUCTIONS

Refer Sikafloor- 316 N and Sikafloor- 511 for complete application instruction

LIMITATIONS

Refer Sikafloor- 316 N and Sikafloor- 511 for complete limitation instruction.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet

Sikafloor® SCO Color Additive
March 2020, Version 01.03
020816030020000001

SikafloorSCOCOLORAdditive-en-US-(03-2020)-1-3.pdf

