



PRODUCT DATA SHEET

DRYLOK® Non-skid

Pumice non-skid texture additive for oil, latex, and epoxy floor paints.

DESCRIPTION

DRYLOK® Non-skid increases traction and helps prevent slipping and falling by providing a slip resistant coating. For use with DRYLOK® E1 Latex 1-Part Epoxy Concrete Floor Paint and other oil, latex, or epoxy floor paints. DRYLOK® Non-skid will not change the drying characteristics or film thickness recommendation of the paint that it is added to. It will however alter the appearance of the surface by lowering the gloss due to the light scattering effect of the particles that will stick up out of the surface of the paint.

USES

- For use with:
- DRYLOK® E1 Latex 1-Part Epoxy Concrete Floor Paint
 - Oil, latex, and epoxy floor paints

CHARACTERISTICS / ADVANTAGES

- Lightweight aggregate additive to paint, does not settle to bottom
- Increase traction and help prevent falls, accidents and injuries

PRODUCT INFORMATION

Composition	Pumice				
Packaging	Size	PC/Case	Color	Order No.	Old Order No.
	4 oz.	6/case	off white	830821	01804

Shelf life	N/A
Storage conditions	Keep container closed when not in use. Store in a dry, well-ventilated place. Keep the container tightly closed when not in use.
Density	19.6 ± 0.1 LBS./US GAL.
Solid content	100%
Appearance	Off white - powder

APPLICATION INFORMATION

Coverage	2 oz.– 4 oz./gal. Note: Actual coverage will vary depending upon application method, surface texture, and porosity.
Drying time	Varies on usage

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

Add 4 oz. bottle to 1 gallon of any oil, latex based or epoxy floor paint. Pour powder into paint and mix thoroughly. For best results use a drill with a stirring blade. Stir thoroughly before and during application.

MIXING

CLEANING OF EQUIPMENT

Vacuum clean spillage. If sweeping, use a dust suppressant. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.



LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAM-**

AGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

PRODUCT DATA SHEET

DRYLOK® Non-skid

May 2025, Version 01.01

020816020020000016

