

# Revision Date 04/08/2025

Print Date 04/08/2025

# **SECTION 1. IDENTIFICATION**

Product name		Sarnacol <sup>®</sup> AD Adhesive Part 1
Company name	:	Sika Corporation
		201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

# **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Aerosols	:	Category 3
Acute toxicity (Inhalation)	:	Category 4
Skin irritation	:	Category 2
Eye irritation	:	Category 2A
Respiratory sensitization	:	Category 1
Skin sensitization	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure (Inhala- tion)	:	Category 2



Other hazards	
GHS label elements Hazard pictograms	
Signal Word	: Danger
Hazard Statements	<ul> <li>H229 Pressurised container: May burst if heated. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure if inhaled.</li> </ul>
Precautionary Statements	<ul> <li>Prevention:</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P251 Do not pierce or burn, even after use.</li> <li>P260 Do not breathe dusts or mists.</li> <li>P264 Wash skin thoroughly after handling.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P272 Contaminated work clothing must not be allowed out of the workplace.</li> <li>P280 Wear protective gloves/ eye protection/ face protection.</li> <li>P284 Wear respiratory protection.</li> </ul>
	<ul> <li>Response:</li> <li>P302 + P352 IF ON SKIN: Wash with plenty of water.</li> <li>P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.</li> <li>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P333 + P313 If skin irritation or rash occurs: Get medical advice attention.</li> <li>P337 + P313 If eye irritation persists: Get medical advice/ attention.</li> <li>P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.</li> <li>P362 + P364 Take off contaminated clothing and wash it before reuse.</li> </ul>



Revision Date 04/08/2025

Print Date 04/08/2025

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

## **Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

## **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%. None known.

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Mixtures**

#### Components

Chemical name	CAS No./Unique	Classification	Concentration
	ID		(% w/w)
Diphenylmethanediisocyanate, iso- meres and homologues	9016-87-9	Acute Tox. 4; H332 Skin Irrit. 2; H315	>= 80 - <= 100
meres and nomologues		Eye Irrit. 2B; H320	
		Resp. Sens. 1; H334	
		Skin Sens. 1; H317	
		STOT SE 3; H335	
		STOT RE 2; H373	
carbon dioxide	124-38-9		>= 3 - <= 7

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attend- ance.	
If inhaled	:	Move to fresh air.	
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.	
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing.	
2 / 12			



Revision Date 04/08/2025	Print Date 04/08/2025
If swallowed :	If eye irritation persists, consult a specialist. Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms : and effects, both acute and delayed	irritant effects sensitizing effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure if inhaled. Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis
Notes to physician :	Treat symptomatically.

# SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :	Use personal protective equipment.
tive equipment and emer-	Deny access to unprotected persons.
gency procedures	



Revision Date 04/08/2025	Print Date 04/08/2025
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
SECTION 7. HANDLING AND STOP	RAGE
Advice on protection against : fire and explosion	Normal measures for preventive fire protection.
Advice on safe handling :	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Provide sufficient air exchange and/or exhaust in work rooms.</li> <li>Follow standard hygiene measures when handling chemical products.</li> </ul>
Conditions for safe storage :	<ul> <li>BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 122 °F. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.</li> <li>Store in original container.</li> <li>Keep in a well-ventilated place.</li> <li>Observe label precautions.</li> <li>Store in accordance with local regulations.</li> </ul>

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Ingredients with workplace control parameters

CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
9016-87-9	С	0.02 ppm 0.2 mg/m3	OSHA Z-1
	С	0.02 ppm 0.2 mg/m3	OSHA P0
	TWA	0.005 ppm	ACGIH
124-38-9	TWA	5,000 ppm	ACGIH
	STEL	30,000 ppm	ACGIH
	TWA	5,000 ppm	OSHA Z-1
	9016-87-9	(Form of exposure) 9016-87-9 C C C TWA 124-38-9 TWA STEL	(Form of exposure)ters / Permissible concentration9016-87-9C0.02 ppm 0.2 mg/m3C0.02 ppm 0.2 mg/m3C0.02 ppm 0.2 mg/m3TWA0.005 ppm124-38-9TWA5,000 ppmSTEL30,000 ppm



#### Revision Date 04/08/2025

# Print Date 04/08/2025

	9,000 mg/m3	
TWA	10,000 ppm 18,000 mg/m3	OSHA P0
STEL	30,000 ppm 54,000 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures	:	Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend- ed or statutory limits.
Personal protective equipme	ent	
Respiratory protection	:	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.
		The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures	:	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance



# Revision Date 04/08/2025

Print Date 04/08/2025

Color	:	amber
Odor	:	aromatic
Odor Threshold	:	No data available
рН	:	not determined
	:	Not applicable
Boiling point/boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.01 hpa
Relative vapor density	:	No data available
Density	:	ca. 1.23 g/cm3 (68 °F / 20 °C)
Solubility(ies) Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Explosive properties	:	No data available
Oxidizing properties	:	No data available



## Revision Date 04/08/2025

Print Date 04/08/2025

Volatile organic compounds	:	32 g/l
(VOC) content		Part 1 + Part 2 Combined

# SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

# SECTION 11. TOXICOLOGICAL INFORMATION

<b>Acute toxicity</b> Harmful if inhaled.		
Components:		
<b>Diphenylmethanediisocyan</b> Acute oral toxicity		, <b>isomeres and homologues:</b> LD50 Oral (Rat): > 10,000 mg/kg
Acute inhalation toxicity	:	LC50: 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgment Assessment: The component/mixture is moderately toxic after short term inhalation.
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 9,400 mg/kg
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye irr Causes serious eye irritation.		ion
<u>Product:</u> Result	:	Irritation to eyes, reversing after 7 to 21 days.



#### Revision Date 04/08/2025

Print Date 04/08/2025

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### **Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data. IARC Not applicable

**OSHA** Not applicable

NTP Not applicable

#### **Reproductive toxicity**

Not classified due to lack of data.

#### STOT-single exposure

May cause respiratory irritation.

#### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure if inhaled. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### Aspiration toxicity

Not classified due to lack of data.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

**Components:** 

#### Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l
Persistence and degradabilit	у	

No data available

#### **Bioaccumulative potential**

No data available



# Sarnacol® AD Adhesive Part 1

Revision Date 04/08/2025	Print Date 04/08/2025			
Mobility in soil No data available Other adverse effects				
<b>Product:</b> Additional ecological infor- : mation	Do not empty into drains; dispose of this material and its con- tainer in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.			
Global warming potential				
Giodal warming Potentials - 40	Global Warming Potentials - 40CFR Part 98 -Table A-1 to SubPart A.			

#### **Components:**

# carbon dioxide:

100-year global warming potential: 1 Further information: Chemical-Specific GWPs

# Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

#### **Components:**

#### carbon dioxide:

20-year global warming potential: 1 100-year global warming potential: 1 500-year global warming potential: 1 Radiative efficiency: 0.000013 Wm2ppb Further information: Major Greenhouse Gases

## **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

## Revision Date 04/08/2025

Print Date 04/08/2025

IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)		UN 3500 Chemical under pressure, n.o.s. (carbon dioxide) 2.2 Not assigned by regulation Non-flammable, non-toxic Gas 218
IMDG-Code UN number Proper shipping name Class Packing group Labels EmS Code Marine pollutant Domestic regulation	:	UN 3500 CHEMICAL UNDER PRESSURE, N.O.S. (carbon dioxide) 2.2 Not assigned by regulation 2.2 F-C, S-V no
<b>49 CFR Road</b> UN/ID/NA number Proper shipping name Class Packing group Labels ERG Code Marine pollutant		UN 3500 Chemical under pressure, n.o.s. (carbon dioxide) 2.2 Not assigned by regulation NON-FLAMMABLE GAS 126 no

## Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# **SECTION 15. REGULATORY INFORMATION**

**TSCA** list

: All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.





#### Revision Date 04/08/2025

Print Date 04/08/2025

## CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	Skin corrosion or	n sensitization gan toxicity (single o	r repeated exposure)
SARA 313	5	nponents are subjec A Title III, Section 3	t to reporting levels es- 13:
	Diphenylme- thanediisocya- nate, isomeres and homologues	9016-87-9	>= 90 - <= 100 %
	4,4'- methylenediphe- nyl diisocyanate	101-68-8	< 0.1 %

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

#### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### **SECTION 16. OTHER INFORMATION**

## Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA P0 / C	:	Ceiling limit

#### Revision Date 04/08/2025

Print Date 04/08/2025

OSHA Z-1 / TWA OSHA Z-1 / C 8-hour time weighted average Ceiling

## Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 04/08/2025

100000064411 US / Z8

