

## PRODUCT DATA SHEET

# Sikalastic®-600 Accelerator

Single component, low viscosity, accelerating agent for Sikalastic® -600 series resins

### PRODUCT DESCRIPTION

Sikalastic®-600 Accelerator is a single component, low viscosity, accelerating agent that enhances the moisture triggered curing characteristics of Sikalastic® -600 series saturating resins for roofing and waterproofing applications.

### USES

Suitable for use with all Sikalastic® -600 series saturating resins

### CHARACTERISTICS / ADVANTAGES

- Reduces cure time of single component Sikalastic® -600 series saturating resins
- Allows more rapid return to service
- Avoids project delays due to lower application temperatures

### PRODUCT INFORMATION

<b>Packaging</b>	4 fl. oz. bottles (6 bottles per carton)
<b>Shelf Life</b>	24 months
<b>Storage Conditions</b>	Store dry between 40 °F and 95 °F (4–35 °C). Condition material to 65–85 °F (18–30 °C) before using
<b>Appearance / Color</b>	Clear
<b>Density</b>	0.87
<b>Viscosity</b>	100 +/- 50 cps. (at 75 °F (24 °C) and 50 % R.H.)
<b>Volatile organic compound (VOC) content</b>	0 g/L (ASTM D-2369-81)

### APPLICATION INFORMATION

<b>Mixing Ratio</b>	Accelerator to Resin 1:160 (0.625 %)
<b>Pot Life</b>	Mixed Resin: 45 minutes (at 75 °F (24 °C) and 50 % R.H.)

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## LIMITATIONS

- Precautions must be taken to prevent vapors and/or odors from entering the building/structure, including but not limited to turning off and sealing air intake vents and through-wall air conditioners, and other means of vapor/odor ingress during resin application and cure
- Do not store materials outdoors directly exposed to sunlight and moisture. Cover and protect materials with breathable type covers such as canvas tarpaulins to allow venting and protection from weather and moisture. Observe temperature storage and conditioning requirements

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## APPLICATION INSTRUCTIONS

### MIXING

Thoroughly mix Sikalastic®-600 Accelerator into Sikalastic® RoofPro resin using a low speed (400–600 rpm) drill with mechanical mixer (Jiffy) at slow speed until a homogenous mixture and uniform color is obtained (typically 1 minute). Use care not to allow the entrapment of air into the mixture.

## OTHER RESTRICTIONS

See Legal Disclaimer.

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
usa.sika.com



Product Data Sheet  
Sikalastic®-600 Accelerator  
April 2024, Version 01.04  
020915953000000003

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sikalastic-600Accelerator-en-US-(04-2024)-1-4.pdf

