



PRODUCT DATA SHEET

SikaBond®-900 Tongue & Groove Flooring Adhesive

Tongue & Groove Flooring Adhesive

PRODUCT DESCRIPTION

SikaBond®-900 Tongue & Groove Flooring Adhesive is a premium wood glue that is specifically formulated for all types of laminate and floating wood floors. SikaBond®-900 Tongue & Groove Flooring Adhesive can also be used over radiant heat systems. It provides a superior bond at the tongue and groove. Tongue & Groove Flooring Adhesive is white in color, which makes it easy to see for quick cleanup. It is non-toxic and nonflammable, making it safe to use and environmentally friendly. SikaBond®-900 Tongue & Groove Flooring Adhesive gives the professional installer a very high level of protection against potential moisture problems, while maintaining a strong superior bond.

USES

- Multi-Ply Engineered Plank
- Laminate

PRODUCT INFORMATION

Packaging	16 oz. Bottle: Spread rate is 100-150 lineal ft. per 16 oz. bottle
Shelf Life	12 months in original, unopened container
Storage Conditions	Store at 40 to 95 °F (4 to 35 °C). Condition material to 65 to 75 °F (18 to 24 °C) before using. Keep from freezing. Freezing may not affect the function of the product but may cause it to thicken. Agitation should restore product to original form.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS

- SikaBond®-900 Tongue and Groove Adhesive passes Type II water-resistance tests
- Do not use for joints below the waterline or continuous submersion. Do not use when temperature, glue or materials are below 55°F
- Remove excess glue from surface while wet. Do not allow glue to dry as it will be difficult to remove
- Installers should provide adequate cross-ventilation during and for 24 hours after installation
- Keep from freezing
- Keep out of reach of children
- Avoid contact with skin, eyes and clothing. Wash thoroughly after handling
- Avoid breathing vapors. Use only with adequate ventilation. Harmful if swallowed, seek medical attention immediately
- In case of eye contact, flush thoroughly with water for at least 15 minutes. SEEK IMMEDIATE MEDICAL ATTENTION
- In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION
- Remove and wash all contaminated clothing
- If inhalation causes physical discomfort, remove to fresh air. If discomfort persists, SEEK MEDICAL ATTENTION

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

APPLICATION

Always follow the wood flooring manufacturer's directions for the use of their products. SikaBond®-900 Tongue and Groove Adhesive and all materials should be above 55°F with normal humidity conditions.

SikaBond®-900 Tongue and Groove Adhesive can be installed using the continuous bead method. When using this method, a water-resistant joint is created. Follow the flooring manufacturer's directions for proper positioning of the adhesive bead. Some manufacturer's prefer gluing the top of the tongue and others prefer gluing of the groove. SikaBond®-900 Tongue and Groove Adhesive is the professional installer's choice for either method.

These directions are general guidelines for tongue and groove installations. It is the responsibility of the installer to determine acceptability of subfloor conditions. Installation must also be in accordance with flooring manufacturer's recommendations. Only items that are approved for floating floor installations by the flooring manufacturer can be used with SikaBond®-900 Tongue and Groove Adhesive. Floors installed with SikaBond®-900 Tongue and Groove Adhesive are not warranted against damage caused by wet mopping, flooding, plumbing leaks or other extraordinary circumstances. For any installation not herein recommended, contact Sika Technical Service before proceeding.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

SikaBond®-900 Tongue & Groove Flooring Adhesive
November 2023, Version 01.02
020512900000000004

SikaBond-900TongueGrooveFlooringAdhesive-en-US-(11-2023)-1-2.pdf

