



# MATERIAL SAFETY DATA SHEET

Page 1 of 4

## SikaWrap Hex 106G

### HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

### 1. Product And Company Identification

<b>Supplier</b> SIKA CORPORATION 201 Polito Ave Lyndhurst, NJ 07071  Company Contact: Kristin Kelley Telephone Number: (201) 933-8800 FAX Number: (201) 933-9379 Web Site: www.sikausa.com	<b>Manufacturer</b> SIKA CORPORATION 201 Polito Ave Lyndhurst, NJ 07071  Company Contact: Kristin Kelley Telephone Number: (201) 933-8800 FAX Number: (201) 933-9379 Web Site: www.sikausa.com
<b>Supplier Emergency Contacts &amp; Phone Number</b> CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887	<b>Manufacturer Emergency Contacts &amp; Phone Number</b> CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887

Issue Date: 04/10/2002

Product Name: SikaWrap Hex 106G  
CAS Number: Not Established  
Chemical Family: Stitch-bonded heat-set fiberglass fabric  
MSDS Number: 2498  
Product Code: 332-XXX

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
Fiberglass, synthetic vitreous fibers	65997-17-3	

### 3. Hazards Identification

#### Primary Routes(s) Of Entry

#### Eye Hazards

MAY BE A MECHANICAL EYE IRRITANT.

#### Skin Hazards

MAY CAUSE MECHANICAL IRRITATION TO THE SKIN AND POSSIBLE DERMITITIS.

#### Ingestion Hazards

VERY UNLIKELY. IF LARGE AMOUNT IS SWALLOWED SEEK MEDICAL ATTENTION.

#### Inhalation Hazards

MAY CAUSE MECHANICAL IRRITATION TO THE UPPER RESPIRATORY TRACT.

## SikaWrap Hex 106G

### 3. Hazards Identification - Continued

#### Chronic/Carcinogenicity Effects

#### Conditions Aggravated By Exposure

PERSONS WITH CHRONIC RESPIRATORY OR SKIN CONDITIONS THAT ARE AGGAVATED BY IRRATANTS MAY BE AT INCREASED RISK FROM EXPOSURE TO THIS PRODUCT.

### 4. First Aid Measures

#### Eye

RINSE EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN.

#### Skin

WASH AFFECTED AREA WITH SOAP AND WATER. USE A WASH CLOTH TO HELP REMOVE THE FIBERS. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

#### Ingestion

IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY.

#### Inhalation

REMOVE TO FRESH AIR AND SUPPORT BREATHING AS NECESSARY. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.

### 5. Fire Fighting Measures

**Flash Point:** N/AV °F

#### Fire And Explosion Hazards

AVOID EXPOSURE THROUGH USE OF A SELF-CONTAINED, POSITIVE PRESSURE BREATHING APPARATUS.

#### Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

#### Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

### 6. Accidental Release Measures

AVOID CONTACT WITH SKIN, EYES, OR CLOTHING. CLEAN UP MATERIAL, PUT INTO SUITABLE CONTAINER AND DISPOSE OF PROPERLY.

### 7. Handling And Storage

#### Handling And Storage Precautions

STORE IN A COOL, DRY AREA. MAINTAIN SEALED AGAINST CONTAMINATION FROM DIRT AND MOISTURE.

#### Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use with adequate ventilation.

#### Eye/Face Protection

Safety glasses with side shields or goggles.

## SikaWrap Hex 106G

### 8. Exposure Controls/Personal Protection - Continued

#### Skin Protection

WEAR PROTECTIVE CLOTHING SUCH AS LOOSE FITTING CLOTHING, LONG SLEEVED SHIRT THAT COVERS TO THE BASE OF THE NECK. LONG PANTS AND GLOVES AS NECESSARY TO PREVENT IRRITATION. SKIN IRRITATION IS KNOWN TO OCCUR PRIMARILY AT PRESSURE POINTS SUCH AS AROUND NECK, WRIST, WAIST, AND BETWEEN FINGERS.

#### Respiratory Protection

In areas where the P.E.L.s are exceeded, use a properly fitted NIOSH-approved respirator.

#### Other/General Protection

WASH THOROUGHLY AFTER HANDLING. USE VACUUM EQUIPMENT TO REMOVE FIBERS AND DUST FROM CLOTHING AND WORK AREAS. COMPRESSED AIR IS NOT RECOMMENDED.

#### Ingredient(s) - Exposure Limits

Fiberglass, synthetic vitreous fibers  
 OSHA PEL: 15 mg/m<sup>3</sup> (TOTAL)  
           : 5 mg/m<sup>3</sup> (RESP DUST)  
 ACGIH TLV: 1 f/cc (TOTAL)  
           : 5 mg/m<sup>3</sup> (RESP DUST)

### 9. Physical And Chemical Properties

#### Appearance

WHITE FIBERS WOVEN INTO FABRICS OF VARYING WEIGHT, WIDTH, AND THICKNESS.

#### Odor

NO DISTINCTIVE ODOR.

**Chemical Type:** Mixture

**Physical State:** Solid

**Melting Point:** 1292 °F 700 °C

**Specific Gravity:** 2.60

**Vapor Pressure:** N/AV

**Vapor Density:** N/AV

**pH Factor:** NOT DETERMINED

**Solubility:** INSOLUBLE

### 10. Stability And Reactivity

**Stability:** STABLE

**Hazardous Polymerization:** WILL NOT OCCUR

#### Conditions To Avoid (Stability)

RAPID HEATING OF THE PRODUCT IN BULK MAY PRODUCE AN UNCONTROLLED EXOTHERMIC REACTION WHICH MAY CHAR AND DECOMPOSE GENERATING UNIDENTIFIED GASES AND VAPORS WHICH MAY BE TOXIC. AVOID INHALATION.

#### Incompatible Materials

NONE KNOWN

#### Hazardous Decomposition Products

CO, CO<sub>2</sub>, WATER, AND OTHER TOXIC GASES.

### 11. Toxicological Information

# MATERIAL SAFETY DATA SHEET

Page 4 of 4

## SikaWrap Hex 106G

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

### 14. Transport Information

#### Proper Shipping Name

NOT REGULATED BY D.O.T.

### 15. Regulatory Information

#### U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### SARA Hazard Classes

Acute Health Hazard

#### SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

#### Canadian Regulatory Information

NONE

### 16. Other Information

#### HMIS Rating

Health: 1

Fire: 0

Reactivity: 0

PPE: B

#### Revision/Preparer Information

This MSDS Supercedes A Previous MSDS Dated: 01/21/2002

### Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION