

## PRODUCT DATA SHEET

# Sikagard<sup>®</sup>-375 Mat

Textured and porous matting for surface protection.



### PRODUCT DESCRIPTION

Sikagard-375 Mat is a porous, non-woven PVC mat. This product is easily customizable and ready-to-use as a floor covering for both interior and outdoor spaces.

### USES

- Surface protection
- Steps, walkways, entryways
- Patio spaces
- Pool decks

### CHARACTERISTICS / ADVANTAGES

- Easy to install and maintain
- Can be trimmed for custom installations
- Porous to prevent, damming or ponding water
- Minimizes re-tracking into the building
- UV Resistant

### APPROVALS / STANDARDS

- Certified to National Floor Safety Institute (NFSI) as providing "High-Traction".
- Passed NFSI B101.1
- Passed NFSI B101.3

### PRODUCT INFORMATION

Packaging	<u>Mat</u>	
	▪ 4ft x 3ft pads	
	<u>Rolls</u>	
	▪ 4.5ft x 10ft rolls	
Appearance / Color	Black	
Shelf Life	n/a	
Storage Conditions	n/a	
Overall Thickness	3/8" nominal thickness	
Microbiological Resistance	No Growth	(ASTM G-22)

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage, and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological, and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

### APPLICATION METHOD / TOOLS

#### Sikagard-375 Mat - Roll

Sikagard-375 Mat may be slightly curled on the ends when first unrolled. If this occurs, allow the mat to lay flat and relax. Roll the matting out a few hours prior to the installation. A utility knife can be used to carefully cut Sikagard-375 Mat. To avoid any frayed edges, it may be necessary to score the material, cut twice, before pulling the two pieces apart. Hold the knife at a 90° angle to ensure a clean straight edge.

Sikagard-375 Mat can be left loose as runners for applications such as pool decks, locker rooms, restrooms, or shower areas. It may also be secured to a surface with the use of a specialty adhesive or screws if necessary.

#### Cleaning

Sikagard-375 Mat does not require any maintenance. Proper surface preparation and installation ensure a maintenance-free area. Dirt and debris may be flushed from the pad or roll by using a power spray or water hose.

## OTHER RESTRICTIONS

See Legal Disclaimer.

#### **Sika Corporation**

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
usa.sika.com

#### **Sika Mexicana S.A. de C.V.**

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



#### **Product Data Sheet**

Sikagard®-375 Mat  
March 2021, Version 01.03  
020720102000000011

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sikagard-375Mat-en-US-(03-2021)-1-3.pdf

