

PRODUCT DATA SHEET

Sikafloor® Urethane Pigment Pack

CONCENTRATED COLOR ADDITIVE FOR URETHANES

PRODUCT DESCRIPTION

Sikafloor® Urethane Pigment Pack used with urethane floor coating products. Refer to the individual PDS for proper quantity and mixing instructions.

USES

Use as color additive in conjunction with Sikafloor® urethane floor coating products. Compatible with the following products:

- Sikafloor®-315
- Sikafloor®-340
- Sikafloor®-510 LPL
- Sikafloor®-521
- Sikafloor®-521 LS
- Sikafloor® TC 421

CHARACTERISTICS / ADVANTAGES

- Color matched to Sikafloor-264 standard colors and Sikafloor Epoxy Pigment Packs

PRODUCT INFORMATION

Packaging	Packaged in one quart metal can. Carton contains 4 cans.
Color	<ul style="list-style-type: none">▪ Agate Gray▪ Basalt Gray▪ Beige▪ Beige Rose▪ Gray Beige▪ Jet Black▪ Light Gray▪ Oxford Gray▪ Oxide Red▪ Pale Green▪ Raffia Beige▪ Signal White▪ Signal Yellow▪ Silver Gray▪ Tan 251▪ Traffic Blue▪ Traffic Gray▪ Traffic Red▪ Window Gray▪ Custom Color is available
Shelf Life	12 months in original unopened container under proper storage conditions.
Storage Conditions	Store dry between 40° - 90 °F (4° - 32 °C)

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

USES

Mixing: Do not hand mix Sikafloor® materials. Mechanically mix only.

Do not thin this product. Addition of thinners (e.g. water, solvent, etc.) will slow cure and reduce ultimate properties of this product. Use of thinners will void any applicable Sika warranty.

- Do not use Sikafloor® Urethane Pigment Pack in any other Sikafloor® products other than those listed or products of other manufacturers.
- Do not use thinners or solvents of any type. Use of solvent thinners will void warranty.
- Use of more color additive than recommended will result in changes in cure times and other physical properties. Do not exceed the recommended amount of color additive.
- For professional use only by experienced and properly trained applicators.
- Refer to the individual PDS for proper quantity and mixing instructions.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service

Department at 1-800-933-7452. Nothing contained in any Sika literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each Sika product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the Sika product.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Sika SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. Sika SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of Sika products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

Sikafloor® Urethane Pigment Pack
October 2025, Version 01.01
020816030010000024

SikafloorUrethanePigmentPack-en-US-(10-2025)-1-1.pdf

