

PRODUCT DATA SHEET

BMI Fog Coat

CEMENTITIOUS FOG COAT



PRODUCT DESCRIPTION

BMI Fog Coat provides a durable and long lasting appearance to an existing Exterior Stucco Finish. BMI Fog Coat is formulated with Portland cement, Hydrated Lime and color pigments.

USES

Used to refresh or change color of existing stucco

CHARACTERISTICS / ADVANTAGES

Raw materials meet or exceed the following standards:

- Hydrated Type-S Lime: ASTM C-206
- White Portland Cement: ASTM C-150 Type I

PRODUCT INFORMATION

Packaging	27 lb (12.2 kg) bag
Shelf Life	6 months from date of production if stored properly in original, unopened and undamaged sealed packaging
Storage Conditions	Store dry at 40–95 °F (4–35 °C). Protect from moisture. If damp, discard material

APPLICATION INFORMATION

Mixing Ratio	10 gal (37.9 L)
Coverage	700–900 ft ³ per bag (Coverage figures do not include allowance for surface profile and porosity or material waste)
Waiting Time / Overcoating	BMI Fog Coat is NOT to be used over a painted or sealed Stucco surface.

APPLICATION INSTRUCTIONS

MIXING

- Mix a bag of BMI Fog Coat to 5 gal (19 L) of potable water thoroughly.
- Add another 5 gal (19 L) of water, mix and let stand 5 to 10 minutes.
- Mix thoroughly and strain through a suitable strainer when pouring into sprayer.
- Mix material often to avoid separation during application.

APPLICATION

- Apply BMI Fog Coat using a hand pump contractor compressed tank sprayer.
- When applying use a circular motion holding the sprayer nozzle 14" to 18" (356–457 mm) away from the structure (DO NOT let puddle).
- In some cases, 2 coats may be needed for complete coverage.

CLEANING OF TOOLS

Immediately after drying, BMI Fog Coat overspray should be cleaned off to prevent staining of painted and trim windows.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LOCAL RESTRICTIONS

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at <http://usa.sika.com/> or by calling Sika's Technical Service Department at 800.933.7452 nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instructions for each Sika product for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.

ECOLOGY, HEALTH AND SAFETY

Keep container tightly closed. Keep out of reach of children. Not for internal consumption. For industrial use only. For professional use only. For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety related data. Read the current actual Safety Data Sheet before using the product. In case of emergency, call CHEMTREC at 1-800-

424-9300, International 703-527-3887.

DIRECTIVE 2004/42/CE - LIMITATION OF EMISSIONS OF VOC

0 g/l

(EPA method 24)

LEGAL DISCLAIMER

KEEP CONTAINER TIGHTLY CLOSED •KEEP OUT OF REACH OF CHILDREN •NOT FOR INTERNAL CONSUMPTION •FOR INDUSTRIAL USE ONLY •FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.** Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 201-933-8300.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

BMI Products of Northern California Inc.
990 Ames Avenue
Milpitas, CA 95035-6303
Phone: (408) 293-4008
Fax: (408) 293-4103



Product Data Sheet
BMI Fog Coat
August 2018, Version 01.01
020405020010000108

BMIFogCoat-en-USBMI-(08-2018)-1-1.pdf

