

PRODUCT DATA SHEET

Sikalastic®-500 Accelerator

Accelerating Agent for Sikalastic®-500 Silicon Roof Coating

PRODUCT DESCRIPTION

Sikalastic®-500 Accelerator is a single component accelerating agent for Sikalastic®-500 silicone coating. It enhances the moisture curing characteristics that accelerates the cure time.

USES

Accelerating agent for Sikalastic®-500 silicone coating

CHARACTERISTICS / ADVANTAGES

The addition of accelerator can shorten cure time of Sikalastic® -500 by 50 %. (dependent on application conditions)

PRODUCT INFORMATION

Packaging	1/2 pint (0.2 L) can
Shelf Life	12 months
Storage Conditions	The product must be stored properly in original, unopened and undamaged sealed packaging in dry conditions at temperatures between 40 °F and 95 °F. Higher storage temperatures may reduce shelf life of product. Reference shall also be made to the storage recommendations within the safety data sheet.
Appearance / Color	Light Yellow

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of

APPLICATION INSTRUCTIONS

MIXING

Add accelerator to Sikalastic®-500 at a rate of 1 can per 5 gal. pail. Use mechanical mixer and Jiffy Paddle at slow speed (300–600 rpm) and thoroughly mix until a homogenous mixture and uniform color is obtained (typically 3 minutes). Use care not to allow the entrapment of air into the mixture. Sikalastic®-500 Accelerator is packaged with nitrogen to keep latent moisture from prematurely starting the curing process. After opening and catalyzing the Sikalastic®-500 Accelerator it becomes much more sensitive to moisture and the entire container must be used in a relatively short period of time.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
Sikalastic®-500 Accelerator
April 2024, Version 01.02
020915953000000006

Sikalastic-500Accelerator-en-US-(04-2024)-1-2.pdf

