



Version 1.0	Revision Date: 09/18/2020		DS Number: 00000936410	Date of last issue: - Date of first issue: 09/18/2020
SECTIO	ON 1. IDENTIFICATION			
Pro	oduct name	:	Sikalastic TC 295 base PTA	tintbase Part A Formerly MSeal TC 295 tint
Pro	oduct code	:	00000000005066	60007
Ма	nufacturer or supplier's	deta	ails	
Co	mpany name of supplier	:	Sika MBCC US L	LC
Ad	dress	:	201 POLITO AVE Lyndhurst NJ 070	-
Err	ergency telephone	:	ChemTel: +1-813	-248-0585
Re	commended use of the	chen	nical and restriction	ons on use
Re	commended use	:	Product for const	ruction chemicals
Re	strictions on use	:	Reserved for indu	ustrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200						
Serious eye damage/eye irritation	:	Category 2A				
Skin sensitization	:	1A				
Short-term (acute) aquatic hazard	:	3				
Long-term (chronic) aquatic hazard	:	3				
Carcinogenicity (Inhalation)	:	1A				
GHS label elements						
Hazard pictograms	:					
Signal Word	:	Danger				
Hazard Statements	:	H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H350 May cause cancer. H402 Harmful to aquatic life.				

Sikalastic TC 295 tintbase Part A Formerly **MSeal TC 295 tint base PTA**



/ersion .0	Revision Date: 09/18/2020	SDS Number: 000000936410	Date of last issue: - Date of first issue: 09/18/2020			
		H412 Harmful t	o aquatic life with long lasting effects.			
Precautionary Statements		 Prevention: P280 Wear protective gloves/ protective clothing/ eye protection face protection. P201 Obtain special instructions before use. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P202 Do not handle until all safety precautions have been read and understood. P273 Avoid release to the environment. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash face, hands and any exposed skin thoroughly after handling. 				
		for several minuto to do. Continue P308 + P311 IF CENTER/ docto P303 + P352 IF and water. P362 + P364 T reuse.	 exposed or concerned: Call a POISON or. ON SKIN (or hair): Wash with plenty of soap ake off contaminated clothing and wash it before eye irritation persists: Call a POISON CENTER 			
		Storage: P405 Store loc	ked up.			
		Disposal: P501 Dispose o waste collection	of contents/container to appropriate hazardous n point.			
Other	[·] hazards					

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: No applicable information available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Aspartic acid, N,N'-(methylenedi-4,1- cyclohexanediyl)bis-, 1,1',4,4'- tetraethyl ester	136210-30-5	>= 25 - < 50
Limestone	1317-65-3	>= 15 - < 50
talc	14807-96-6	>= 5 - < 15
Barium sulfate	7727-43-7	>= 5 - < 10
Diethyl fumarate	623-91-6	>= 0 - < 3
calcium oxide	1305-78-8	>= 1 - < 3



Sikalastic TC 295 tintbase Part A Formerly MSeal TC 295 tint base PTA

Version 1.0	Revision Date: 09/18/2020		S Number: 000936410		e of last issue: - e of first issue: 09/18/2020
	(1,2,2,6,6-pentamethyl-4- eridyl)sebacate		41556-26-7		>= 0.3 - < 1
	thyl 1,2,2,6,6-pentamethyl- eridyl sebacate	4-	82919-37-7		>= 0.2 - < 0.3
Qu	artz (SiO2)		14808-60-7		>= 0 - < 1
SECTIC	ON 4. FIRST AID MEASUR	ES			
Ge	neral advice	;	Move out of dang Show this materia ance. Do not leave the	al safe	ety data sheet to the doctor in attend-
lf ir	nhaled	;	If unconscious, p advice. If symptoms pers		n recovery position and seek medical II a physician.
In d	case of skin contact	:	lf on skin, rinse w	ell wit	h water.
In o	case of eye contact		Remove contact Protect unharmed Keep eye wide op	lenses d eye. ben wi	
lf s	wallowed		Keep respiratory Do not give milk (tract o or alco ing by ist, ca	bholic beverages. mouth to an unconscious person. Il a physician.
and	st important symptoms d effects, both acute and ayed	(May cause an all Causes serious e May cause cance	ye irri	
No	tes to physician	: '	Treat symptomat	ically.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Foam Dry powder Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Further information	:	Collect contaminated fire extinguishing water separately. This

Sikalastic TC 295 tintbase Part A Formerly MSeal TC 295 tint base PTA



Version 1.0	Revision Date: 09/18/2020		DS Number: 0000936410	Date of last issue: - Date of first issue: 09/18/2020
			Fire residues and	harged into drains. d contaminated fire extinguishing water must n accordance with local regulations.
•	ial protective equipment e-fighters	:	Wear self-contai essary.	ned breathing apparatus for firefighting if nec-
SECTION	6. ACCIDENTAL RELE	AS	E MEASURES	
tive e	onal precautions, protec- quipment and emer- y procedures	:	Use personal pro	otective equipment.
Envir	onmental precautions	:	Prevent further le	from entering drains. eakage or spillage if safe to do so. ntaminates rivers and lakes or drains inform rities.
	ods and materials for inment and cleaning up	:	acid binder, univ	rt absorbent material (e.g. sand, silica gel, ersal binder, sawdust). closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Conditions for safe storage	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Further information on stor- age conditions	•	Keep only in the original container in a cool, dry, well- ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.



Sikalastic TC 295 tintbase Part A Formerly MSeal TC 295 tint base PTA

Version 1.0	Revision Date: 09/18/2020	SDS Number:Date of last issue: -000000936410Date of first issue: 09/18/2020	
Mater	ials to avoid	: No applicable information available.	
	er information on stor- tability	: No data available	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
calcium oxide	1305-78-8	TWA value	2 mg/m3	ACGIHTLV
		REL value	2 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respir- able fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respir- able fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respir- able dust fraction)	5 mg/m3	OSHA P0
		TWA (Res- pirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL



sion	Revision Date: 09/18/2020	SDS Number: 000000936410	Date of las Date of firs	t issue: - t issue: 09/18/2020	
			TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH RE
Bariur	m sulfate	7727-43-7	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTL\
			REL value (Respirable)	5 mg/m3	NIOSH
			REL value (Total)	10 mg/m3	NIOSH
			PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
			PEL (Respir- able fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
			TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
			TWA (Res- pirable)	5 mg/m3	NIOSH RE
			TWA (total)	10 mg/m3	NIOSH RE
			TWA (total dust)	15 mg/m3	OSHA Z-1
			TWA (respir- able fraction)	5 mg/m3	OSHA Z-1
			TWA (Total dust)	10 mg/m3	OSHA P0
			TWA (respir- able dust fraction)	5 mg/m3	OSHA P0
talc		14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
			TWA (Dust)	20 Million parti- cles per cubic foot	OSHA Z-3
			TWA (respir- able dust fraction)	2 mg/m3	OSHA P0
			TWA (Res- pirable)	2 mg/m3	NIOSH RE
			TWA	0.1 fibres per cubic centimeter	ACGIH
			TWA (Res- pirable par- ticulate mat- ter)	2 mg/m3	ACGIH
Quart	z (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
_			TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001



		SDS Number: 000000936410	Date of las Date of firs	t issue: - t issue: 09/18/2020	
					1050
			OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
			REL value (Respirable dust)	0.05 mg/m3	NIOSH
			TWÁ (Res- pirable dust)	0.05 mg/m3	OSHA Z-1
			TWA (respir- able)	10 mg/m3 / %SiO2+2	OSHA Z-3
			TWA (respir- able)	250 mppcf / %SiO2+5	OSHA Z-3
			TWA (respir- able dust fraction)	0.1 mg/m3	OSHA P0
			TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
			PEL (respir- able)	0.05 mg/m3	OSHA CARC
			TWA (Res- pirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

Engineering measures	:	No applicable information available.

Personal protective equipmen	t
Respiratory protection :	When workers are facing concentrations above the occupa- tional exposure limits they must use appropriate certified respirators.
Hand protection	
Remarks :	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection :	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection :	Impervious clothing Choose body protection according to the amount and con- centration of the dangerous substance at the work place.
Protective measures :	Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended.



Vers 1.0	sion	Revision Date: 09/18/2020		S Number: 0000936410	Date of last issue: - Date of first issue: 09/18/2020
	Hygien	e measures	:	When using do ne When using do ne Wash hands befo	
SEC	CTION 9	. PHYSICAL AND CHI	EMIC	CAL PROPERTIE	S
	Appea	rance	:	slurry	
	Color		:	off-white	
	Odor		:	faint odour	
	Odor T	hreshold	:	No data available	e
	рН		:	No data available	e
	Melting	j point	:	No applicable inf	formation available.
	Boiling	point	:	No data available	e.
	Flash p	point	:	323.60 °F / 162.0	0° 00
	Evapor	ration rate	:	No applicable inf	formation available.
	Flamm	ability (solid, gas)	:	not flammable	
	Self-ig	nition	:	not self-igniting	
		explosion limit / Upper ability limit	:	No applicable inf	formation available.
		explosion limit / Lower ability limit	:	No applicable inf	formation available.
	Vapor	pressure	:	No applicable inf	formation available.
	Relativ	e vapor density	:	No applicable inf	formation available.
	Relativ	e density	:	No applicable inf	formation available.
	Density	4	:	1.505 - 1.519 g/d	cm3 (68 °F / 20 °C)
	Solubil Wa	ity(ies) ter solubility	:	No data availabl	e
	Sol	ubility in other solvents	:	No applicable inf	formation available.
	Partitio octano	n coefficient: n- I/water	:	No applicable inf	formation available.





Version 1.0	Revision Date: 09/18/2020		S Number: 0000936410	Date of last issue: - Date of first issue: 09/18/2020
Autoi	gnition temperature	÷	No applicable in	formation available.
Deco	mposition temperature	: No decomposition if stored and handled as pre- scribed/indicated.		•
Visco	5			
Vi	scosity, dynamic	:	No applicable in	formation available.
Vi	scosity, kinematic	:	No applicable in	formation available.
Oxidi	zing properties	: Based on its structural properties the product as oxidizing.		actural properties the product is not classified
Subli	mation point	:	: No applicable information available.	
Mole	cular weight	: No data available		e

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reac- tions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	See SDS section 7 - Handling and storage.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks

: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Sikalastic TC 295 tintbase Part A Formerly MSeal TC 295 tint base PTA



Version 1.0	Revision Date: 09/18/2020	SDS Number: 000000936410	Date of last issue: - Date of first issue: 09/18/2020
	oduct: emarks	: May cause irrev	versible eye damage.
Re	spiratory or skin sensitiz	zation	
	in sensitization ay cause an allergic skin re	action.	
	espiratory sensitization at classified based on availa	able information.	
	oduct: emarks	: Causes sensitiz	zation.
	erm cell mutagenicity at classified based on availa	able information.	
	r cinogenicity ay cause cancer.		
	productive toxicity	able information.	
	OT-single exposure It classified based on availa	able information.	
	OT-repeated exposure ot classified based on availa	able information.	
	piration toxicity of classified based on availa	able information.	
Fu	rther information		
	oduct: marks	: No data availab	le
	ON 12. ECOLOGICAL INF	ORMATION	

No data available Persistence and degradability

No data available

Bioaccumulative potential

Components:

Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester:

Partition coefficient: n-	:	log Pow: 5.16
octanol/water		Method: other (calculated)

Sikalastic TC 295 tintbase Part A Formerly MSeal TC 295 tint base PTA



Version 1.0	Revision Date: 09/18/2020		OS Number: 0000936410	Date of last issue: - Date of first issue: 09/18/2020
	ion coefficient: n- ol/water	:	Remarks: not a	pplicable
Partit	im sulfate: ion coefficient: n- iol/water	:	Pow: 4.26 log Pow: 0.63 Method: other (calculated)
calci	um oxide:			
	ion coefficient: n- ol/water	:	Remarks: The substance is in	value has not been determined because the organic.
bis(1	,2,2,6,6-pentamethyl-4	4-pip	eridyl)sebacate	:
	ion coefficient: n- nol/water	:	Remarks: No d	ata available.
Meth	yl 1,2,2,6,6-pentameth	nyl-4-	piperidyl sebac	ate:
Partit	ion coefficient: n- ol/water	-	Remarks: No d	
Quar	tz (SiO2):			
	ion coefficient: n- ol/water	:	Remarks: not a	pplicable
	lity in soil ata available			
Othe	r adverse effects			
<u>Prod</u> Addit matic	ional ecological infor-	:	unprofessional Harmful to aqua	tal hazard cannot be excluded in the event of handling or disposal. atic life. atic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater.
Contaminated packaging	: Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the sub- stance/product.





Version 1.0 Revision Date: 09/18/2020

SDS Number: 000000936410

Date of last issue: -Date of first issue: 09/18/2020

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

· ····································	
calcium oxide	1305-78-8
Limestone	1317-65-3
Barium sulfate	7727-43-7
talc	14807-96-6
New Jersey Right To Know	
calcium oxide	1305-78-8
Limestone	1317-65-3
talc	14807-96-6

California Prop. 65

WARNING: This product can expose you to chemicals including formaldehyde, which is/are known to the State of California to cause cancer, and methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA

: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information



Version 1.0	Revision Date: 09/18/2020	SDS Number: 000000936410	Date of last issue: - Date of first issue: 09/18/2020	
NFPA	704 :		HMIS® IV:	
	Flammability		HEALTH	
	1		FLAMMABILITY	
Hea		Instability	PHYSICAL HAZARD	
	Special hazard		HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal haz- ards or risks, and 4 representing signifi- cant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.	
Full to	ext of other abbreviation	ons		
29 CF 1-A)	R 1910.1000 (Table Z-	: OSHA - Tabl	e Z-1-A (29 CFR 1910.1000)	
29 ĆF	R 1910.1000 (Table Z-		e Z-1 (Limits for Air Contaminants) 29 CFR	
1) 29 CF	R 1910.1001-1050	1910.1000 : OSHA - Spec 1910.1001-1	cifically Regulated Substances (29 CFR	
ACGI ACGI		: USA. ACGIH : American Co	I Threshold Limit Values (TLV) onference of Governmental Industrial Hygienists - it values (US)	
	H REL	: NIOSH Pock : USA. NIOSH	et Guide to Chemical Hazards (US) I Recommended Exposure Limits	
OSHA OSHA	A CARC A P0		fically Regulated Chemicals/Carcinogens - TABLE Z-1 Limits for Air Contaminants -	
OSHA	A Z-1	: USA. Occupa its for Air Cor		
OSHA	A Z-3	eral Dusts	ational Exposure Limits (OSHA) - Table Z-3 Min-	
1-A) /	R 1910.1000 (Table Z- TWA value R 1910.1000 (Table Z-	-	ed Average (TWA): exposure limit	
1) / Pl	EL			
OSHA	R 1910.1001-1050 / A Action level R 1910.1001-1050 /		: OSHA Action level: : Time Weighted Average (TWA):	
TWA ACGI	value H / TWA	: 8-hour, time-	weighted average	
	HTLV / TWA value	: Time Weight	ed Average (TWA):	
	H / REL value H REL / TWA	: Time-weighte	ed exposure limit (REL): ed average concentration for up to a 10-hour	
OSHA	A CARC / PEL		workday during a 40-hour workweek Permissible exposure limit (PEL)	



Sikalastic TC 295 tintbase Part A Formerly MSeal TC 295 tint base PTA

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/18/2020	000000936410	Date of first issue: 09/18/2020

OSHA P0 / TWA	: 8-hour time weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date

09/18/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT



Sikalastic TC 295 tintbase Part A Formerly MSeal TC 295 tint base PTA

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/18/2020	00000936410	Date of first issue: 09/18/2020

PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN