

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
Date of first issue: 12/31/2020

SECTION 1. IDENTIFICATION

Product name : Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry
Product code : 000000000056413453

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3
Acute toxicity (Inhalation - vapour) : Category 3
Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2A
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Reproductive toxicity : Category 1B
Reproductive toxicity : Category 1B
Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)
Hazardous to the aquatic environment - acute hazard : Category 3
Hazardous to the aquatic environment - chronic hazard : Category 3

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
Date of first issue: 12/31/2020

GHS label elements

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H331 Toxic if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H360 May damage fertility or the unborn child.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P260 Do not breathe dust or mist.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 Avoid release to the environment.
P243 Take action to prevent static discharges.
P201 Obtain special instructions before use.
P284 In case of inadequate ventilation wear respiratory protection.
P202 Do not handle until all safety precautions have been read and understood.
P264 Wash face, hands and any exposed skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P242 Use only non-sparking tools.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 00000247494 Date of last issue: -
Date of first issue: 12/31/2020

P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P311 Call a POISON CENTER or doctor/ physician.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P233 Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Stoddard solvent	8052-41-3	$\geq 15 - < 20$
talc	14807-96-6	$\geq 5 - < 15$
4,4'-methylenedicyclohexyl diisoncy-anate	5124-30-1	$\geq 7 - < 10$
Titanium dioxide	13463-67-7	$\geq 0 - < 7$
Calcium sulphate	7778-18-9	$\geq 0.3 - < 1$
dibutyltin dilaurate	77-58-7	$\geq 0.3 - < 1$
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7	$\geq 0.3 - < 1$
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	$\geq 0.1 - < 0.2$

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control center immediately.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
Date of first issue: 12/31/2020

- If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Toxic if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May damage fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)

Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : water jet

High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
-

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/31/2020	000000247494	Date of first issue: 12/31/2020

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Prevent unauthorized access.
no smoking
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
 Date of first issue: 12/31/2020

kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage conditions : Keep container tightly closed and dry; store in a cool place. Avoid all sources of ignition: heat, sparks, open flame.
- Materials to avoid : Observe TRGS 509/510 storage rules.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m3 (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m3 (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m3 (tin (Sn))	NIOSH
		PEL	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL
4,4'-methylenedicyclohexyl diisoncyanate	5124-30-1	TWA value	0.005 ppm	ACGIHTLV
		Ceil_Time	0.01 ppm 0.11 mg/m3	NIOSH
		CLV	0.01 ppm 0.11 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.005 ppm	ACGIH
		C	0.01 ppm 0.11 mg/m3	NIOSH REL

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version
1.0

Revision Date:
12/31/2020

SDS Number:
000000247494

Date of last issue: -
Date of first issue: 12/31/2020

		C	0.01 ppm 0.11 mg/m3	OSHA P0
Calcium sulphate	7778-18-9	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhalable particulate matter)	10 mg/m3 (Calcium)	ACGIH
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (Titanium dioxide)	10 mg/m3	ACGIH
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
 Date of first issue: 12/31/2020

		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m ³	OSHA P0
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIH TLV
		REL value	350 mg/m ³	NIOSH
		Ceil_Time	1,800 mg/m ³	NIOSH
		PEL	500 ppm 2,900 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm	ACGIH
		TWA	350 mg/m ³	NIOSH REL
		C	1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,900 mg/m ³	OSHA Z-1
		TWA	100 ppm 525 mg/m ³	OSHA P0

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.
 Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
Date of first issue: 12/31/2020

- Protective measures : Avoid inhalation of dusts/mists/vapours.
Avoid contact with the skin, eyes and clothing.
Avoid prolonged and/or repeated contact with the skin.
Handle in accordance with good building materials hygiene and safety practice.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and immediately after handling the product.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : various colours
- Odor : solvent
- Odor Threshold : not determined
- pH : Not applicable
- Boiling point : approx. 222.01 - 500 °F / 105.56 - 260 °C
- Flash point : 106 °F / 41 °C
Method: Standard Method of Test for Flash Point by Setaflash Closed Tester
- Flammability (solid, gas) : Flammable.
- Self-ignition : not self-igniting
- Upper explosion limit / Upper flammability limit : 7.0 %(V)
- Lower explosion limit / Lower flammability limit : 1.0 %(V)
- Vapor pressure : No data available
- Relative vapor density : Heavier than air.
- Density : approx. 1.107 g/cm³ (68 °F / 20 °C)
9.23 lb/USg (68 °F / 20 °C)
- Solubility(ies)
-

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0	Revision Date: 12/31/2020	SDS Number: 000000247494	Date of last issue: - Date of first issue: 12/31/2020
----------------	------------------------------	-----------------------------	--

Water solubility	:	slightly soluble (68 °F / 20 °C)
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	20 - 40 poise (73 °F / 23 °C)
Viscosity, kinematic	:	No data available.
Explosive properties	:	Not explosive Not explosive
Oxidizing properties	:	not fire-propagating
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.
Conditions to avoid	:	Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge. Avoid heat. Avoid moisture. See SDS section 7 - Handling and storage. Heat, flames and sparks.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents Water
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
Date of first issue: 12/31/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Toxic if inhaled.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : ATE: 5.11 mg/l
Remarks: Determined for vapor

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Eye contact causes irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
Date of first issue: 12/31/2020

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

dibutyltin dilaurate:

M-Factor (Acute aquatic toxicity) : 1

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

Bioaccumulative potential

Components:

Stoddard solvent:

Partition coefficient: n-octanol/water : log Pow: 3.5 - 6.4 (68 °F / 20 °C)
Method: Partition coefficient (n-octanol/water), HPLC method.

dibutyltin dilaurate:

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
Date of first issue: 12/31/2020

Partition coefficient: n-octanol/water : log Pow: 3.17 (69.4 °F / 20.8 °C)
pH: 6.1 - 6.3
Method: Partition coefficient (n-octanol/water), Shake-flask method
GLP: yes

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
Date of first issue: 12/31/2020

ger aircraft)

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1263
Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : FLAMMABLE LIQUID
ERG Code : 128
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

4,4'-methylenedicyclohexyl diisoncyanate 5124-30-1

US State Regulations

Pennsylvania Right To Know

4,4'-methylenedicyclohexyl diisoncyanate	5124-30-1
Calcium sulphate	7778-18-9
Titanium dioxide	13463-67-7
talc	14807-96-6
Stoddard solvent	8052-41-3

New Jersey Right To Know

4,4'-methylenedicyclohexyl diisoncyanate	5124-30-1
Calcium sulphate	7778-18-9

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version 1.0 Revision Date: 12/31/2020 SDS Number: 000000247494 Date of last issue: -
Date of first issue: 12/31/2020

Titanium dioxide 13463-67-7
talc 14807-96-6
Stoddard solvent 8052-41-3

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, Carbon black, Quartz (SiO₂), formaldehyde, toluene, methanol, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/31/2020	000000247494	Date of first issue: 12/31/2020

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / CLV : Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / Ceil_Time : Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value : Recommended exposure limit (REL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C : Ceiling value not be exceeded at any time.
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / C : Ceiling limit
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET

Sikalastic TC 225 HT grey Formerly MSeal TC 225HT gry



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/31/2020	000000247494	Date of first issue: 12/31/2020

Revision Date : 12/31/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN