

PRODUCT DATA SHEET

DRYLOK® Pourable Masonry Crack Filler

Pourable, self-leveling, masonry crack filler

DESCRIPTION

DRYLOK® Pourable Masonry Crack Filler is formulated to fill and seal cracks on interior and exterior concrete and masonry surfaces. Reduces radon gas penetration. Dries to the color of concrete.

USES

Sealing/filling cracks in concrete & masonry:

- Sidewalks
- Walkways
- Steps
- Patios
- Garage floors
- Concrete slabs

CHARACTERISTICS / ADVANTAGES

- Easy flow formula self-levels
- Blends with natural color and texture of surface
- Precise nozzle tip - no special tools needed
- Paintable with a good quality latex paint
- Reduces radon gas penetration

PRODUCT DATA SHEET

DRYLOK® Pourable Masonry Crack Filler

June 2025, Version 01.01

021820301000000022

PRODUCT INFORMATION

Packaging	Size	PC/Case	Color	Order No.	Old Order No.
	1 quart	6/case	Gray	832428	30512
Shelf life	2 years in the original unopened container				
Storage conditions	Store in a cool, dry place between 50°F (10°C) and 90°F (32°C). Keep from freezing.				
Solid content	85% (by weight)				

TECHNICAL INFORMATION

Freeze thaw resistance	Protect from freezing
------------------------	-----------------------

APPLICATION INFORMATION

Coverage	One quart (946mL) will fill approx. a ½" by ¼" (12mm by 6mm) crack 38 ft (11m) long
	Note: Actual coverage will vary depending on application method, surface texture, and porosity.
Ambient air temperature	Min. 50°F (10°C)
Substrate temperature	Min. 50°F (10°C)
Setting time	12 hours

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS

- Do not apply if rain is expected within 24 hours of application
- Use only on cracks that are a ½" wide or less and a ¼" deep or less
- For use on horizontal surfaces only
- Protect from freezing

PRODUCT DATA SHEET
DRYLOK® Pourable Masonry Crack Filler
June 2025, Version 01.01
021820301000000022



BUILDING TRUST



ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1- 800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

Apply when air and surface temperatures are a minimum of 50°F (10°C). Crack must be free from frost, dust, dirt, oil, and particles. Clean the crack using a wire brush and hose. Remove any excess moisture before filling the crack. Do not apply if rain is expected within 24 hours. Use only when cracks are 1/2" (12mm) wide or less.

APPLICATION

SHAKE WELL BEFORE USING. Remove the red cap. Cut the tip of the spout to a size slightly smaller than the width of the crack. Squeeze DRYLOK® Pourable Masonry Crack Filler tightly into the crack, over-filling slightly to allow for shrinkage. Smooth repaired area with a putty knife. Place the back on the spout after use.

CLEANING OF EQUIPMENT

Soap and water. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

PRODUCT DATA SHEET

DRYLOK® Pourable Masonry Crack Filler

June 2025, Version 01.01

021820301000000022