

PRODUCT DATA SHEET

Sikaplan® Termination Bar

Extruded aluminum bar

PRODUCT DESCRIPTION

Sikaplan Termination Bar is flat aluminum bar with a 45° lip used with approved fasteners to terminate Sikaplan roofing membranes at walls and roof edges.

USES

To terminate Sikaplan roofing membranes at walls and roof edges. Also used for Sarnafil® and Sikaplan vented roof terminations.

AREAS OF APPLICATION

- Wall terminations
- Roof edge terminations
- Vented roof terminations
- Other approved Sikaplan flashing details

CHARACTERISTICS / ADVANTAGES

- Convenient punched 1/4" x 3/8" (6.4 mm x 9.5 mm) oval holes spaced 6" (15.2 cm) on center
- 3/16" (4.8 mm) lip formed to a 45° angle

PRODUCT INFORMATION

Chemical Base	Extruded aluminium (6063 T6 alloy) with a mill finish
Packaging	25 – 10 ft (3.05 m) bars per tube (250 ft, 76.2 m), 29 lbs (13.2 kg) per tube, 10 tubes per pallet (2500 ft, 762 m)
Shelf Life	N/A
Storage Conditions	N/A
Appearance / Color	Gray
Dimensions	Length: 10 ft (3.05m) Width: 3/4" (19 mm) Thickness: 0.090" (2.3 mm)

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

AVAILABILITY/WARRANTY

AVAILABILITY

From Sika Corporation – Roofing Authorized Applications for use within Sarnafil or Sikaplan systems.

WARRANTY

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator.

LIMITATIONS

For use with Sikaplan roof membranes. Refer to specific Sikaplan detail drawings. For use in vented roof applications.

ENVIRONMENTAL, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Install Sikaplan Termination Bar with a 1/4" (6 mm) gap between adjoining bars. Cut Sikaplan Termination Bar at inside and outside corners. Do not bend around corners.

Fasten Sikaplan Termination Bar with approved fasteners 12" (30.5 cm) on center and within 1" (25 mm) of each bar end. Refer to specific Sikaplan and vented roof detail drawings.

COVERAGE

10 linear feet (3.05 m) per bar

MAINTENANCE

Standard maintenance of Sarnafil or Sikaplan systems should include regular inspections of flashings, drains, and termination sealants at least twice a year and after each storm.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and

to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
Sikaplan® Termination Bar
March 2022, Version 02.01
020945051100000082

SikaplanTerminationBar-en-US-(03-2022)-2-1.pdf

