Sikadur®-514 Plus Part C


Revision Date 02/18/2014

1. Identification

Product name	:	Sikadur®-514 Plus Part C
Supplier	:	Sika Corporation
Address	:	201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887 ehs@sika-corp.com
Recommended use of the chemical and restrictions on use	:	For further information, refer to the product technical data sheet.

2. Hazards identification

GHS Classification Carcinogenicity , Category 1A	H350: May cause cancer.
GHS Label element	
Hazard pictograms	
Signal Word	: Danger
Hazard Statements	: H350 May cause cancer.
Precautionary Statements	 Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P281 Use personal protective equipment as required. Response: P308 + P313 IF exposed or concerned: Get medical advice/ attention. Storage: P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal plant.



Print Date 02/18/2014

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Quartz (SiO2)	14808-60-7	>= 50 - <= 100 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If inhaled	: Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. 	
In case of eye contact	 Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. 	
If swallowed	 Clean mouth with water and drink afterwards plenty of wa Induce vomiting immediately and call a physician. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person 	
Most important symptoms and effects, both acute and delayed	: carcinogenic effects	
	See Section 11 for more detailed information on health e and symptoms.	ffects
Protection of first-aiders	 Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance. 	
Notes to physician	: Treat symptomatically.	

5. Fire-fighting measures

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Specific extinguishing	: Collect contaminated fire extinguishing water separately.	This

	Saf
Jika ®	Sik
Revision Date	e 02/1

kadur®-514 Plus Part C

Revision Date 02/18/2014	Print Date 02/18/2014
methods	must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
Environmental precautions	 Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.
7. Handling and storage	
Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see

Advice on safe handling	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	 Prevent unauthorized access. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.
Materials to avoid	: no data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Quartz (SiO2)	14808-60-7	ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-3	TWA	30 mg/m3 / %SiO2+2 total dust



Sikadur®-514 Plus Part C

Revision Date 02/18/2014

Print Date 02/18/2014

		OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
Limestone	1317-65-3	OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA Z-1	TWA	5 mg/m3 respirable fraction
		OSHA P0	TWA	15 mg/m3 Total
		OSHA P0	TWA	5 mg/m3 Respirable fraction

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**<u>Basis</u>

ACGIH. Threshold Limit Values (TLV) OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values) OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant OSHA P2. Permissible Exposure Limits (PEL), Table Z-2 OSHA Z3. Table Z-3, Mineral Dust

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection :		Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
		The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection

Safety Data S	Safety Data Sheet		
Jika Sikadur®-5	14 Plus Part C		
Revision Date 02/18/2014	Print Date 02/18/2014		
Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.		
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.		
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.		
Hygiene measures	 Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Avoid breathing dust. 		

9. Physical and chemical properties

Appearance	:	powder
Color	:	gray
Odor	:	characteristic
Odor Threshold	:	no data available
Flash point	:	Note: not applicable
Ignition temperature	:	no data available
Decomposition temperature	:	no data available
Lower explosion limit (Vol%)	:	no data available
Upper explosion limit (Vol%)	:	no data available
Flammability (solid, gas)	:	no data available
Oxidizing properties	:	no data available
Autoignition temperature	:	no data available
рН	:	no data available
Melting point/range / Freezing point	:	no data available
Boiling point/boiling range	:	no data available
Vapor pressure	:	no data available
Density	:	ca.1.7 g/cm3 at 68 °F (20 °C)
Water solubility	:	Note: insoluble



Revision Date 02/18/2014

Partition coefficient: n- octanol/water	:	no data available
Viscosity, dynamic	:	no data available
Viscosity, kinematic	:	Note: not applicable
Relative vapor density	:	no data available
Evaporation rate	:	no data available
Burning rate	:	no data available
Volatile organic compounds (VOC) content	:	31 g/l Combined with Sikadur®-42 LE Plus Part A and B

10. Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: no data available
Incompatible materials	: no data available

11. Toxicological information

Acute toxicity

Product		
Acute oral toxicity	:	no data available
Acute inhalation toxicity	:	no data available
Acute dermal toxicity	:	no data available

Skin corrosion/irritation

Product

no data available

Serious eye damage/eye irritation

Product

no data available

Respiratory or skin sensitization


Sikadur®-514 Plus Part C

Revision Date 02/18/2014		Print Date 02/18/2014
<u>Product</u>		
no data available		
Germ cell mutagenicity		
Product		
Mutagenicity	: no data available	
Carcinogenicity		
Product		
Carcinogenicity	: May cause cancer.	
IARC	Group 1: Carcinogenic to humans	
NTP	Quartz (SiO2) 14808 Known to be human carcinogen	
Reproductive Toxicity/Fertilit	Quartz (SiO2) 14808- y	-00-7
Product		
Reproductive toxicity	: no data available	
Reproductive Toxicity/Develo	pment/Teratogenicity	
Product		
Teratogenicity	: no data available	
STOT-single exposure		
<u>Product</u>		
Assessment: no data avail	able	
STOT-repeated exposure		
Prolonged exposure can cause	silicosis.	
<u>Product</u>		
Assessment: no data avail	able	
Aspiration toxicity		
<u>Product</u>		
no data available		

12. Ecological information

Other information

Do not empty into drains; dispose of this material and its container in a safe way.



13. Disposal considerations

Disposal methods	
Waste from residues	: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods IATA Not dangerous goods IMDG Not dangerous goods

Special precautions for user no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

15. Regulatory information

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.



Sikadur®-514 Plus Part C

evision Date 02/18/2014		Pr	int Date 02/18/2014
SARA 313	: The following compone established by SARA T Barium sulphate		orting levels 10.00 %
Clean Air Act			
Ozone-Depletion Potential	This product neither co Class I or Class II ODS Section 602 (40 CFR 8	S as defined by the U.S	S. Clean Air Act
This product does not contain Air Act Section 12 (40 CFR 61 This product does not contain Accidental Release Preventior). any chemicals listed unde	er the U.S. Clean Air A	
California Prop 65	WARNING! This produ State of California to ca WARNING: This produ State of California to ca harm.	ause cancer. Ict contains a chemica	l known in the

16. Other information

HMIS Classification


Health *	3
Flammability	0
Physical Hazard	0
Personal Protection	X

Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.



Print Date 02/18/2014

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 02/18/2014

Material number: 463481