

PRODUCT DATA SHEET

Sikafloor®-100 HD Pronto

(formerly MTop SRS 100HD)

METHYL-METHACRYLATE INITIATOR

PRODUCT DESCRIPTION

Sikafloor®-100 HD Pronto is a white, free-flowing, granular powder consisting of dibenzoyl peroxide, phthalate ester plasticizer. This peroxide is used as a cure initiator for Sikafloor® Pronto acrylic resins in both elevated temperature cure and ambient temperature cure processes. Sikafloor®-100 HD Pronto is easy to disperse and dissolves fast in Sikafloor® Pronto acrylic resins.

USES

- Activates Sikafloor® Pronto MMA resin when properly dispersed in mixing container prior to transport to the project area
- Initiates curing of residual material in empty pails and drums prior to disposal

CHARACTERISTICS / ADVANTAGES

- Able to adjust quantity (oz) used per mix based on floor, air, and resin temperatures

PRODUCT INFORMATION

Packaging	55 lb box 0.5 gallon bottle
Appearance / Color	White, free-flowing powder
Shelf Life	12 months for the 50 lb box 24 months for the 0.5 gallon bottle
Storage Conditions	Store in original container away from flammables and all sources of heat, sparks, or flames; out of direct sunlight; and away from cobalt naphthenate, anilines, other promoters, accelerators, oxidizing or reducing agents and strong acids or bases.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
Sikafloor®-100 HD Pronto
January 2025, Version 04.02
020816220010000032

Sikafloor-100HDPronto-en-US-(01-2025)-4-2.pdf

