

# TECHNICAL BULLETIN

## TARGET MARKET ROOFING & WATERPROOFING

BUILDING TRUST



### Subject: Material Storage Guidelines

25-02

To ensure the integrity and performance of roofing materials, applicators must adhere to proper storage practices from the time of delivery through installation. Materials may be delivered as they become available and stored either at their facility yards or directly on job sites. Given that installation timelines can vary significantly, it is critical that all materials are protected during this interim period.

#### Stacking Limitations

Due to limited space, applicators may be inclined to stack pallets of PVC membrane rolls. However, these rolls—typically 10 feet wide and heavy—must not be stacked more than one pallet high. Stacking two or three pallets high is strictly prohibited, as it can lead to deformation or damage to the membrane.

#### Environmental Protection

Please be reminded that standard plastic packaging is not sufficient to protect materials from environmental exposure. All materials must be stored off the ground or floor and covered with breathable tarps to shield them from rain, sunlight, and other elements until installation.

#### Inspection and Replacement

Any materials deemed damaged by the building Sika's Technical Service Representative must be promptly removed from the job site and replaced to maintain compliance and ensure installation quality.

#### Reference Materials

For detailed guidance, please refer to:

- Pages 5 and 6 of the Sika Roofing Applicator Handbook
- PIMA Technical Bulletin #109

These requirements are also outlined in Sika's guide specifications and product data sheets.