

**BUILDING TRUST** 

# PRODUCT DATA SHEET SikaCem<sup>®</sup>-100 Flattening Paste

Solvent-based silica paste for use in SikaCem<sup>®</sup> solvent-based sealers to reduce the surface gloss of the dried film these sealers create

#### **PRODUCT DESCRIPTION**

SikaCem<sup>®</sup>-100 Flattening Paste is a solvent-based silica paste added directly to SikaCem<sup>®</sup> solvent-based sealers to reduce the surface gloss of the dried film these sealers create. Previously named Butterfield Color<sup>®</sup> Flattening Paste.

#### USES

 Added directly to SikaCem®-100 Clear Guard®, SikaCem®-100 PRO 350®, SikaCem®-100 Silane PRO 350®, and SikaCem®-100 PRO 100 to reduce the surface gloss of the dried film these solvent-based sealers create

#### **PRODUCT INFORMATION**

# Chemical BaseSolvent-BasedPackaging1 qt. (0.9 L) fill in 1 qt. (0.9 L) steel canShelf Life12 months in original unopened containerStorage ConditionsStore in original, unopened containers in dry storage.

#### **BASIS OF PRODUCT DATA**

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

### ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding

Product Data Sheet SikaCem®-100 Flattening Paste July 2025, Version 01.01 021405071000000110

# CHARACTERISTICS / ADVANTAGES

• Reduces surface gloss of the sealer

transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

# **APPLICATION INSTRUCTIONS**

#### MIXING

Add the entire 1 qt. (0.9 L) container to 5 gal. (18.9 L) of SikaCem<sup>®</sup> solvent-based sealer being used. Do not thin or alter with any chemical. Mix thoroughly with a drill-mounted mixer. Do not introduce air bubbles by excessive high-speed mixing. Remix periodically.

#### APPLICATION

Once SikaCem<sup>®</sup>-100 Flattening Paste is mixed into the SikaCem<sup>®</sup> solvent-based sealer being used, consult the most current SikaCem<sup>®</sup> solvent-based sealer being used local Product Data Sheet for complete Application Instructions.

# **OTHER RESTRICTIONS**

See Legal Disclaimer.

#### LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at https://usa.sika.com/en/about-us/terms-conditions-ofsale.html or by calling 1-800-933-7452.

#### Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071 Phone: +1-800-933-7452 Fax: +1-201-933-6225 usa.sika.com



Product Data Sheet SikaCem®-100 Flattening Paster July 2025, Version 01.01 021405071000000110 SikaCem-100FlatteningPaste-en-US-(07-2025)-1-1.pdf

**BUILDING TRUST** 

