



## HOW-TO GUIDE

# Sikacryl® Pourable Crack Repair Sealant

**FAST SETTING • READY-TO-USE • FIBER-REINFORCED FOR ADDED STRENGTH • TEXTURED**

### MATERIALS:

- Safety glasses & gloves
- Jug of Sikacryl® Pourable Crack Repair Sealant
- Scissors or utility knife
- Sika® Backer Rod (optional)
- Masking tape (optional)

### SITE PREP & PROCEDURE

1. Remove all loose dirt and debris, oil, grease, and other foreign materials that may interfere with adhesion and/or performance. Make sure the application area is completely clean, dry, and structurally sound.
2. For cracks deeper than 1/4" (6 mm), use backer rod to fill the crack up to 1/4" (6 mm) below the surface.
3. Shake the bottle thoroughly before each use to ensure a consistent mixture. Remove the cap and cut the nozzle tip to 1/4" (6 mm) opening for narrower applications and 3/8" (9 mm) opening for wider applications.
4. Squeeze the Sikacryl® Pourable Crack Repair Sealant directly into the crack, filling the crack up to or just above the surface. Smooth or tool the surface as needed for a uniform, level finish.
5. Protect newly repaired surfaces from heavy traffic and rain for 24 hours after application.
6. Clean up excess wet material with a damp rag or sponge. Remove uncured material from skin and tools with soap and water immediately after use. Dried material must be mechanically removed.

