



SikaShield[®] S-60

SELF-ADHERING SHEET WATERPROOFING MEMBRANE

- Easy to install, self-adhesive overlap ensure installation quality
- Controlled thickness, minimizes opportunity for job site error
- Flexible, handles shrinkage movement and minor settlement
- Cross-laminated film, great stability, and resistance to puncture and tearing
- Cold-applied, no heat necessary for installation

SikaShield® S-60

SELF-ADHERING SHEET WATERPROOFING MEMBRANE

DESCRIPTION

SikaShield® S-60 is a self-adhering sheet waterproofing membrane designed for post-applied applications. Ideal for below grade and between slab concrete structures.

TYPICAL APPLICATIONS

- Commercial/Educational
- Parking Garages
- Pedestrian Tunnels
- Hotels/Residential
- Warehouses
- Production Facilities

PRODUCT/SYSTEM OVERVIEW

SikaShield® S-60 is a proprietary composite, uniquely designed to provide high strength, low temperature adhesion and high temperature stability in a superior waterproofing membrane. A tough, cross-laminated film forms a resilient barrier against physical damage and water migration. It is a cold-applied system, requiring no heat or special equipment to install.

SikaShield® S-60 is ideal for waterproofing below grade concrete, masonry structures, and wood surfaces where in-service temperatures will not exceed 130°F. It can also be applied to split slab construction both above and below grade as well as earth sheltered structures.

- SikaShield® S-60 is available in 200 sf rolls.
- Each roll is 3 ft. x 66.7 ft.



FOR MORE INFORMATION:

Contact Sika: Phone 800.325.9504 Website: usa.sika.com

SIKA ST. LOUIS

3400 Tree Court Industrial Blvd
St. Louis, MO 63122
Phone: 800.325.9504
Fax: 636.225.2049