

**SECTION 1. IDENTIFICATION**

|   |   |  |
|---|---|--|
| Product name  | : | Sikaflex® Crack Flex Sealant   |
| Company name  | : | Sika Corporation<br>201 Polito Avenue<br>Lyndhurst, NJ 07071<br>USA<br>www.sikausa.com |
| Telephone   | : | (201) 933-8800   |
| Telefax   | : | (201) 804-1076   |
| E-mail address  | : | ehs@sika-corp.com  |
| Emergency telephone                                     | : | CHEMTREC: 800-424-9300<br>INTERNATIONAL: +1-703-527-3887                               |
| Recommended use of the chemical and restrictions on use | : | For further information, refer to product data sheet.                                  |

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

|   |   |             |
|---|---|-------------|
| Flammable liquids   | : | Category 4  |
| Skin sensitization  | : | Category 1  |
| Carcinogenicity (Inhalation)                                    | : | Category 1A |
| Specific target organ toxicity - repeated exposure (Inhalation) | : | Category 2  |

**GHS label elements**

|                   |   |   |
|-------------------|---|---|
| Hazard pictograms | : |  |
|-------------------|---|---|

|                   |   |   |
|-------------------|---|---|
| Signal Word       | : | Danger  |
| Hazard Statements | : | H227 Combustible liquid.<br>H317 May cause an allergic skin reaction.<br>H350 May cause cancer by inhalation.<br>H373 May cause damage to organs through prolonged or repeated exposure if inhaled. |



## Precautionary Statements

:

**Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
 P260 Do not breathe mist or vapors.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 Store in a well-ventilated place.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

**Other hazards**

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Mixtures****Components**

| Chemical name | CAS-No.   | Classification   | Concentration (% w/w) |
|---------------|-----------|--|-----------------------|
| xylene        | 1330-20-7 | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>STOT SE 3; H335<br>STOT RE 2; H373 | $\geq 1 - < 5$        |



|                                 |             |   |              |
|---------------------------------|-------------|---|--------------|
|                                 |             | Asp. Tox. 1; H304   |              |
| Isophoronedialdimine            | 932742-30-8 | Skin Sens. 1B; H317   | >= 1 - < 5   |
| ethylbenzene                    | 100-41-4    | Flam. Liq. 2; H225<br>Acute Tox. 4; H332<br>STOT RE 2; H373<br>Asp. Tox. 1; H304<br>Eye Irrit. 2A; H319 | >= 0.1 - < 1 |
| Aliphatic polyisocyanate        | 28182-81-2  | Acute Tox. 4; H332<br>Skin Sens. 1; H317<br>STOT SE 3; H335   | >= 0.1 - < 1 |
| Quartz (SiO <sub>2</sub> ) >5µm | 14808-60-7  | Carc. 1A; H350<br>STOT RE 1; H372<br>STOT SE 3; H335  | >= 0.1 - < 1 |

Actual concentration is withheld as a trade secret

#### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : sensitizing effects  
Allergic reactions  
May cause an allergic skin reaction.  
May cause cancer by inhalation.  
May cause damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : Treat symptomatically.

#### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)



- Unsuitable extinguishing media : Water
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.
- Materials to avoid : Explosives  
Oxidizing agents



Poisonous gases  
Poisonous liquids

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

| Components         | CAS-No.    | Value type (Form of exposure)       | Control parameters / Permissible concentration | Basis     |
|--------------------|------------|-------------------------------------|--|-----------|
| xylene             | 1330-20-7  | TWA                                 | 100 ppm<br>435 mg/m3                           | OSHA Z-1  |
|                    |            | TWA                                 | 20 ppm   | ACGIH     |
|                    |            | STEL                                | 150 ppm<br>655 mg/m3                           | OSHA P0   |
| ethylbenzene       | 100-41-4   | TWA                                 | 100 ppm<br>435 mg/m3                           | OSHA P0   |
|                    |            | TWA                                 | 100 ppm<br>435 mg/m3                           | OSHA Z-1  |
|                    |            | TWA                                 | 100 ppm<br>435 mg/m3                           | OSHA P0   |
|                    |            | STEL                                | 125 ppm<br>545 mg/m3                           | OSHA P0   |
|                    |            | TWA                                 | 20 ppm   | ACGIH     |
|                    |            | TWA                                 | 20 ppm   | ACGIH     |
| Quartz (SiO2) >5µm | 14808-60-7 | TWA (Respirable particulate matter) | 0.025 mg/m3                                    | ACGIH     |
|                    |            | TWA (Respirable dust)               | 0.05 mg/m3                                     | OSHA Z-1  |
|                    |            | TWA (respirable)                    | 10 mg/m3 / %SiO2+2                             | OSHA Z-3  |
|                    |            | TWA (respirable)                    | 250 mppcf / %SiO2+5                            | OSHA Z-3  |
|                    |            | TWA (respirable dust fraction)      | 0.1 mg/m3                                      | OSHA P0   |
|                    |            | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica)                           | ACGIH     |
|                    |            | PEL (respirable)                    | 0.05 mg/m3                                     | OSHA CARC |
|                    |            | TWA (respirable dust fraction)      | 0.1 mg/m3                                      | OSHA P0   |
|                    |            | TWA (Respirable particulate matter) | 0.025 mg/m3                                    | ACGIH     |
|                    |            | TWA (Respirable par-                | 0.025 mg/m3 (Silica)                           | ACGIH     |



|  |  |                       |  |
|--|--|-----------------------|--|
|  |  | ticulate mat-<br>ter) |  |
|--|--|-----------------------|--|

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.  
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** : viscous liquid

**Color** : various



|  |   |                      |
|--|---|----------------------|
| Odor   | : | aromatic             |
| Odor Threshold                                   | : | No data available    |
| pH   | : | Not applicable       |
| Melting point/range / Freezing point             | : | No data available    |
| Boiling point/boiling range                      | : | No data available    |
| Flash point                                      | : | 187.00 °F / 86.11 °C |
| Evaporation rate                                 | : | No data available    |
| Flammability (solid, gas)                        | : | No data available    |
| Upper explosion limit / Upper flammability limit | : | No data available    |
| Lower explosion limit / Lower flammability limit | : | No data available    |
| Vapor pressure                                   | : | 0.01 hpa             |
| Relative vapor density                           | : | No data available    |
| Density  | : | 1.25 - 1.29 g/cm3    |
| Solubility(ies)                                  |   |                      |
| Water solubility                                 | : | insoluble            |
| Solubility in other solvents                     | : | No data available    |
| Partition coefficient: n-octanol/water           | : | No data available    |
| Autoignition temperature                         | : | No data available    |
| Decomposition temperature                        | : | No data available    |
| Viscosity  |   |                      |
| Viscosity, dynamic                               | : | No data available    |
| Viscosity, kinematic                             | : | > 20.5 mm2/s         |
| Explosive properties                             | : | No data available    |
| Oxidizing properties                             | : | No data available    |
| Volatile organic compounds (VOC) content         | : | 32.5 g/l             |

---

**SECTION 10. STABILITY AND REACTIVITY**

|            |   |   |
|------------|---|---|
| Reactivity | : | No dangerous reaction known under conditions of normal use. |
|------------|---|---|



|                                    |   |   |
|------------------------------------|---|---|
| Chemical stability                 | : | The product is chemically stable.                   |
| Possibility of hazardous reactions | : | Stable under recommended storage conditions.        |
| Conditions to avoid                | : | Extremes of temperature and direct sunlight.        |
| Incompatible materials             | : | No data available                                   |
| Hazardous decomposition products   | : | No decomposition if stored and applied as directed. |

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Not classified based on available information.

### Components:

#### **xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

#### **Isophoronedialdimine:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

#### **ethylbenzene:**

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

#### **Aliphatic polyisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 2,500 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgment

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

### **Serious eye damage/eye irritation**

Not classified based on available information.





**Respiratory or skin sensitization**

**Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer by inhalation.

|             |   |            |
|-------------|---|------------|
| <b>IARC</b> | Group 1: Carcinogenic to humans           |            |
|             | Quartz (SiO <sub>2</sub> )                | 14808-60-7 |
|             | (Silica dust, crystalline)                |            |
|             | Group 2B: Possibly carcinogenic to humans |            |
|             | Titanium dioxide (> 10 µm)                | 13463-67-7 |
|             | Group 2B: Possibly carcinogenic to humans |            |
|             | Carbon black                              | 1333-86-4  |
|             | Group 2B: Possibly carcinogenic to humans |            |
|             | ethylbenzene                              | 100-41-4   |
| <b>OSHA</b> | OSHA specifically regulated carcinogen    |            |
|             | Quartz (SiO <sub>2</sub> )                | 14808-60-7 |
|             | (crystalline silica)                      |            |
| <b>NTP</b>  | Known to be human carcinogen              |            |
|             | Quartz (SiO <sub>2</sub> )                | 14808-60-7 |
|             | (Silica, Crystalline (Respirable Size))   |            |

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure if inhaled.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

**Product:**

Remarks : Carbon black (1333-86-4)  
Animal Toxicity:  
 Rat, oral, duration 2 year  
 Effect: no tumors  
  
 Mouse, oral, duration 2 years  
 Effect: no tumors



Mouse, dermal, duration 18 months

Effect: no skin tumors

Rat, inhalation, duration 2 years

Target organ: lungs

Effect: inflammation, fibrosis, tumors

Note: Tumors in the rat lung are considered to be related to the "particle overload phenomenon" rather than to a specific chemical effect of carbon black itself in the lung. These effects in rats have been reported in many studies on other poorly soluble inorganic particles and appear to be rat specific. Tumors have not been observed in other species (i.e., mouse and hamster) for carbon black or other poorly soluble particles under similar circumstances and study conditions.

Mortality studies (human data): A study on carbon black production workers in the UK (Sorahan, 2001) found an increased risk of lung cancer in two of the five plants studied; however, the increase was not related to the dose of carbon black. Thus, the authors did not consider the increased risk in lung cancer to be due to carbon black exposure. A German study of carbon black workers at one plant (Morfeld, 2006; Buechte, 2006) found a similar increase in lung cancer risk but, like the Sorahan, 2001 (UK study) found no association with carbon black exposure. A large US study of 18 plants showed a reduction in lung cancer risk in carbon black production workers (DEll, 2006). Based upon these studies, the February 2006 Working Group at the International Agency for Research on Cancer (IARC) concluded that the human evidence for carcinogenicity was inadequate (IARC, 2010).

Since the IARC evaluation of carbon black, Sorahan and Harrington (2007) have re-analyzed the UK study data using an alternative exposure hypothesis and found a positive association with carbon black exposure in two of the five plants. The same exposure hypothesis was applied by Morfeld and McCunney (2009) to the German cohort; in contrast, they found no association between carbon black exposure and lung cancer risk and, thus, no support for the alternative exposure hypothesis used by Sorahan and Harrington.

Overall, as a result of these detailed investigations, no causative link between carbon black exposure and cancer risk in humans has been demonstrated.

**IARC CANCER CLASSIFICATION:** In 2006 IARC re-affirmed its 1995 finding that there is "inadequate evidence" from human health studies to assess whether carbon black causes cancer in humans. IARC concluded that there is "sufficient evidence" in experimental animal studies for the carcinogenicity of carbon black. IARC's overall evaluation is that carbon black is "possibly carcinogenic to humans" (Group 2B)". This conclusion was based on IARC's guidelines, which generally require such a classification if one species exhibits carcinogenicity in two or more animal studies (IARC, 2010).

Solvent extracts of carbon black were used in one study of rats in which skin tumors were found after dermal application and several studies of mice in which sarcomas were found



following subcutaneous injection. IARC concluded that there was "sufficient evidence" that carbon black extracts can cause cancer in animals (Group 2B).

**ICGIH CANCER CLASSIFICATION:** Confirmed Animal Carcinogen with Unknown Relevance to Humans (Category A3 Carcinogen).

**ASSESSMENT:** Applying the guidelines of self-classification under the Globally Harmonized System of Classification and Labeling of Chemicals, carbon black is not classified as a carcinogen. Lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rats tumors are a result of a secondary non-genotoxic mechanism that has questionable relevance for classification in humans. In support of this opinion, the CLP Guidance for Specific Target Organ Toxicity - Repeated Exposure (STOT-RE), cites lung overload under mechanisms not relevant to humans. Human health studies show that exposure to carbon black does not increase the risk to carcinogenicity.

Titanium dioxide (13463-67-7)

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **xylene:**

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
Exposure time: 56 d



Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia): 1.17 mg/l  
Exposure time: 7 d

**Isophoronedialdimine:**

Toxicity to fish : LC50 (Fish): 87.2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 180.4 mg/l  
Exposure time: 72 h

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION**

**TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**CERCLA Reportable Quantity**

| Components | CAS-No.   | Component RQ (lbs) |
|------------|-----------|--------------------|
| xylene     | 1330-20-7 | 100                |

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Respiratory or skin sensitization  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

|              |           |                |
|--------------|-----------|----------------|
| xylene       | 1330-20-7 | >= 1 - < 5 %   |
| ethylbenzene | 100-41-4  | >= 0.1 - < 1 % |

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):  
xylene 1330-20-7 >= 1 - < 5 %

**California Prop. 65**

**⚠ WARNING:** This product can expose you to chemicals including Titanium dioxide, which is known to the State of California to cause cancer, and 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens  
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

# Sikaflex® Crack Flex Sealant



Revision Date 10/14/2022

Print Date 10/14/2022

|                 |   |  |
|-----------------|---|--|
| OSHA Z-3        | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
| ACGIH / TWA     | : | 8-hour, time-weighted average                                      |
| OSHA CARC / PEL | : | Permissible exposure limit (PEL)                                   |
| OSHA P0 / TWA   | : | 8-hour time weighted average                                       |
| OSHA P0 / STEL  | : | Short-term exposure limit  |
| OSHA Z-1 / TWA  | : | 8-hour time weighted average                                       |
| OSHA Z-3 / TWA  | : | 8-hour time weighted average                                       |

### **Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 10/14/2022

100000034340  
US / Z8