

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 000000261032 Date of last issue: -
Date of first issue: 12/29/2020

SECTION 1. IDENTIFICATION

Product name : Sikaflex NP 125 clear Formerly MSeal NP 125 CLR
Product code : 000000000051670006

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2A
Carcinogenicity : Category 1B
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure : Category 2 (Auditory organ)
Short-term (acute) aquatic hazard : Category 2
Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : The image shows two GHS hazard pictograms side-by-side. The first is a red diamond with a black exclamation mark inside, representing a general hazard. The second is a red diamond with a black silhouette of a person and a flame over their chest, representing a health hazard.

Signal Word : Danger

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 00000261032 Date of last issue: -
Date of first issue: 12/29/2020

Hazard Statements : H319 Causes serious eye irritation.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H350 May cause cancer.
H373 May cause damage to organs (Auditory organ) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
H401 Toxic to aquatic life.

Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P201 Obtain special instructions before use.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust or mist.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:
P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards
None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 000000261032 Date of last issue: -
Date of first issue: 12/29/2020

Chemical nature : polymers
solvent(s)

Components

Chemical name	CAS-No.	Concentration (% w/w)
ethylbenzene	100-41-4	>= 10 - < 15
xylene	1330-20-7	>= 15 - < 20
Silica, amorphous, fumed, cryst.-free	112945-52-5	>= 3 - < 5
White mineral oil (petroleum)	8042-47-5	>= 1 - < 3
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 1 - < 3
Distillates (petroleum), hydrotreated light	64742-47-8	>= 1 - < 3
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 1 - < 3
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]	64742-54-7	>= 1 - < 3
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	>= 1 - < 3
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil, and; solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil having a viscosity of approximately 112cSt at 40 oC. It contains a relatively large proportion of saturated hydrocarbons.]	72623-85-9	>= 1 - < 3
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified; [A complex combination of hydrocarbons ob-	72623-86-0	>= 1 - < 3

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 00000261032 Date of last issue: -
 Date of first issue: 12/29/2020

<p>tained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 oC. It contains a relatively large proportion of saturated hydrocabons.]</p>		
<p>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 oC. It contains a relatively large proportion of saturated hydrocarbons.]</p>	72623-87-1	>= 1 - < 3

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Show this material safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : Keep patient calm, remove to fresh air, seek medical attention.

 If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/29/2020	00000261032	Date of first issue: 12/29/2020

- Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause cancer.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.
-

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 00000261032 Date of last issue: -
Date of first issue: 12/29/2020

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, well-ventilated place.
Protect from direct sunlight.
Store protected against freezing.
- Materials to avoid : Observe TRGS 509/510 storage rules.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethylbenzene	100-41-4	TWA value	20 ppm	ACGIHTLV
		STEL value	125 ppm 545 mg/m3	NIOSH
		REL value	100 ppm 435 mg/m3	NIOSH
		PEL	100 ppm 435 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 435 mg/m3	29 CFR 1910.1000

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 00000261032 Date of last issue: -
Date of first issue: 12/29/2020

		STEL value	125 ppm 545 mg/m3	(Table Z-1-A) 29 CFR 1910.1000 (Table Z-1-A)
		TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
xylene	1330-20-7	TWA value	100 ppm	ACGIHTLV
		STEL value	150 ppm	ACGIHTLV
		PEL	100 ppm 435 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 435 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 655 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		REL value	100 ppm 435 mg/m3	NIOSH
		STEL value	150 ppm 655 mg/m3	NIOSH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
White mineral oil (petroleum)	8042-47-5	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		STEL value (Mist)	10 mg/m3	NIOSH
		REL value (Mist)	5 mg/m3	NIOSH
		PEL (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Mist)	5 mg/m3	OSHA Z-1

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 00000261032 Date of last issue: -
 Date of first issue: 12/29/2020

		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		STEL value (Mist)	10 mg/m3	NIOSH
		REL value (Mist)	5 mg/m3	NIOSH
		PEL (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated light	64742-47-8	TWA value (Non-aerosol)	200 mg/m3 (total hydrocarbon vapor)	ACGIHTLV
		Skin Designation (Non-aerosol)		ACGIHTLV
		REL value	100 mg/m3	NIOSH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		STEL value (Mist)	10 mg/m3	NIOSH

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 00000261032 Date of last issue: -
 Date of first issue: 12/29/2020

		REL value (Mist)	5 mg/m3	NIOSH
		PEL (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Silica, amorphous, fumed, cryst.-free	112945-52-5	REL value	6 mg/m3	NIOSH
		TWA value	0.8 mg/m3	29 CFR 1910.1000 (Table Z-3)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL

Engineering measures : Wear appropriate respiratory protection.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0	Revision Date: 12/29/2020	SDS Number: 000000261032	Date of last issue: - Date of first issue: 12/29/2020
----------------	------------------------------	-----------------------------	--

Protective measures : Avoid contact with the skin, eyes and clothing.
No special measures necessary if stored and handled correctly.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : various colours

Odor : solvent

pH : Not applicable

Melting point : No data available

Boiling point : No applicable information available.

Flash point : Not applicable

Evaporation rate : No applicable information available.

Flammability (solid, gas) : Not a flammable solid according to UN transport regulations division 4.1 and GHS chapter 2.7.
Method: Manual of tests and criteria. Test N.1 (United Nations Recommendations on the Transport of Dangerous Goods).

Self-ignition : not self-igniting

Upper explosion limit / Upper flammability limit : 6.7 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapor pressure : No applicable information available.

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : 0.98 g/cm³

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0	Revision Date: 12/29/2020	SDS Number: 00000261032	Date of last issue: - Date of first issue: 12/29/2020
----------------	------------------------------	----------------------------	--

Bulk density	:	0.98 g/cm ³
Solubility(ies)	:	
Water solubility	:	slightly soluble
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	454.400 mm ² /s (104 °F / 40 °C)
Explosive properties	:	Not explosive Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Self-heating substances	:	No data available
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	See SDS section 7 - Handling and storage.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 000000261032 Date of last issue: -
Date of first issue: 12/29/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information

Product:

Remarks : No data available

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version 1.0 Revision Date: 12/29/2020 SDS Number: 00000261032 Date of last issue: -
Date of first issue: 12/29/2020

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

ethylbenzene:

Partition coefficient: n- : Pow: 4,170 (68 °F / 20 °C)
octanol/water : log Pow: 3.6 (68 °F / 20 °C)
pH: 7.8
Method: Partition coefficient
GLP: yes

Silica, amorphous, fumed, cryst.-free:

Partition coefficient: n- : Remarks: Not applicable
octanol/water

White mineral oil (petroleum):

Partition coefficient: n- : Remarks: not applicable for mixtures
octanol/water

Distillates (petroleum), hydrotreated middle:

Partition coefficient: n- : Remarks: No data available.
octanol/water

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]:

Partition coefficient: n- : log Pow: approx. 7 - 25
octanol/water : Method: other (calculated)

Distillates (petroleum), hydrotreated light paraffinic:

Partition coefficient: n- : Pow: > 3.5
octanol/water

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/29/2020	00000261032	Date of first issue: 12/29/2020

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 oC. It contains a relatively large proportion of saturated hydrocarbons.]:

Partition coefficient: n- : log Pow: 7.868
octanol/water Method: other (calculated)

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/29/2020	00000261032	Date of first issue: 12/29/2020

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

xylene	1330-20-7
ethylbenzene	100-41-4

US State Regulations

Pennsylvania Right To Know

ethylbenzene	100-41-4
xylene	1330-20-7
Silicon dioxide	7631-86-9
White mineral oil (petroleum)	8042-47-5
Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons ob- tained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8

New Jersey Right To Know

ethylbenzene	100-41-4
xylene	1330-20-7
Distillates (petroleum), hydrotreated light	64742-47-8
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons ob- tained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]	64742-54-7

California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, methanol, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR




Version 1.0 Revision Date: 12/29/2020 SDS Number: 00000261032 Date of last issue: -
Date of first issue: 12/29/2020


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- 29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- 29 CFR 1910.1000 (Table Z-1-A) / STEL value : Short Term Exposure Limit (STEL):
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- 29 CFR 1910.1000 (Table Z-3) / TWA value : Time Weighted Average (TWA):
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIHTLV / Skin Designa- : Skin Designation:

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/29/2020	00000261032	Date of first issue: 12/29/2020

tion

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):
NIOSH / STEL value : Short Term Exposure Limit (STEL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
workday during a 40-hour workweek
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded
at any time during a workday
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 12/29/2020

SAFETY DATA SHEET

Sikaflex NP 125 clear Formerly MSeal NP 125 CLR



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/29/2020	00000261032	Date of first issue: 12/29/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN