



## Sika® PU Accelerator

### Catalyst for Sikalastic RoofPro 600 series base and top coats

<b>Description</b>	Sika PU Accelerator is designed to increase the cure rate of Sikalastic 601 BC, 621 TC and 624 AR to facilitate a faster application and reduce downtime in areas where a rapid return to service is required.
<b>Advantages</b>	<ul style="list-style-type: none"><li>■ Reduces downtime in areas where a rapid return to service is required</li><li>■ Avoids delays due to lower temperatures</li></ul>
<b>Coverage</b>	300 ml pack per 5 gal. pail
<b>Packaging</b>	300 ml pack

#### How to Use

<b>Mixing</b>	Mixing level - 1% by weight maximum. Add contents to specific Sikalastic product on site at time of application and mix manually or mechanically at low speed to prevent aeration. Mix with electric drill and paddle. The pack of 300 ml is sufficient to accelerate a full 5 gal. pail. Once the Sika PU Accelerator is added the product must be used immediately, as the product has a working time of 1 hour.
---------------	--

#### Typical Data

RESULTS MAY DIFFER BASED UPON STATISTICAL VARIATIONS DEPENDING UPON MIXING METHODS AND EQUIPMENT, TEMPERATURE, APPLICATION METHODS, TEST METHODS, ACTUAL SITE CONDITIONS AND CURING CONDITIONS.

<b>Shelf Life</b>	9 months from date of production if stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between 40 and 85 degrees F (4-30 degrees C).
<b>Storage</b>	Store dry at 40-85 degrees F (4-30 degrees C) before using.
<b>Product Conditioning</b>	Condition material to 65-85 degrees F (4-30 degrees C) before using
<b>Chemical Base</b>	Catalyst in hydrocarbon solvent
<b>Density</b>	1.01 kg/l
<b>Appearance</b>	Clear, low viscosity liquid

Construction

Sika®

<b>Surface Preparation</b>	Refer to specific Sikalastic Product Data Sheet.
<b>Application</b>	Refer to specific Sikalastic Product Data Sheet.
<b>Limitations</b>	Accelerated Sikalastic material has a pot life of 1 hour and must be used immediately.
<b>Caution</b>	<b>WARNING: IRRITANT.</b> Contains 1-ethylpyrrolidin-2-one (CAS:2687-91-4) and benzoic acid (CAS:65-85-0). Causes severe eye irritation. May cause eye injury, effects may be delayed. May cause skin/respiratory tract irritation. May cause gastrointestinal disturbance if swallowed.
<b>Handling and Storage</b>	Avoid direct contact. Wear personal protective equipment (chemical resistant goggles/gloves/clothing) to prevent direct contact with skin and eyes. Use only in well ventilated areas. Open doors and windows during use. Use a properly fitted NIOSH respirator if ventilation is poor. Wash thoroughly with soap and water after use. Remove contaminated clothing and launder before reuse.
<b>Cleanup</b>	Use personal protective equipment (chemical resistant gloves/goggles/clothing). Without direct contact, sweep up spilled or excess product and place in suitable sealed container. Dispose of excess product and container in accordance with applicable local, state, and federal regulations.
<b>First Aid Measures</b>	<b>Eyes</b> – Hold eyelids apart and flush thoroughly with water for 15 minutes. <b>Skin</b> – Remove contaminated clothing. Wash skin thoroughly for 15 minutes with soap and water. <b>Inhalation</b> – Remove to fresh air. <b>Ingestion</b> – Do not induce vomiting. Dilute with water. Contact physician. <b>In all cases contact a physician immediately if symptoms persist.</b>

**KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY**  
 All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at [www.sikausa.com](http://www.sikausa.com) or by calling 800-933-7452.

**Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Material Safety Data Sheet which are available online at [www.sikausa.com](http://www.sikausa.com) or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use.**

**LIMITED WARRANTY:** Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKASHALL NOT BELIEVE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKASHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Visit our website at [www.sikausa.com](http://www.sikausa.com)

1-800-933-SIKA NATIONWIDE

**Regional Information and Sales Centers.** For the location of your nearest Sika sales office, contact your regional center.

**Sika Corporation**  
 201 Polito Avenue  
 Lyndhurst, NJ 07071  
 Phone: 800-933-7452  
 Fax: 201-933-6225

**Sika Canada Inc.**  
 601 Delmar Avenue  
 Pointe Claire  
 Quebec H9R 4A9  
 Phone: 514-697-2610  
 Fax: 514-694-2792

**Sika Mexicana S.A. de C.V.**  
 Carretera Libre Celaya Km. 8.5  
 Fracc. Industrial Balvanera  
 Corregidora, Queretaro  
 C.P. 76920  
 Phone: 52 442 2385800  
 Fax: 52 442 2250537

