

Revision Date 09/16/2024

Print Date 09/16/2024

SECTION 1. IDENTIFICATION

Product name	:	Sika [®] Stabilizer-2232 TBM
Company name	:	Sika Corporation
		201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)			
Carcinogenicity (Inhalation) :	Category 1A		
Specific target organ toxicity : - repeated exposure	Category 1 (Lungs)		
GHS label elements			
Hazard pictograms :			
Signal Word :	Danger		
Hazard Statements :	H350 May cause cancer by inhalation. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.		
Precautionary Statements :	Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read		

Revision Date 09/16/2024



Print Date 09/16/2024

and understood. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
barium sulfate	7727-43-7		>= 10 - < 20
distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	Asp. Tox. 1; H304	>= 10 - < 20
Quartz (SiO2) >5µm	14808-60-7	Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	>= 1 - < 5
Residual oils (petroleum) solvent dewaxed	64742-62-7		>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attend- ance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.

Revision Date 09/16/2024



Print Date 09/16/2024

In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	:	May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure. No known significant effects or hazards. No information available.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions :	Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for : containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).



Revision Date 09/16/2024

Print Date 09/16/2024

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	:	Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
barium sulfate	7727-43-7	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respir- able fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respir- able dust fraction)	5 mg/m3	OSHA P0
Quartz (SiO2) >5µm	14808-60-7	TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Res- pirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respir- able)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respir-	250 mppcf /	OSHA Z-3



Revision Date 09/16/2024

Print Date 09/16/2024

I	1	able)	%SiO2+5	1
		TWÁ (respir- able dust	0.1 mg/m3	OSHA P0
		fraction) TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respir- able)	0.05 mg/m3	OSHA CARC
		TWÁ (respir- able dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
Residual oils (petroleum) sol- vent dewaxed	64742-62-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures :	Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend- ed or statutory limits.
Personal protective equipmen	t
Respiratory protection :	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.
	The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection :	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling



Revision Date 09/16/2024	Print Date 09/16/20)24
	chemical products if a risk assessment indicates this is nec- essary.	
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.	
Skin and body protection	: Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.	
Hygiene measures	 Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. 	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Color	:	gray
Odor	:	slight
Odor Threshold	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/ range / Freez-	:	No data available
ing point Boiling point/boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.01 hpa
Relative vapor density	:	No data available
Density	:	ca. 1.62 g/cm3 (68 °F / 20 °C)
Solubility(ies)		



Revision Date 09/16/2024

Print Date 09/16/2024

Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	> 20.5 mm2/s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Not classified due to lack of data.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.



sion Date 09	0/16/2024	Print Date 09/16/2
Respirator	y sensitization	
Not classifi	ed due to lack of data.	
Germ cell	mutagenicity	
Not classifi	ed due to lack of data.	
Carcinoge	nicity	
	cancer by inhalation.	
IARC	Group 1: Carcinogenic to humans Quartz (SiO2) (Silica dust, crystalline)	14808-60-7
OSHA	OSHA specifically regulated carcinogen Quartz (SiO2) (crystalline silica)	14808-60-7
NTP	Known to be human carcinogen Quartz (SiO2) (Silica, Crystalline (Respirable Size))	14808-60-7
Reproduct	ive toxicity	
-	ed due to lack of data.	
STOT-sing	le exposure	
Not classifi	ed due to lack of data.	
STOT-repe	eated exposure	
Causes da	mage to organs (Lungs) through prolonged or repea	ated exposure.
Aspiration	toxicity	
Not classifi	ed due to lack of data.	
Further inf	ormation	
Product:		
	Quartz (14808 60 7): This a	lassification is relevant when ex

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available



Revision	Date	09/16/2024
1101131011	Daio	00/10/2024

Print Date 09/16/2024

Mobility in soil No data available Other adverse effects		
Product: Additional ecological infor- mation	:	Do not empty into drains; dispose of this material and its con- tainer in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.



Revision Date 09/16/2024

Print Date 09/16/2024

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Carcinogenicity Specific target organ toxicity (single or repeated exposure)
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

▲ WARNING: This product can expose you to chemicals including Quartz (SiO2) >5µm, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH OSHA CARC OSHA P0	:	USA. ACGIH Threshold Limit Values (TLV) OSHA Specifically Regulated Chemicals/Carcinogens USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.



Revision Date 09/16/2024

Print Date 09/16/2024

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 09/16/2024

10000054066 US / Z8