

PRODUCT DATA SHEET

LaHabra® Superhold

Liquid Bonding Agent For Plaster and Concrete

PRODUCT DESCRIPTION

LaHabra® Superhold is a premium quality, ethylene vinyl acetate emulsion which allows for the adhesion of gypsum plasters and portland cement materials to existing surfaces. LaHabra® Superhold is a unique formulation that is ready-to-use, high build, film forming, and re-emulsifiable. It has a blue tint so the area of application can be easily identified.

USES

LaHabra® Superhold may be used in both interior or exterior applications for bonding new portland cement or gypsum plasters to existing substrates, including stucco colorcoat, concrete, cementitious mortars, thin set cements, patching compounds, and veneer plaster systems. It may be applied to structurally sound existing surfaces such as portland cement scratch and brown coats, stucco colorcoat, concrete, concrete block, brick, tile, stone, gypsum wallboard, terrazzo, glass, and plywood underlayments. It may be used over damp or dry surfaces provided that there is no source of constant moisture.

CHARACTERISTICS / ADVANTAGES

- Ready to use, no mixing.
- Simple application.
- Resistant to effects of high alkalinity associated with lime plasters and portland cement.
- Resistant to humidity, may be used over dry and damp, but not continuously wet surfaces.
- Non-flammable, VOC compliant.
- Easy, time-saving application.

PRODUCT INFORMATION

Packaging	5 gal. (19 ltr) plastic pails
Shelf Life	2 years with proper storage
Storage Conditions	Do not store in direct sunlight. Storage temperature should be between 50°F (10° c) and 90°F (32° C). Protect from freezing.

APPLICATION INFORMATION

Coverage

1 gallon (3.8 ltr) covers approximately 250 to 300 sq. ft. (23 to 27.6 m2).
Note: Coarse or porous surfaces may require more material.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS

- Do not use in areas subject to continuous water exposure or hydrostatic pressure (e.g., swimming pools, fountains, spas, water tanks, below-grade applications, or other permanently wet environments).
- Do not allow Superhold to freeze,
- Do not apply over frozen or frost filled surfaces.
- Do not use when ambient temperature will fall below 40° F (4° C) within 48 hours after application.
- Do not dilute with water.
- Do not apply over water soluble materials.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The receiving surface should be clean, free of dust, dirt, oil, grease, loose stone, loose sand, deteriorating paint or other foreign materials which could impair bonding ability. Smooth surfaces should be abraded before application. On porous surfaces, lightly dampen before applying LaHabra® Superhold.

Try a test patch on questionable surfaces and allow to dry for 24 hours. If LaHabra® Superhold curls or cracks, the surface must be cleaned thoroughly prior to application.

APPLICATION

LaHabra® Superhold is ready to use. It needs no mixing or stirring. Do not dilute with water. It may be applied by hand with brush or roller, or spray applied using an airless sprayer delivering at least 40 psi (2.8 kg/cm2), with an orifice size no smaller than .020 inch (.5 mm). A larger orifice may be necessary. Spray approximately 18"

from surface in a crisscross pattern. Apply new materials within 72 hours of the application of Superhold.

For maximum adhesion of new cementitious materials, use SikaWall®-73 Adacryl Admix & Bonder as an admix (1 part Adacryl to 3 parts water) plus LaHabra® Superhold (undiluted) on the substrate.

CLEANING OF TOOLS

Clean all tools and equipment with detergent and water immediately after use. Clean up spills, splatters and overspray before it is allowed to dry.

Product Data Sheet

LaHabra® Superhold
November 2025, Version 01.01
021890401000244160

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

LaHabra® Superhold
November 2025, Version 01.01
021890401000244160

LaHabraSuperhold-en-US-(11-2025)-1-1.pdf

