



Revision Date: Version SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

**SECTION 1. IDENTIFICATION** 

Product name Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe

brz

Product code 000000000051704668

Manufacturer or supplier's details

Company name of supplier Sika MBCC US LLC

Address 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use Product for construction chemicals

Restrictions on use Reserved for industrial and professional use.

**SECTION 2. HAZARDS IDENTIFICATION** 

GHS classification in accordance with 29 CFR 1910.1200

Serious eye damage/eye

irritation

: Category 2A

Skin sensitization Category 1

Reproductive toxicity 1B

Reproductive toxicity 1B

Specific target organ toxicity : 2 (Liver, Kidney)

- repeated exposure

Short-term (acute) aquatic

hazard

: 3

Long-term (chronic) aquatic

hazard

3

**GHS** label elements

Hazard pictograms



Signal Word Danger

## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz



Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

Hazard Statements : H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs (Liver, Kidney) through

prolonged or repeated exposure.

H360 May damage fertility or the unborn child.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary Statements** 

#### Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P260 Do not breathe dust or mist. P273 Avoid release to the environment. P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P264 Wash face, hands and any exposed skin thoroughly after

handling.

### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap

and water.

P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P337 + P311 If eye irritation persists: Call a POISON CENTER

or doctor/physician.

#### Storage:

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

#### Other hazards

No data available.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Sealant

#### Components

Chemical name   CAS-No.   Concentration (% w/w)	Chemical name	CAS-No.	Concentration (% w/w)
---	---------------	---------	-----------------------



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

calcium carbonate	471-34-1	>= 20 - < 50
Limestone	1317-65-3	>= 3 - < 10
stearic acid	57-11-4	>= 0.3 - < 3
carbon black	1333-86-4	>= 0.3 - < 1
N-(3-	1760-24-3	>= 0.3 - < 1
(Trimethoxysi-		
lyl)propyl)ethylenediamine		
Dibutylbis(pentane-2,4-dionato-	22673-19-4	>= 0.1 - < 0.2
O,O')tin		
2-(2H-Benzotriazol-2-yl)-4,6-	25973-55-1	>= 0.2 - < 1
ditertpentylphenol		
bis(2,2,6,6-tetramethyl-4-	52829-07-9	>= 0.2 - < 1
piperidyl)sebacate		

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.

No applicable information available.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

May cause an allergic skin reaction.

and effects, both acute a

Causes serious eye irritation.

delayed

May damage fertility or the unborn child.

Notes to physician : Treat symptomatically.

## **SECTION 5. FIRE-FIGHTING MEASURES**



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

Suitable extinguishing media : Water spray

Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Keep in suitable, closed containers for disposal.

## **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, well-ventilated

place.

Protect from direct sunlight. Store protected against freezing.

Materials to avoid : Observe VCI storage rules.

Further information on stor-

age stability

No data available

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
stearic acid	57-11-4	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		TWA value (Respirable fraction)	3 mg/m3	ACGIHTLV
		TWA (Inhal- able particu- late matter)	10 mg/m3	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
calcium carbonate	471-34-1	REL value (Total)	10 mg/m3	NIOSH
		REL value (Respirable)	5 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL



# **Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz**

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Dibutylbis(pentane-2,4-dionato-O,O')tin	22673-19-4	TWA value	0.1 mg/m3 (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m3 (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m3 (tin (Sn))	NIOSH
		PEL	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH





Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

TWA	0.1 mg/m3 (Tin)	OSHA P0
TWA	0.1 mg/m3 (Tin)	NIOSH REL

**Engineering measures** : No applicable information available.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures : Avoid contact with the skin, eyes and clothing.

No special measures necessary if stored and handled cor-

rectly.

Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : pigmented

Odor : odorless

Odor Threshold : No data available

pH : neutral to slightly alkaline

Melting point : No applicable information available.



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

Boiling point : No applicable information available.

Flash point : does not flash

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Self-ignition : not self-igniting

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure : No applicable information available.

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : 12.2 lb/USg (73 - 77 °F / 23 - 25 °C)

Bulk density : approx. 1.5 g/cm3

Solubility(ies)

Water solubility : slightly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No data available.

Autoignition temperature : No data available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Self-heating substances : No data available

Sublimation point : No applicable information available.



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

Molecular weight : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified based on available information.

#### **Product:**

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

#### Skin corrosion/irritation

Not classified based on available information.

#### **Product:**

Remarks : May cause skin irritation and/or dermatitis.

## Serious eye damage/eye irritation

Causes serious eye irritation.

#### **Product:**

Remarks : May cause irreversible eye damage.

### Respiratory or skin sensitization

## Skin sensitization

May cause an allergic skin reaction.



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

### Respiratory sensitization

Not classified based on available information.

**Product:** 

Remarks : Causes sensitization.

## Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

## Reproductive toxicity

May damage fertility or the unborn child.

### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

## **Aspiration toxicity**

Not classified based on available information.

#### **Product:**

No aspiration hazard expected.

#### **Further information**

**Product:** 

Remarks : No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

## Persistence and degradability

No data available

## **Bioaccumulative potential**

## **Components:**

## calcium carbonate:

Partition coefficient: n- : GLP: no

octanol/water Remarks: The value has not been determined because the

substance is inorganic.

stearic acid:

Partition coefficient: n-

octanol/water

Remarks: No data available.



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

log Pow: 8.23

Method: other (measured)

carbon black:

Partition coefficient: n-

octanol/water

Remarks: not applicable

N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

Partition coefficient: n- : log Pow: -0.82

octanol/water Method: other (calculated)

Dibutylbis(pentane-2,4-dionato-O,O')tin:

Partition coefficient: n-

octanol/water

Remarks: Study technically not feasible.

2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol:

Partition coefficient: n- :  $\log Pow: > 6.5 (73 \degree F / 23 \degree C)$ 

octanol/water pH: 6.4

Method: Partition coefficient (n-octanol/water), HPLC method.

log Pow: 7.3 (77 °F / 25 °C) Method: other (calculated)

bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate:

Partition coefficient: n- : log Pow: 0.35 (77 °F / 25 °C)

octanol/water pH: 7

Method: Partition coefficient (n-octanol/water), Shake-flask

method

**Mobility in soil**No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

#### **49 CFR**

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

### **US State Regulations**

## Pennsylvania Right To Know

calcium carbonate	471-34-1
Iron oxide	1309-37-1
Limestone	1317-65-3
carbon black	1333-86-4
Di-isononylphthalate	28553-12-0
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters,	68515-48-0
C9-rich	
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters,	68515-49-1
C10-rich	

#### **New Jersey Right To Know**

Limestone	1317-65-3
carbon black	1333-86-4

## California Prop. 65

WARNING: This product can expose you to chemicals including lead, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory





## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version SDS Number: Date of last issue: -Revision Date:

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:

## Flammability Health Instability 2 0

Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1)

1910.1000 **ACGIH** USA. ACGIH Threshold Limit Values (TLV)

American Conference of Governmental Industrial Hygienists -**ACGIHTLV** 

threshold limit values (US)

NIOSH NIOSH Pocket Guide to Chemical Hazards (US) USA. NIOSH Recommended Exposure Limits NIOSH REL

USA. OSHA - TABLE Z-1 Limits for Air Contaminants -OSHA PO

1910.1000

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-OSHA Z-1

its for Air Contaminants

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA 8-hour, time-weighted average ACGIH / STEL Short-term exposure limit

ACGIHTLV / STEL value Short Term Exposure Limit (STEL): ACGIHTLV / TWA value Time Weighted Average (TWA): Recommended exposure limit (REL): NIOSH / REL value

Time-weighted average concentration for up to a 10-hour NIOSH REL / TWA

workday during a 40-hour workweek

8-hour time weighted average OSHA P0 / TWA



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 08/07/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR



## Sikaflex HY 150 special bronze Formerly MSeal NP 150 spe brz

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260981 Date of first issue: 08/07/2020

TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN