Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB



Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

SECTION 1. IDENTIFICATION

Product name : Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB

Product code : 00000000055511022

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Oral) : 4

Acute toxicity (Dermal) : 4

Skin corrosion/irritation : 1B

Serious eye damage/eye

irritation

Category 1

Skin sensitization : Category 1

Reproductive toxicity : 2

Reproductive toxicity : 2

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 1

GHS label elements





Version Revision Date: SDS Number: Date of last issue: -

000000259986 1.0 08/17/2020 Date of first issue: 08/17/2020

Hazard pictograms









Signal Word Danger

Hazard Statements H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child. H314 Causes severe skin burns and eye damage. H302 + H312 Harmful if swallowed or in contact with skin.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P273 Avoid release to the environment.

P260 Do not breathe dust or mist.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P272 Contaminated work clothing should not be allowed out of the workplace.

P270 Do not eat, drink or smoke when using this product. P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth, Do NOT

induce vomiting.

P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.

P391 Collect spillage.

P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.





Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
2-piperazin-1-ylethylamine	140-31-8	>= 25 - < 50
4-nonylphenol, branched	84852-15-3	>= 25 - < 75
alpha-(2-Aminomethylethyl)-omega-	9046-10-0	>= 10 - < 15
(2-aminomethylethoxy)-		
poly(oxy(methyl-1,2-ethanediyl))		

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.

Immediately administer a corticosteroid from a con-

trolled/metered dose inhaler.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediately wash thoroughly with plenty of water, apply ster-

ile dressings, consult a skin specialist.

Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with difficul-

ty.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately wash affected eyes for at least 15 minutes under

running water with eyelids held open, consult an eye special-

ist.

Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB



Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

> Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Do NOT induce vomiting.

Immediately rinse mouth and then drink 200-300 ml of water.

seek medical attention.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

Harmful if swallowed or in contact with skin.

May cause an allergic skin reaction.

Causes serious eye damage.

Suspected of damaging fertility or the unborn child.

Causes severe burns.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Water spray

> Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

delayed

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Environmental precautions Prevent product from entering drains.





Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Further information on stor-

age stability

No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : No applicable information available.

Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB



Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupa-

tional exposure limits they must use appropriate certified

respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : amber

Odor : amine-like

Odor Threshold : No data available

pH : No data available

Melting point : No applicable information available.

Boiling point : 397 °F / 203 °C

Flash point : 200.01 °F / 93.34 °C

Evaporation rate : No applicable information available.

Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB



Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

Flammability (solid, gas) : No applicable information available.

Upper explosion limit / Upper

flammability limit

No data available.

Lower explosion limit / Lower

flammability limit

No data available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : 8.01 lb/USg (75 °F / 24 °C)

Bulk density : not applicable

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation temperature : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids



Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

carbon oxides nitrogen oxides Aldehydes Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or in contact with skin.

Product:

Acute oral toxicity : ATE: 1,649 mg/kg

Acute inhalation toxicity : ATE: > 20.0000 mg/l

Remarks: Determined for vapor

ATE: > 5.0000 mg/l

Remarks: Determined for mist

Acute dermal toxicity : ATE: 1,485 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB



Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information

Product:

Remarks : The product has not been tested. The statement has been

derived from the properties of the individual components.

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

alpha-(2-Aminomethylethyl)-omega-(2-aminomethylethoxy)- poly(oxy(methyl-1,2-ethanediyl)):

Toxicity to algae/aquatic : EC50 (Skeletonema costatum): 141.72 mg/l

plants Exposure time: 72 h
Test Type: static

Analytical monitoring: no

Method: Marine algal growth inhibition test with Skeletonema

costatum and Phaeodactylum tricornutum.

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

2-piperazin-1-ylethylamine:

Partition coefficient: n- : log Pow: -1.44 (77 °F / 25 °C)





Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

octanol/water Method: other (measured)

GLP: no

4-nonylphenol, branched:

Partition coefficient: n-

octanol/water

log Pow: 5.4 (73 °F / 23 °C)

pH: 5.7

Method: Partition coefficient (n-octanol/water), HPLC method.

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

Do not discharge product into the environment without control. May cause long-term adverse effects in the aquatic environ-

ment.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3267

Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(NONYLPHENOL, POLYOXYPROPYLENEDIAMINE)

Class : 8
Packing group : III
Labels : 8

IATA-DGR

UN/ID No. : UN 3267

Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.



Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

(NONYLPHENOL, POLYOXYPROPYLENEDIAMINE)

Class : 8 Packing group : III

Labels : Corrosive Packing instruction (cargo : 856

aircraft)

Packing instruction (passen: 852

ger aircraft)

IMDG-Code

UN number : UN 3267

Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(NONYLPHENOL, POLYOXYPROPYLENEDIAMINE)

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3267

Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(NONYLPHENOL, POLYOXYPROPYLENEDIAMINE)

Class : 8 Packing group : III

Labels : CORROSIVE

ERG Code : 153 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

4-nonylphenol, 84852-15-3

branched

US State Regulations

Pennsylvania Right To Know

2-piperazin-1-ylethylamine 140-31-8 4-nonylphenol, branched 84852-15-3

New Jersey Right To Know

BUILDING TRUST

Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

2-piperazin-1-ylethylamine

140-31-8

The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:

Flammability Health 3 0 Instability

Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada): ECx - Concentration associated with x% response: EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level;



Sikafloor BC 500 FS Part B Formerly MTop BC 500FS PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/17/2020 000000259986 Date of first issue: 08/17/2020

NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/17/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE, FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN