



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

### SECTION 1. IDENTIFICATION

Product name : SikaForce®-800 (formerly SikaForce®-7800) Part B

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### **GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2B

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

#### **GHS label elements**



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

Hazard pictograms :



Signal Word :

Danger

Hazard Statements :

H315 + H320 Causes skin and eye irritation.  
H317 May cause an allergic skin reaction.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements :

**Prevention:**

P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves.  
P284 Wear respiratory protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

None known.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomers and homologues	9016-87-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	$\geq 90 - \leq 100$

Actual concentration is withheld as a trade secret

---

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitizing effects  
Asthmatic appearance



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

Cough  
Respiratory disorder  
Allergic reactions  
Headache  
Causes skin and eye irritation.  
May cause an allergic skin reaction.  
Harmful if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

- Advice on safe handling** : Avoid exceeding the given occupational exposure limits (see section 8).  
 Do not get in eyes, on skin, or on clothing.  
 For personal protection see section 8.  
 Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage** : Store in original container.  
 Keep in a well-ventilated place.  
 Observe label precautions.  
 Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	C	0.02 ppm 0.2 mg/m3	OSHA Z-1
		C	0.02 ppm 0.2 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

- Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

#### Personal protective equipment

- Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : gray
- Odor : slight
- Odor Threshold : No data available
- pH : substance/mixture reacts with water
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 212 °F / 100 °C  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapor pressure : 0.01 hpa



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

Relative vapor density	:	No data available
Density	:	ca. 1.23 g/cm <sup>3</sup> (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	ca. 35,000 mPa.s (68 °F / 20 °C)
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	1.5 g/l A+B Combined

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

**Acute toxicity**  
Harmful if inhaled.



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

### Components:

#### **Diphenylmethanediisocyanate, isomeres and homologues:**

- Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg
- Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgment  
Assessment: The component/mixture is moderately toxic after short term inhalation.
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

#### **Skin corrosion/irritation**

Causes skin irritation.

#### **Serious eye damage/eye irritation**

Causes eye irritation.

#### **Respiratory or skin sensitization**

##### **Skin sensitization**

May cause an allergic skin reaction.

##### **Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

##### **Germ cell mutagenicity**

Not classified due to lack of data.

##### **Carcinogenicity**

Not classified due to lack of data.

**IARC** Not applicable

**OSHA** Not applicable

**NTP** Not applicable

##### **Reproductive toxicity**

Not classified due to lack of data.

##### **STOT-single exposure**

May cause respiratory irritation.

##### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure if inhaled.  
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

##### **Aspiration toxicity**

Not classified due to lack of data.





## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l  
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

##### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

Not regulated as a dangerous good

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

---

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Acute toxicity (any route of exposure)  
Respiratory or skin sensitization  
Specific target organ toxicity (single or repeated exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Diphenylmethanediisocyanate, isomers and homologues	9016-87-9	>= 90 - <= 100 %
---	-----------	------------------

### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.



## SikaForce®-800 (formerly SikaForce®-7800) Part B

Revision Date 08/31/2023

Print Date 08/31/2023

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / C	:	Ceiling

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 08/31/2023

100000005942  
US / Z8