

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version 2.0      Revision Date: 07/09/2024      SDS Number: 000000268971      Date of last issue: 09/29/2020  
Date of first issue: 09/29/2020

---

### SECTION 1. IDENTIFICATION

Product name : Pigment Brown Oxide 888-1572I  
Product code : 000000000056435077

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC  
Address : 201 POLITO AVE  
Lyndhurst NJ 07071  
Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Coloring agents, pigments  
Restrictions on use : Reserved for industrial and professional use.


---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Oral) : Category 4

#### GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H302 Harmful if swallowed.

Precautionary Statements : **Prevention:**  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.

**Response:**  
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version 2.0      Revision Date: 07/09/2024      SDS Number: 000000268971      Date of last issue: 09/29/2020  
Date of first issue: 09/29/2020

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aqueous solution

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Iron oxide	1309-37-1	$\geq 30 - < 50$
ethylene glycol	107-21-1	$\geq 20 - < 30$
talc	14807-96-6	$\geq 10 - < 20$
Diethylene glycol	111-46-6	$\geq 5 - < 10$
Nonylphenol, branched, ethoxylated	68412-54-4	$\geq 5 - < 10$
Carbon black	1333-86-4	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety.  
Remove contaminated clothing.
- If inhaled : If generated vapours are inhaled, move to fresh air.  
Seek medical attention.
- In case of skin contact : Wash thoroughly with soap and water  
Under no circumstances should organic solvent be used.  
If irritation develops, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running  
water with eyelids held open, consult an eye specialist.  
Remove contact lenses, if present, after first 5 minutes, then  
continue rinsing for an additional 15 minutes.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.  
DO NOT induce vomiting unless directed to do so by a physi-  
cian or poison control center.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
- Notes to physician : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version 2.0      Revision Date: 07/09/2024      SDS Number: 000000268971      Date of last issue: 09/29/2020  
Date of first issue: 09/29/2020

---

- Unsuitable extinguishing media : water jet
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Sweep/shovel up.  
Dispose of absorbed material in accordance with regulations.

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from sources of ignition - No smoking.  
The relevant fire protection measures should be noted.
- Advice on safe handling : Avoid contact with the skin, eyes and clothing.
- Conditions for safe storage : Store in original container.  
Keep containers tightly closed in a cool, well-ventilated place.  
Protect from direct sunlight.
- Further information on storage stability : PROTECT FROM FREEZING DURING THE COLD-SEASON (BELOW 40°F / 5°C ).

---

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
------------	---------	------------	-----------------	-------

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version 2.0      Revision Date: 07/09/2024      SDS Number: 000000268971      Date of last issue: 09/29/2020  
 Date of first issue: 09/29/2020

		(Form of exposure)	ters / Permissible concentration	
Iron oxide	1309-37-1	TWA (Respirable particulate matter)	5 mg/m3	ACGIH
		TWA (dust and fume)	5 mg/m3 (Iron)	NIOSH REL
		TWA (Fumes)	10 mg/m3	OSHA Z-1
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Fumes)	10 mg/m3	OSHA P0
ethylene glycol	107-21-1	TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
Diethylene glycol	111-46-6	TWA	10 mg/m3	US WEEL
Carbon black	1333-86-4	TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL

**Engineering measures** : Ensure adequate ventilation.

**Personal protective equipment**

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version	Revision Date:	SDS Number:	Date of last issue: 09/29/2020
2.0	07/09/2024	000000268971	Date of first issue: 09/29/2020

---

Use NIOSH approved respiratory protection.

### Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Avoid contact with the skin, eyes and clothing.  
No special measures necessary if stored and handled correctly.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid, paste

Color : brown

Odor : of glycol

Odor Threshold : not determined

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : > 212 °F / > 100 °C

Flash point : 235 °F / 113 °C

Method: estimate

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version	Revision Date:	SDS Number:	Date of last issue: 09/29/2020
2.0	07/09/2024	000000268971	Date of first issue: 09/29/2020

---

Evaporation rate	:	No data available
Flammability (liquids)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available.
Relative vapor density	:	No data available
Relative density	:	1.7
Density	:	1.7 g/cm <sup>3</sup> (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	Not an oxidizer.
Sublimation point	:	No data available
Molecular weight	:	Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version	Revision Date:	SDS Number:	Date of last issue: 09/29/2020
2.0	07/09/2024	000000268971	Date of first issue: 09/29/2020

---

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Harmful if swallowed.

#### Product:

Acute oral toxicity : Acute toxicity estimate: 2,000 mg/kg  
Method: Calculation method

#### Skin corrosion/irritation

Not classified due to lack of data.

#### Serious eye damage/eye irritation

Not classified due to lack of data.

#### Respiratory or skin sensitization

##### Skin sensitization

Not classified due to lack of data.

##### Respiratory sensitization

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

IARC Group 2B: Possibly carcinogenic to humans  
Carbon black

1333-86-4

#### Reproductive toxicity

Not classified due to lack of data.

#### STOT-single exposure

Not classified due to lack of data.

#### STOT-repeated exposure

Not classified due to lack of data.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version	Revision Date:	SDS Number:	Date of last issue: 09/29/2020
2.0	07/09/2024	000000268971	Date of first issue: 09/29/2020

---

### Aspiration toxicity

Not classified due to lack of data.

### Further information

#### Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

#### Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version 2.0      Revision Date: 07/09/2024      SDS Number: 000000268971      Date of last issue: 09/29/2020  
Date of first issue: 09/29/2020

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethylene glycol	107-21-1	5000	25000

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethylene glycol	107-21-1	>= 20 - < 30 %
Nonylphenol, branched, ethoxylated	68412-54-4	>= 5 - < 10 %

#### US State Regulations

##### Pennsylvania Right To Know

Iron oxide	1309-37-1
ethylene glycol	107-21-1
talc	14807-96-6
Diethylene glycol	111-46-6
Carbon black	1333-86-4

##### New Jersey Right To Know

Iron oxide	1309-37-1
ethylene glycol	107-21-1
talc	14807-96-6
Carbon black	1333-86-4

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version 2.0      Revision Date: 07/09/2024      SDS Number: 000000268971      Date of last issue: 09/29/2020  
Date of first issue: 09/29/2020

### California Prop. 65

WARNING: This product can expose you to chemicals including Carbon black, which is/are known to the State of California to cause cancer, and ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).


### The ingredients of this product are reported in the following inventories:

- TSCA : All substances listed as active on the TSCA inventory
- DSL : All components of this product are on the Canadian DSL

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / C : Ceiling limit

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Pigment Brown Oxide 888-1572I

Version	Revision Date:	SDS Number:	Date of last issue: 09/29/2020
2.0	07/09/2024	000000268971	Date of first issue: 09/29/2020

---

OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average
US WEEL / TWA	:	8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/09/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN