



**SECTION 1. IDENTIFICATION**

Product name : Sikadur®-506 RC Trowel Aggregate

Company name : Sika Corporation  
 201 Polito Avenue  
 Lyndhurst, NJ 07071  
 USA  
 www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
 INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity : Category 3 (Respiratory system)  
 - single exposure

Specific target organ toxicity : Category 1 (Lungs)  
 - repeated exposure

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H335 May cause respiratory irritation.  
 H350 May cause cancer by inhalation.  
 H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**



P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Mixtures****Components**

| Chemical name                         | CAS-No.    | Classification  | Concentration (% w/w) |
|---------------------------------------|------------|---|-----------------------|
| Quartz (SiO <sub>2</sub> ) >5 $\mu$ m | 14808-60-7 | Carc. 1A; H350i<br>STOT RE 1; H372<br>STOT SE 3; H335 | $\geq 90 - \leq 100$  |
| aluminium oxide                       | 1344-28-1  |   | $\geq 1 - < 5$        |

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this material safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.



- Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Prolonged exposure can cause silicosis.  
irritant effects  
Cough  
Respiratory disorder  
May cause respiratory irritation.  
May cause cancer by inhalation.  
Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Avoid breathing dust.  
Deny access to unprotected persons.
- Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.



Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Avoid dust formation.  
Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

Further information on storage stability : Keep in a dry place.  
No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

| Components                      | CAS-No.    | Value type (Form of exposure)       | Control parameters / Permissible concentration | Basis     |
|---------------------------------|------------|-------------------------------------|--|-----------|
| Quartz (SiO <sub>2</sub> ) >5µm | 14808-60-7 | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup>                        | ACGIH     |
|                                 |            | TWA (Respirable dust)               | 0.05 mg/m <sup>3</sup>                         | OSHA Z-1  |
|                                 |            | TWA (respirable)                    | 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2    | OSHA Z-3  |
|                                 |            | TWA (respirable)                    | 250 mppcf / %SiO <sub>2</sub> +5               | OSHA Z-3  |
|                                 |            | TWA (respirable dust fraction)      | 0.1 mg/m <sup>3</sup>                          | OSHA P0   |
|                                 |            | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup> (Silica)               | ACGIH     |
|                                 |            | PEL (respirable)                    | 0.05 mg/m <sup>3</sup>                         | OSHA CARC |

**Sikadur®-506 RC Trowel Aggregate**



Revision Date 08/16/2022

Print Date 08/17/2022

|                 |           |                                     |                      |          |
|-----------------|-----------|-------------------------------------|----------------------|----------|
|                 |           | TWA (respirable dust fraction)      | 0.1 mg/m3            | OSHA P0  |
|                 |           | TWA (Respirable particulate matter) | 0.025 mg/m3          | ACGIH    |
|                 |           | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH    |
| aluminium oxide | 1344-28-1 | TWA (total dust)                    | 15 mg/m3             | OSHA Z-1 |
|                 |           | TWA (respirable fraction)           | 5 mg/m3              | OSHA Z-1 |
|                 |           | TWA (Total dust)                    | 10 mg/m3             | OSHA P0  |
|                 |           | TWA (respirable dust fraction)      | 5 mg/m3              | OSHA P0  |
|                 |           | TWA (Respirable particulate matter) | 1 mg/m3 (Aluminum)   | ACGIH    |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Particles of nuisance dust**

| Form of exposure    | Value type | Control parameters | Basis    |
|---------------------|------------|--------------------|----------|
| total dust          | TWA        | 15 mg/m3           | OSHA Z-3 |
| respirable fraction | TWA        | 5 mg/m3            | OSHA Z-3 |

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.



|                          |   |   |
|--------------------------|---|---|
| Hand protection          | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.   |
| Eye protection           | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.   |
| Skin and body protection | : | Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.  |
| Hygiene measures         | : | Avoid contact with skin, eyes and clothing.<br>Wash hands before breaks and immediately after handling the product.<br>Remove contaminated clothing and protective equipment before entering eating areas.<br>Avoid breathing dust. |

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

|  |   |                        |
|--|---|------------------------|
| Appearance                                       | : | granular powder        |
| Color  | : | tan, gray, white       |
| Odor   | : | odorless               |
| Odor Threshold                                   | : | No data available      |
| pH   | : | 6 - 8                  |
| Melting point/range                              | : | 3,110 °F / 1,710 °C    |
| Boiling point/boiling range                      | : | 4,046 °F / 2,230 °C    |
| Flash point                                      | : | Not applicable         |
| Evaporation rate                                 | : | No data available      |
| Flammability (solid, gas)                        | : | No data available      |
| Upper explosion limit / Upper flammability limit | : | No data available      |
| Lower explosion limit / Lower flammability limit | : | No data available      |
| Vapor pressure                                   | : | No data available      |
| Relative vapor density                           | : | No data available      |
| Density  | : | 2.65 g/cm <sup>3</sup> |



|  |                     |
|--|---------------------|
| Solubility(ies)                          |                     |
| Water solubility                         | : negligible        |
| Solubility in other solvents             | : No data available |
| Partition coefficient: n-octanol/water   | : No data available |
| Autoignition temperature                 | : No data available |
| Decomposition temperature                | : No data available |
| Viscosity                                |                     |
| Viscosity, dynamic                       | : No data available |
| Viscosity, kinematic                     | : Not applicable    |
| Explosive properties                     | : No data available |
| Oxidizing properties                     | : No data available |
| Volatile organic compounds (VOC) content | : Not applicable    |

---

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |
|------------------------------------|---|
| Reactivity                         | : No dangerous reaction known under conditions of normal use. |
| Chemical stability                 | : The product is chemically stable.                           |
| Possibility of hazardous reactions | : Stable under recommended storage conditions.                |
| Conditions to avoid                | : No data available   |
| Incompatible materials             | : No data available   |
| Hazardous decomposition products   | : No decomposition if stored and applied as directed.         |

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

Not classified based on available information.

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.



**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer by inhalation.

|             |   |            |
|-------------|---|------------|
| <b>IARC</b> | Group 1: Carcinogenic to humans<br>Quartz (SiO <sub>2</sub> )<br>(Silica dust, crystalline)           | 14808-60-7 |
| <b>OSHA</b> | OSHA specifically regulated carcinogen<br>Quartz (SiO <sub>2</sub> )<br>(crystalline silica)          | 14808-60-7 |
| <b>NTP</b>  | Known to be human carcinogen<br>Quartz (SiO <sub>2</sub> )<br>(Silica, Crystalline (Respirable Size)) | 14808-60-7 |

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

Causes damage to organs (Lungs) through prolonged or repeated exposure.  
Prolonged exposure can cause silicosis.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

**Product:**

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available





**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Domestic regulation**

**49 CFR**

Not regulated as a dangerous good

---

**SECTION 15. REGULATORY INFORMATION**

**TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)



**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

aluminium oxide 1344-28-1 >= 1 - < 5 %

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

#### California Prop. 65

**⚠ WARNING:** This product can expose you to chemicals including Quartz (SiO<sub>2</sub>) >5µm, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

---

## SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens  
 OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)  
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  
 OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts  
 ACGIH / TWA : 8-hour, time-weighted average  
 OSHA CARC / PEL : Permissible exposure limit (PEL)  
 OSHA P0 / TWA : 8-hour time weighted average  
 OSHA Z-1 / TWA : 8-hour time weighted average  
 OSHA Z-3 / TWA : 8-hour time weighted average

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Safety Data Sheet

**Sikadur®-506 RC Trowel Aggregate**



Revision Date 08/16/2022

Print Date 08/17/2022

---

00000606496  
US / Z8