

# PRODUCT DATA SHEET

## G459 GRID STRIP FLASHING MEMBRANE

G459 Grid Strip Flashing Membrane is a heat-weldable thermoplastic waterproofing membrane used in conjunction with Sikaflex-11 FC adhesive to construct sub-membrane water stops as part of the Sika Containment Grid Waterproofing System.

### PRODUCT INFORMATION

#### USES

The G459 Grid Strip Flashing Membrane is specially formulated for grid strip installations using Sikaflex-11 FC adhesive. The backside of the membrane is resistant to asphalt and most liquid coatings including urethane. Sika Sarnafil recommends in field testing for compatibility.

#### AREAS OF APPLICATION

- Flashing pipes
- Inside/outside corners
- Unusual shaped penetrations

#### FEATURES / BENEFITS

- Reinforced for dimensional stability and durability
- Lacquer coated top surface to reduce dirt pick up
- Convenient pre-cut rolls

### PRODUCT DATA

#### FORM

#### COMPOSITION

High-quality, PVC membrane containing pigments, stabilizers, ultraviolet absorbers, and a fiberglass carrier sheet.

#### COLOR

- Top: White
- Bottom: Tan

#### PACKAGING

- 1 ft x 100 ft (0.3 m x 30.5 m) rolls, 39 lbs (17 kg) per roll

**STORAGE****STORAGE CONDITIONS**

Store rolls standing on end on pallets and fully protected from the weather with clean canvas tarpaulins. Unvented polyethylene tarpaulins are not accepted due to the accumulation of moisture beneath the tarpaulin in certain weather conditions that may affect the ease of membrane weldability.

**TECHNICAL DATA**

<b>TYPICAL PHYSICAL PROPERTIES*</b>		
<b>Properties</b>	<b>ASTM Test Method</b>	<b>Typical Results</b>
Reinforcing Material	--	Polyester
Reinforcement/Carrier	--	Fiberglass
Overall Thickness, mil	D638	1.5
Weight, kg/m <sup>2</sup>	--	0.39 (1.88)
Tensile Strength, psi (MPa)	D638	1600 (11.1)
Elongation at Break, % M.D. <sup>1</sup> & C.M.D. <sup>1</sup>	D638	270 & 270
Seam Strength, % of original <sup>2</sup>	D638	90
Retention of Properties After Heat Aging	D3045	--
Tensile Strength, % of original	D638	95
Elongation, % of original	D638	95
Tearing Resistance, lbf (N)	D1004	22 (95)
Low Temperature Bend, -40 °F (-40 °C)	D2136	Pass
Linear Dimensional Change, %	D1204	0.002
Weight Change After Immersion in Water, %	D570	2.0
Static Puncture Resistance, 33 lbf (15 kg)	D5602	Pass
Dynamic Puncture Resistance, 7.3 ft-lbf (10 J)	D5635	Pass
VOC Content, g/L	--	0

\* Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions, and curing conditions.

<sup>1</sup> M.D. = Machine Direction, C.M.D. = Cross Machine Direction

<sup>2</sup> Failure occurs through membrane rupture not seam failure.

---

## SYSTEM INFORMATION

---

<b>APPLICATION</b>	Sarnafil G459 Grid Strip flashing membrane is installed by an authorized Sika Sarnafil Waterproofing Applicator. The flashing can be installed horizontally or vertically depending on the specific detail. Consult with Sika Sarnafil specifications.
<b>AVAILABILITY</b>	From Sika Sarnafil Authorized Applicators when used within a Sika Sarnafil Roofing or Waterproofing System. Contact Sika Sarnafil or visit our website <a href="http://www.sikacorp.com">www.sikacorp.com</a> for further information.
<b>MAINTENANCE</b>	G459 flashing membrane requires no maintenance.
<b>WARRANTY</b>	As a Sika Sarnafil-supplied accessory, G459 flashing membrane is included in Sika Sarnafil's Standard or System Warranty to the Building Owner.

---

<b>LEGAL NOTES</b>	<p>All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at <a href="http://usa.sarnafil.sika.com">usa.sarnafil.sika.com</a> or by calling 800-451-2504.</p> <p><b>Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at <a href="http://usa.sarnafil.sika.com">usa.sarnafil.sika.com</a> or by calling Sika's Technical Service Department at 800-451-2504. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.</b></p> <p>Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.</p> <p><b>NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.</b></p>
--------------------	--

---

<b>SIKA CORPORATION – ROOFING</b>	<b>UNITED STATES</b> 100 Dan Road Canton, MA 02021 800-451-2504 (p) 781-828-5365 (f) <a href="http://usa.sarnafil.sika.com">usa.sarnafil.sika.com</a> <a href="mailto:webmaster.sarnafil@us.sika.com">webmaster.sarnafil@us.sika.com</a>	<b>SIKA CANADA INC.</b> 6915 Davand Drive Mississauga, ON L5T 1L5 905-795-3177 (p) 905-795-3192 (f) <a href="http://can.sika.com">can.sika.com</a> <a href="mailto:marketing.construction@ca.sika.com">marketing.construction@ca.sika.com</a>
-----------------------------------	--	---

---