

# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version 2.0      Revision Date: 10/05/2021      SDS Number: 000000261228      Date of last issue: 09/04/2020  
Date of first issue: 09/04/2020

---

### SECTION 1. IDENTIFICATION

Product name : Sikaflex-900 target red Formerly MSeal 900 Target Red  
Product code : 000000000050694249

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC  
Address : 201 POLITO AVE  
Lyndhurst NJ 07071  
Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS).

#### GHS label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS).

#### Other hazards

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : polymers  
inorganic compounds

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Titanium dioxide	13463-67-7	>= 20 - < 50
Iron oxide	1309-37-1	>= 7 - < 10
C.I. Pigment Blue 15	147-14-8	>= 3 - < 5
aluminium hydroxide	21645-51-2	>= 0 - < 3
Carbon black	1333-86-4	>= 1 - < 3

---

### SECTION 4. FIRST AID MEASURES

# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2020
2.0	10/05/2021	000000261228	Date of first issue: 09/04/2020

---

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
Under no circumstances should organic solvent be used.  
If irritation develops, seek medical attention.
- In case of eye contact : Remove contact lenses, if present.  
Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.  
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black  
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment : Wear a self-contained breathing apparatus.
-

# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version 2.0      Revision Date: 10/05/2021      SDS Number: 000000261228      Date of last issue: 09/04/2020  
Date of first issue: 09/04/2020

for fire-fighters

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.  
Wear eye/face protection.  
If exposed to high vapour concentration, leave area immediately.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
C.I. Pigment Blue 15	147-14-8	TWA	1 mg/m <sup>3</sup> (Copper)	NIOSH REL

# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version 2.0      Revision Date: 10/05/2021      SDS Number: 000000261228      Date of last issue: 09/04/2020  
Date of first issue: 09/04/2020

Iron oxide	1309-37-1	TWA (Respirable particulate matter)	5 mg/m3	ACGIH
		TWA (dust and fume)	5 mg/m3 (Iron)	NIOSH REL
		TWA (Fumes)	10 mg/m3	OSHA Z-1
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Fumes)	10 mg/m3	OSHA P0
Carbon black	1333-86-4	TWA value (Inhalable fraction)	3 mg/m3	ACGIHTLV
		PEL	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		REL value	0.1 mg/m3 (Polycyclic aromatic hydrocarbons (PAH))	NIOSH
		TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (Titanium dioxide)	10 mg/m3	ACGIH
aluminium hydroxide	21645-51-2	TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH

**Engineering measures** : Ensure adequate ventilation.

### Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version 2.0      Revision Date: 10/05/2021      SDS Number: 000000261228      Date of last issue: 09/04/2020  
Date of first issue: 09/04/2020

---

### Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : light protective clothing

Protective measures : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : pasty

Color : pigmented

Odor : product specific

Odor Threshold : No data available

pH : slightly alkaline

Melting point : No applicable information available.

Boiling point : No data available

Flash point : Not applicable

Evaporation rate : No applicable information available.

Flammability (solid, gas) : Not classified as a flammability hazard

# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2020
2.0	10/05/2021	000000261228	Date of first issue: 09/04/2020

---

Self-ignition	:	not self-igniting
Upper explosion limit / Upper flammability limit	:	No applicable information available.
Lower explosion limit / Lower flammability limit	:	No applicable information available.
Vapor pressure	:	No data available
Relative vapor density	:	No applicable information available.
Relative density	:	No applicable information available.
Density	:	
Bulk density	:	1,800 - 2,400 kg/m <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No applicable information available.
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as pre-

# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2020
2.0	10/05/2021	000000261228	Date of first issue: 09/04/2020

---

scribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitization

##### Skin sensitization

Not classified based on available information.

##### Respiratory sensitization

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### Further information

#### Product:

# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version 2.0	Revision Date: 10/05/2021	SDS Number: 000000261228	Date of last issue: 09/04/2020 Date of first issue: 09/04/2020
----------------	------------------------------	-----------------------------	---

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

#### Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good



# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version 2.0      Revision Date: 10/05/2021      SDS Number: 000000261228      Date of last issue: 09/04/2020  
Date of first issue: 09/04/2020

---

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

### Special precautions for user

Not applicable

---

## SECTION 15. REGULATORY INFORMATION

### US State Regulations

#### Pennsylvania Right To Know

Titanium dioxide	13463-67-7
Silicon dioxide	7631-86-9
Carbon black	1333-86-4
Iron oxide	1309-37-1

#### New Jersey Right To Know

Titanium dioxide	13463-67-7
Carbon black	1333-86-4
C.I. Pigment Blue 15	147-14-8
Iron oxide	1309-37-1
Silicon dioxide	7631-86-9

#### California Prop. 65

WARNING: This product can expose you to chemicals including Carbon black, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

---

## SECTION 16. OTHER INFORMATION

### Further information


# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red




Version 2.0      Revision Date: 10/05/2021      SDS Number: 000000261228      Date of last issue: 09/04/2020  
Date of first issue: 09/04/2020

### NFPA 704:



### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / REL value : Recommended exposure limit (REL):
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration asso-

# SAFETY DATA SHEET

## Sikaflex-900 target red Formerly MSeal 900 Target Red



Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2020
2.0	10/05/2021	000000261228	Date of first issue: 09/04/2020

---

ciated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10/05/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN