

Revision Date 12/06/2024 Print Date 12/06/2024

**SECTION 1. IDENTIFICATION** 

Product name : Sikalastic®-720 One Shot Arctic Part A

Company name : Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300

INTERNATIONAL: +1-703-527-3887

Recommended use of the

chemical and restrictions on

use

For further information, refer to product data sheet.

### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Inhalation) : Category 4

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system)

**GHS label elements** 

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.



Revision Date 12/06/2024 Print Date 12/06/2024

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

### **Precautionary Statements**

### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist or vapors.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P284 Wear respiratory protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.



# Sikalastic®-720 One Shot Arctic Part A

Revision Date 12/06/2024 Print Date 12/06/2024

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

### **Mixtures**

### Components

Chemical name	CAS-No.	Classification	Concentra-
			tion (% w/w)
Hexamethylene-1,6-diisocyanate	28182-81-2	Acute Tox. 4; H332	>= 10 - < 20
Homopolymer		Skin Sens. 1; H317	
		STOT SE 3; H335	
aliphatic polyisocyanate 1	164250-92-4	Acute Tox. 4; H332	>= 10 - < 20
		Skin Sens. 1B; H317	
		STOT SE 3; H335	
propylene carbonate	108-32-7	Eye Irrit. 2A; H319	>= 5 - < 10
Hexanedioic acid, polymer with 1,4-	29891-05-2	Acute Tox. 4; H332	>= 5 - < 10
butanediol, 1,6-diisocyanatohexane,		Skin Sens. 1B; H317	
2,2-dimethyl-1,3-propanediol and		STOT SE 3; H335	
1,6-hexanediol			
Isophorondiisocyanate homopoly-	53880-05-0	Skin Sens. 1B; H317	>= 5 - < 10
mer		STOT SE 3; H335	
3-isocyanatomethyl-3,5,5-	4098-71-9	Acute Tox. 1; H330	>= 0.1 - < 1
trimethylcyclohexyl isocyanate		Skin Corr. 1C; H314	
		Eye Dam. 1; H318	
		Resp. Sens. 1; H334	
		Skin Sens. 1; H317	
		STOT SE 3; H335	
Pentamethyl piperidylsebacate	41556-26-7	Skin Sens. 1A; H317	>= 0.1 - < 1
		Repr. 2; H361	
4-morpholinecarbaldehyde	4394-85-8	Skin Sens. 1; H317	>= 0.1 - < 1
Hydroxyphenyl-benzotriazol deri-	104810-47-1	Skin Sens. 1A; H317	>= 0.1 - < 1
vates			
Poly(oxy-1,2-ethanediyl), .alpha[3-	104810-48-2	Skin Sens. 1A; H317	>= 0.1 - < 1
[3-(2H-benzotriazol-2-yl)-5-(1,1-			
dimethylethyl)-4-hydroxyphenyl]-1-			
oxopropyl]omegahydroxy-			
methyl 1,2,2,6,6-pentamethyl-4-	82919-37-7	Skin Sens. 1A; H317	>= 0.1 - < 1
piperidyl sebacate		Repr. 2; H361	

Actual concentration is withheld as a trade secret

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.



# Sikalastic®-720 One Shot Arctic Part A

Revision Date 12/06/2024 Print Date 12/06/2024

Take off contaminated clothing and shoes immediately. In case of skin contact

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitizing effects

Asthmatic appearance

Cough

Respiratory disorder Allergic reactions

Headache

May cause an allergic skin reaction.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation.

Suspected of damaging fertility or the unborn child.

Notes to physician Treat symptomatically.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.



Revision Date 12/06/2024 Print Date 12/06/2024

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

### **SECTION 7. HANDLING AND STORAGE**

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	TWA	0.005 ppm	OSHA P0
		STEL	0.02 ppm	OSHA P0



Revision Date 12/06/2024 Print Date 12/06/2024

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : gray

Odor : mild

Odor Threshold : No data available



Revision Date 12/06/2024 Print Date 12/06/2024

pH : Not applicable

Melting point/ range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Flash point :  $> 199.99 \,^{\circ}\text{F} / > 93.33 \,^{\circ}\text{C}$ 

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : 0.04 hpa

Relative vapor density : No data available

Density : ca. 1.23 g/ml (74.7 °F / 23.7 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (104 °F / 40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

44 g/l

A+B+C Combined

### **SECTION 10. STABILITY AND REACTIVITY**



Revision Date 12/06/2024 Print Date 12/06/2024

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Harmful if inhaled.

#### **Components:**

### Hexamethylene-1,6-diisocyanate Homopolymer:

Acute oral toxicity : LD50 Oral (Rat): > 2,500 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgment

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

### 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4,814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.031 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 7,000 mg/kg

#### Skin corrosion/irritation

Not classified due to lack of data.

### Serious eye damage/eye irritation

Not classified due to lack of data.



# Sikalastic®-720 One Shot Arctic Part A

Revision Date 12/06/2024 Print Date 12/06/2024

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

IARC Group 2B: Possibly carcinogenic to humans

Titanium dioxide (> 10 μm) 13463-67-7

OSHA Not applicable

NTP Not applicable

### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

### STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

### **Aspiration toxicity**

Not classified due to lack of data.

#### **Further information**

#### **Product:**

Remarks : Titanium dioxide (13463-67-7)

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been charac-



# Sikalastic®-720 One Shot Arctic Part A

Revision Date 12/06/2024 Print Date 12/06/2024

terized as a potential carcinogen by either NTP or OSHA.

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

#### **Components:**

### Hexamethylene-1,6-diisocyanate Homopolymer:

Toxicity to daphnia and other : EC50 (Daphnia): > 100 mg/l aquatic invertebrates Exposure time: 48 h

### Persistence and degradability

No data available

### **Bioaccumulative potential**

No data available

### Mobility in soil

No data available

#### Other adverse effects

#### **Product:**

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulations**

#### **IATA-DGR**

Not regulated as a dangerous good



# Sikalastic®-720 One Shot Arctic Part A

Revision Date 12/06/2024 Print Date 12/06/2024

**IMDG-Code** 

Not regulated as a dangerous good

**Domestic regulation** 

**49 CFR** 

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

TSCA list : All chemical substances in this product are either listed as ac-

tive on the TSCA Inventory or are in compliance with a TSCA

Inventory exemption.

The following substance(s) is/are subject to a Significant New Use Rule:

triphenyl phosphate 115-86-6 See 40 CFR 721.11780; Proposed

Rule

No substances are subject to TSCA 12(b) export notification requirements.

### **CERCLA Reportable Quantity**

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

Respiratory or skin sensitization

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

hexachloroben- 118-74-1 < 0.1 %

zene

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

### California Prop. 65

⚠

**WARNING:** This product can expose you to chemicals including Titanium dioxide, which is known to the State of California to cause cancer, and methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Revision Date 12/06/2024 Print Date 12/06/2024

### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA P0 / TWA : 8-hour time weighted average OSHA P0 / STEL : Short-term exposure limit

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 12/06/2024

100000054028 US / Z8