

## PRODUCT DATA SHEET

# Sika® Reemat Premium

Randomly oriented glass fiber reinforcement for Sikalastic® roofing and waterproofing systems

### PRODUCT DESCRIPTION

Surface treated, randomly oriented glass fiber reinforcement used to enhance the strength and durability of Sikalastic® resins 621 TC, 624 WP, 641 Lo-VOC, 646 Lo-VOC and 644 Lo-VOC roofing and waterproofing systems.

### USES

- Ideal for roofing and waterproofing applications when detailing complex and geometrically shaped surfaces or when accessibility is limited
- Suitable for applications where visibility of reinforcement overlaps is an aesthetic concern

### PRODUCT INFORMATION

<b>Packaging</b>	<ul style="list-style-type: none"> <li>▪ 49" (1.3 m) w x 295' (90 m), individually bagged rolls</li> <li>▪ 12" (0.3 m) w x 295' (90 m), individually bagged rolls</li> </ul>
<b>Shelf Life</b>	N/A
<b>Storage Conditions</b>	Store rolls on end, and not on their side in original unopened and undamaged sealed packaging in dry conditions. Recommended to condition material to 50°-77°F (10°-25°C) before using to match liquid resin.
<b>Appearance / Color</b>	Off-White
<b>Dimensions</b>	Gross Area: 1,180 ft <sup>2</sup> (109.6 m <sup>2</sup> ) 295 ft <sup>2</sup> (27 m <sup>2</sup> )

### BASIS OF PRODUCT DATA

Results may differ based upon statistical variations

### CHARACTERISTICS / ADVANTAGES

- Provides maximum conformability to uneven substrates
- Creates strong reinforced roofing and waterproofing membranes with enhanced tensile strength
- Increases puncture and tear resistance

### APPROVALS / STANDARDS

- FM Approved (as a system component of Sikalastic RoofPro)

depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## LIMITATIONS

- Any repairs required to achieve a level surface must be performed prior to application (consult a Sika representative for guidance on various Sika product solutions). Surface irregularities may reflect through the cured system
- Do not apply to a porous or damp surface where moisture vapor transmission will occur during application and cure
- Substrate must be dry prior to application. Do not apply to a frosted, wet or damp surface
- Allow sufficient time for the substrate to dry after rain or inclement weather as there is the potential for bonding problems

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

Substrate surfaces, including flashing substrates, shall be primed, clean and dry, in accordance with separate System Data Sheet.

### APPLICATION

Apply the specified base layer resin quantity to primed substrate surface with a 1/2" (12.7 mm) nap phenolic resin core roller. Immediately place Sika® Reemat into wet resin, overlapping reinforcement 2" (50.8 mm) along the sides and at the roll ends. Apply wet roller to topside with light pressure to completely saturate the Reemat. Allow the Reemat to conform to substrate irregularities and flashing conditions. Apply additional resin as required to top of the Reemat to aid in conformity.

Allow Reemat base reinforcement to cure. Apply top coat to cured base coat with resin in specified mils quantity, allow to cure.

#### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
usa.sika.com



#### Product Data Sheet

Sika® Reemat Premium  
September 2024, Version 04.01  
020915952000000004

## OTHER RESTRICTIONS

See Legal Disclaimer.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

SikaReematPremium-en-US-(09-2024)-4-1.pdf

