according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

### **SECTION 1. IDENTIFICATION**

Product name : PEBBLETEX TERSUS F1.0 DK TB

Product code : 00000000050525440

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Functional surface coating

Restrictions on use : Reserved for industrial and professional use.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

: Category 2 (Kidney, Immune system)

### **GHS** label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

H373 May cause damage to organs (Kidney, Immune system)

according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

through prolonged or repeated exposure if inhaled.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Acrylic polymer

## Components

Chemical name	CAS-No.	Concentration (% w/w)
crystalline silica	14808-60-7	>= 30 - < 50
Mica-group minerals	12001-26-2	>= 1 - < 5
Kieselguhr, soda ash flux-calcined	68855-54-9	>= 1 - < 5
Cellulose	9004-34-6	>= 1 - < 5
Titanium dioxide	13463-67-7	>= 0.1 - < 1
1,3,5-Triazine-1,3,5(2H,4H,6H)-	4719-04-4	>= 0.1 - < 1
triethanol		

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Remove contact lenses, if present.

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention. Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Prolonged or repeated inhalation of respirable crystalline silica

(quartz) may result in silicosis.

Notes to physician : Treat symptomatically.

## **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke

carbon black carbon oxides

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

09/22/2023 000000540425 Date of first issue: 09/22/2023 1.0

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: :

tive equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Contain contaminated water/firefighting water. **Environmental precautions** 

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact. Avoid contact with eyes.

Conditions for safe storage Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Recommended storage tem-

perature

: > 39 °F / > 4 °C

Further information on stor-

age stability

PROTECT FROM FREEZING DURING THE COLD-SEASON

(BELOW 40°F / 5°C).

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
crystalline silica	14808-60-7	TWA (Res- pirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respir-	0.1 mg/m3	OSHA P0

according to the OSHA Hazard Communication Standard



# PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

	•	1	1	1
		able dust fraction)		
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
Mica-group minerals	12001-26-2	TWA (Respirable particulate matter)	0.1 mg/m3	ACGIH
		TWA (Dust)	20 Million parti- cles per cubic foot	OSHA Z-3
		TWA (Res- pirable)	3 mg/m3	NIOSH REL
		TWA (respirable dust fraction)	3 mg/m3	OSHA P0
Kieselguhr, soda ash flux- calcined	68855-54-9	TWA (Dust)	20 Million parti- cles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL
Cellulose	9004-34-6	TWA value	10 mg/m3	ACGIHTLV
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA	10 mg/m3	ACGIH
		TWA (Res- pirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (Res-	0.2 mg/m3	ACGIH

according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

pirable par- ticulate mat- ter)	(Titanium dioxide)	
TWA (Res- pirable par- ticulate mat- ter)	2.5 mg/m3 (Titanium dioxide)	ACGIH

**Engineering measures** : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen depending on activity and

possible exposure, e.g. head protection, apron, protective

boots, chemical-protection suit.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous liquid

Color : off-white

Odor : mild, acrylic-like

according to the OSHA Hazard Communication Standard



# PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

Odor Threshold : not determined

pH : 8.5 - 9.8 (73 °F / 23 °C)

Melting point/freezing point : No data available

Boiling point : No data available

Flash point :  $> 200 \, ^{\circ}\text{F} / > 93 \, ^{\circ}\text{C}$ 

Method: Seta closed cup

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Self-ignition : Based on the water content the product does not ignite.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 1.85 g/cm3 (73 °F / 23 °C)

Solubility(ies)

Water solubility : partly miscible (59 °F / 15 °C)

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: not applicable for mixtures

Autoignition temperature : Based on the water content the product does not ignite.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

09/22/2023 000000540425 Date of first issue: 09/22/2023 1.0

Explosive properties Not explosive

Oxidizing properties Not an oxidizer.

No data available Sublimation point

Molecular weight Not applicable

No corrosive effect on metal. Metal corrosion rate

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability The product is stable if stored and handled as pre-

scribed/indicated.

tions

Possibility of hazardous reac- : The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid See SDS section 7 - Handling and storage.

Strong acids Incompatible materials

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified due to lack of data.

#### Skin corrosion/irritation

Not classified due to lack of data.

## Serious eye damage/eye irritation

Not classified due to lack of data.

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified due to lack of data.

according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

### Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

crystalline silica 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

NTP Known to be human carcinogen

crystalline silica 14808-60-7

(Silica, Crystalline (Respirable Size))

## Reproductive toxicity

Not classified due to lack of data.

#### STOT-single exposure

Not classified due to lack of data.

## STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

## **Aspiration toxicity**

Not classified due to lack of data.

#### **Further information**

## **Product:**

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

## **Product:**

## **Ecotoxicology Assessment**

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### Persistence and degradability

No data available

according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

## **Bioaccumulative potential**

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

#### **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**Domestic regulation** 

49 CFR

Not regulated as a dangerous good

## **SECTION 15. REGULATORY INFORMATION**

### **US State Regulations**

### Pennsylvania Right To Know

crystalline silica 14808-60-7 Mica-group minerals 12001-26-2

according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version	Revision Date:	SDS Number: 000000540425	Date of last issue: -	
1.0	09/22/2023		Date of first issue: 09/22/2023	
Kieselguhr, soda ash flux-calcined Cellulose ethylene glycol ammonia ammonia, aqueous solution			68855-54-9 9004-34-6 107-21-1 7664-41-7 1336-21-6	
New Jersey Right To Know				
crystalline silica			14808-60-7	
Mica-group minerals			12001-26-2	
Cellulose			9004-34-6	

#### California Prop. 65

WARNING: This product can expose you to chemicals including crystalline silica, which is/are known to the State of California to cause cancer, and

ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## The ingredients of this product are reported in the following inventories:


TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

#### **SECTION 16. OTHER INFORMATION**


#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1) 1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

according to the OSHA Hazard Communication Standard



## PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA : 8-hour, time-weighted average ACGIHTLV / TWA value : Time Weighted Average (TWA):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/22/2023

according to the OSHA Hazard Communication Standard



# PEBBLETEX TERSUS F1.0 DK TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN