

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0      Revision Date: 08/05/2021      SDS Number: 960000009351      Date of last issue: -  
Date of first issue: 08/05/2021

---

### SECTION 1. IDENTIFICATION

Product name : SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B

Product code : 00000000058408847

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE  
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity : Category 1 (Lungs)  
- repeated exposure (Inhalation)

Specific target organ toxicity : Category 2 (Kidney)  
- repeated exposure

Specific target organ toxicity : Category 2 (Immune system)  
- repeated exposure (Inhalation)

Short-term (acute) aquatic hazard : Category 1

Long-term (chronic) aquatic hazard : Category 1

#### GHS label elements

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0      Revision Date: 08/05/2021      SDS Number: 960000009351      Date of last issue: -  
Date of first issue: 08/05/2021

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.  
H350 May cause cancer by inhalation.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.  
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.  
H373 May cause damage to organs (Immune system) through prolonged or repeated exposure if inhaled.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.  
P391 Collect spillage.  
**Storage:**  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**  
None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Hardener

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0      Revision Date: 08/05/2021      SDS Number: 960000009351      Date of last issue: -  
Date of first issue: 08/05/2021

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO <sub>2</sub> )	14808-60-7	>= 50 - < 100
dibenzoyl peroxide	94-36-0	>= 1 - < 10
ethylene glycol	107-21-1	>= 1 - < 10

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
- In case of eye contact : Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction. May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure if inhaled. May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated inhalation of respirable crystalline silica (quartz) may result in silicosis.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : water jet

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0      Revision Date: 08/05/2021      SDS Number: 960000009351      Date of last issue: -  
Date of first issue: 08/05/2021

- Hazardous combustion products : fumes/smoke  
harmful vapours  
Carbon oxides  
nitrogen oxides  
carbon black
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
Wear eye/face protection.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Pick up with suitable appliance and dispose of.  
Dispose of absorbed material in accordance with regulations.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : The product is neither self-ignitable, nor an explosion hazard, nor does it promote fires.
- Advice on safe handling : In case of insufficient ventilation, wear suitable respiratory equipment.  
Do NOT breathe dust because it is hazardous to respiratory system.  
Avoid skin contact.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
------------	---------	------------	-----------------	-------

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0      Revision Date: 08/05/2021      SDS Number: 960000009351      Date of last issue: -  
Date of first issue: 08/05/2021

		(Form of exposure)	ters / Permissible concentration	
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m <sup>3</sup>	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
dibenzoyl peroxide	94-36-0	TWA	5 mg/m <sup>3</sup>	ACGIH
		TWA	5 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	5 mg/m <sup>3</sup>	OSHA P0
ethylene glycol	107-21-1	TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m <sup>3</sup>	ACGIH
		C	50 ppm 125 mg/m <sup>3</sup>	OSHA P0

**Engineering measures** : Ensure adequate ventilation.

### Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.  
Use NIOSH approved respiratory protection.

Hand protection

Remarks : Chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.  
Avoid contact with the skin, eyes and clothing.

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0	Revision Date: 08/05/2021	SDS Number: 960000009351	Date of last issue: - Date of first issue: 08/05/2021
----------------	------------------------------	-----------------------------	--

Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Color	: black
Odor	: mild, of glycol
Odor Threshold	: not determined
pH	: No data available
Melting point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 212 °F / > 100 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: No data available
Density	: 1.7 - 1.8 g/cm <sup>3</sup> (68 °F / 20 °C)

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0	Revision Date: 08/05/2021	SDS Number: 960000009351	Date of last issue: - Date of first issue: 08/05/2021
----------------	------------------------------	-----------------------------	--

---

Solubility(ies)  
Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-  
octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-  
scribed/indicated.

Viscosity  
Viscosity, dynamic : 70 - 110 Pas (68 °F / 20 °C)

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Molecular weight : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-  
scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-  
scribed/indicated.

Possibility of hazardous reac-  
tions : The product is stable if stored and handled as pre-  
scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Powdered metals  
Strong acids  
Strong bases  
Strong oxidizing agents

Hazardous decomposition  
products : No hazardous decomposition products if stored and handled  
as prescribed/indicated.

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0      Revision Date: 08/05/2021      SDS Number: 960000009351      Date of last issue: -  
Date of first issue: 08/05/2021

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitization

##### Skin sensitization

May cause an allergic skin reaction.

##### Respiratory sensitization

Not classified based on available information.

##### Germ cell mutagenicity

Not classified based on available information.

##### Carcinogenicity

May cause cancer by inhalation.

<b>IARC</b>	Group 1: Carcinogenic to humans Quartz (SiO <sub>2</sub> ) (Silica dust, crystalline)	14808-60-7
<b>OSHA</b>	OSHA specifically regulated carcinogen Quartz (SiO <sub>2</sub> ) (crystalline silica)	14808-60-7
<b>NTP</b>	Known to be human carcinogen Quartz (SiO <sub>2</sub> ) (Silica, Crystalline (Respirable Size))	14808-60-7

##### Reproductive toxicity

Not classified based on available information.

##### STOT-single exposure

Not classified based on available information.

##### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.  
May cause damage to organs (Kidney) through prolonged or repeated exposure.  
May cause damage to organs (Immune system) through prolonged or repeated exposure if inhaled.

##### Aspiration toxicity

Not classified based on available information.

##### Further information

##### Product:



# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0	Revision Date: 08/05/2021	SDS Number: 960000009351	Date of last issue: - Date of first issue: 08/05/2021
----------------	------------------------------	-----------------------------	--

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Product:

##### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

##### Components:

##### dibenzoyl peroxide:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

#### Persistence and degradability

##### Product:

Biodegradability : Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

#### Bioaccumulative potential

##### Product:

Bioaccumulation : Remarks: No data available. Discharge into the environment must be avoided.

#### Mobility in soil

No data available

#### Other adverse effects

##### Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0      Revision Date: 08/05/2021      SDS Number: 960000009351      Date of last issue: -  
Date of first issue: 08/05/2021

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not discharge into drains/surface waters/groundwater.  
Do not contaminate ponds, waterways or ditches with chemical or used container.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.
- 

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

- UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (DIBENZOYL PEROXIDE)  
Class : 9  
Subsidiary risk : EHSM  
Packing group : III  
Labels : 9 (EHSM)

##### IATA-DGR

- UN/ID No. : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (DIBENZOYL PEROXIDE)  
Class : 9  
Subsidiary risk : EHSM  
Packing group : III  
Labels : Miscellaneous, Environmentally hazardous  
Packing instruction (cargo aircraft) : 956  
Packing instruction (passenger aircraft) : 956

##### IMDG-Code

- UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (DIBENZOYL PEROXIDE)  
Class : 9  
Subsidiary risk : EHSM  
Packing group : III  
Labels : 9 (EHSM)  
EmS Code : F-A, S-F  
Marine pollutant : yes

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version 1.0      Revision Date: 08/05/2021      SDS Number: 960000009351      Date of last issue: -  
Date of first issue: 08/05/2021

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,  
N.O.S.  
(DIBENZOYL PEROXIDE)  
Class : 9  
Subsidiary risk : EHSM  
Packing group : III  
Labels : CLASS 9, Environmentally hazardous  
ERG Code : 171  
Marine pollutant : yes

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

dibenzoyl peroxide	94-36-0	>= 5 - < 10 %
ethylene glycol	107-21-1	>= 5 - < 10 %

### US State Regulations

#### Pennsylvania Right To Know

Quartz (SiO <sub>2</sub> )	14808-60-7
dibenzoyl peroxide	94-36-0
ethylene glycol	107-21-1

#### New Jersey Right To Know

Quartz (SiO <sub>2</sub> )	14808-60-7
dibenzoyl peroxide	94-36-0
ethylene glycol	107-21-1

#### California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO<sub>2</sub>), which is/are known to the State of California to cause cancer, and ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B




Version 1.0      Revision Date: 08/05/2021      SDS Number: 960000009351      Date of last issue: -  
Date of first issue: 08/05/2021

DSL : All components of this product are on the Canadian DSL

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



##### HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA CARC / PEL : Permissible exposure limit (PEL)
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / C : Ceiling limit
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic

# SAFETY DATA SHEET

## SikaEmaco ADH 612 Part B Formerly MEmaco ADH 612 Part B



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2021	960000009351	Date of first issue: 08/05/2021

---

Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/05/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN