PEBBLETEX ULTRA SMOOTH COL DARK



Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

SECTION 1. IDENTIFICATION

Product name : PEBBLETEX ULTRA SMOOTH COL DARK

Product code : 00000000050002492

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling.

PEBBLETEX ULTRA SMOOTH COL DARK



Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of

the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 30 - < 50
Quartz (SiO2)	14808-60-7	>= 10 - < 20
Kieselguhr, soda ash flux-calcined	68855-54-9	>= 1 - < 5
Titanium dioxide	13463-67-7	>= 0.1 - < 1
1,3,5-Triazine-1,3,5(2H,4H,6H)-	4719-04-4	>= 0.1 - < 1
triethanol		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Remove contact lenses, if present.

Wash affected eyes for at least 15 minutes under running

PEBBLETEX ULTRA SMOOTH COL DARK



Version **Revision Date:** SDS Number: Date of last issue: -

04/13/2022 000000837547 Date of first issue: 04/13/2022 1.0

water with eyelids held open, consult an eye specialist.

If swallowed Immediately rinse mouth and then drink 200-300 ml of water.

> seek medical attention. Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction. May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Prolonged or repeated inhalation of respirable crystalline silica

(quartz) may result in silicosis.

Treat symptomatically. Notes to physician

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

Aqueous preparation

The substances/groups of substances mentioned can be re-

leased if the product is involved in a fire.

Hazardous combustion prod-

ucts

oxides

carbon compounds

fumes/smoke

Further information The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment: Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

PEBBLETEX ULTRA SMOOTH COL DARK



Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

gency procedures If exposed to high vapour concentration, leave area immedi-

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up

: Large spills should be collected mechanically (remove by

pumping) for disposal.

Pick up with inert absorbent material (e.g. sand, earth etc.). Spilled product should be disposed in accordance with all

applicable government regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact. Avoid contact with eyes.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : No applicable information available.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Quartz (SiO2)	14808-60-7	TWA (Res- pirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respir-	10 mg/m3 /	OSHA Z-3





Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

		able)	%SiO2+2	
		TWA (respir-	250 mppcf /	OSHA Z-3
		able)	%SiO2+5	
		TWA (respir-	0.1 mg/m3	OSHA P0
		able dust		
		fraction)		
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-	(Silica)	
		ticulate mat-		
		ter)		
		TWA (Res-	0.05 mg/m3	NIOSH REL
		pirable dust)	(Silica)	
Kieselguhr, soda ash flux- calcined	68855-54-9	REL value	6 mg/m3	NIOSH
		TWA value	20 millions of	29 CFR
			particles per cubic	1910.1000
			foot of air	(Table Z-3)
		TWA value	0.8 mg/m3	29 CFR
				1910.1000
				(Table Z-3)
		OSHA Action	0.025 mg/m3	29 CFR
		level	(Respirable dust)	1910.1001-
				1050
		TWA value	0.05 mg/m3	29 CFR
			(Respirable dust)	1910.1001-
				1050
		TWA (Dust)	20 Million parti-	OSHA Z-3
			cles per cubic foot	
			(Silica)	
		TWA (Dust)	80 mg/m3 /	OSHA Z-3
			%SiO2	
			(Silica)	
		TWA	6 mg/m3	NIOSH REL
			(Silica)	

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Wear a NIOSH-certified (or equivalent) organic va-

pour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : light protective clothing

Protective measures : Do not inhale gases/vapours/aerosols.

PEBBLETEX ULTRA SMOOTH COL DARK



Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : off-white

Odor : moderate odour

pH : 9.5 (approx. 73.40 °F / 23.00 °C)

Melting point : No applicable information available.

Boiling point : No applicable information available.

Flash point : approx. 201.20 °F / 94.00 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : Based on the structure or composition there is no indication of

flammability

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure : No applicable information available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

PEBBLETEX ULTRA SMOOTH COL DARK



Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

Density : approx. 1.8000 g/cm3 (73.40 °F / 23.00 °C)

Solubility(ies)

Water solubility : No applicable information available.

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No applicable information available.

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Oxidizing properties : Not an oxidizer.

Sublimation point : No applicable information available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

harmful vapours

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

PEBBLETEX ULTRA SMOOTH COL DARK



Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

PEBBLETEX ULTRA SMOOTH COL DARK



Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

PEBBLETEX ULTRA SMOOTH COL DARK



Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Limestone	1317-65-3
Quartz (SiO2)	14808-60-7
Feldspar-group minerals	68476-25-5
Kieselguhr, soda ash flux-calcined	68855-54-9
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
1,2,4-trimethylbenzene	95-63-6
ammonia	7664-41-7
ammonia, aqueous solution	1336-21-6

New Jersey Right To Know

Limestone	1317-65-3
Quartz (SiO2)	14808-60-7
Feldspar-group minerals	68476-25-5

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO2), which is/are known to the State of California to cause cancer, and

PEBBLETEX ULTRA SMOOTH COL DARK



Version **Revision Date:** SDS Number: Date of last issue: -

04/13/2022 000000837547 Date of first issue: 04/13/2022 1.0

ethylene oxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

All chemical substances in this product are either listed as


active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

29 CFR 1910.1001-1050 OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH USA. ACGIH Threshold Limit Values (TLV) NIOSH Pocket Guide to Chemical Hazards (US) NIOSH **NIOSH REL** USA. NIOSH Recommended Exposure Limits

USA. Table Z-1-A Limits for Air Contaminants (1989 vacated OSHA P0

values)

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-OSHA Z-1

its for Air Contaminants

OSHA Action level:

OSHA Z-3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

> eral Dusts Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z- :

3) / TWA value

29 CFR 1910.1001-1050 /

OSHA Action level

29 CFR 1910.1001-1050 /

TWA value

Time Weighted Average (TWA):

ACGIH / TWA 8-hour, time-weighted average

PEBBLETEX ULTRA SMOOTH COL DARK



Version Revision Date: SDS Number: Date of last issue: -

1.0 04/13/2022 000000837547 Date of first issue: 04/13/2022

NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 04/13/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN