PEBBLETEX ULTRA SMOOTH COL MAXI WHITE



Version 2.0

Revision Date: 04/05/2021

SDS Number: 000000837745

Date of last issue: 08/27/2020 Date of first issue: 08/27/2020

SECTION 1. IDENTIFICATION

Product name : PEBBLETEX ULTRA SMOOTH COL MAXI WHITE

Product code : 00000000050002494

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Specific target organ toxicity - repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

Germ cell mutagenicity : Category 1B

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or





Version Revision Date: SDS Number: Date of last issue: 08/27/2020 2.0 04/05/2021 000000837745 Date of first issue: 08/27/2020

repeated exposure if inhaled.

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|------------------------------------|------------|-----------------------|
| Limestone | 1317-65-3 | >= 30 - < 50 |
| Quartz (SiO2) | 14808-60-7 | >= 10 - < 20 |
| Titanium dioxide | 13463-67-7 | >= 1 - < 5 |
| Kieselguhr, soda ash flux-calcined | 68855-54-9 | >= 1 - < 5 |
| Quartz (SiO2) | 14808-60-7 | >= 0.1 - < 1 |
| cristobalite | 14464-46-1 | >= 0.1 - < 1 |
| Silicon dioxide | 7631-86-9 | >= 0.1 - < 1 |
| 1,3,5-Triazine-1,3,5(2H,4H,6H)- | 4719-04-4 | >= 0.1 - < 1 |
| triethanol | | |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

PEBBLETEX ULTRA SMOOTH COL MAXI WHITE



Version Revision Date: SDS Number: Date of last issue: 08/27/2020 2.0 04/05/2021 000000837745 Date of first issue: 08/27/2020

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Prolonged or repeated inhalation of respirable crystalline silica

(quartz) may result in silicosis.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod: :

ucts

harmful vapours nitrogen oxides fumes/smoke

fumes/smoke carbon black carbon oxides

Further information : Standard procedure for chemical fires.





Version 2.0

Revision Date: 04/05/2021

SDS Number: 000000837745

Date of last issue: 08/27/2020 Date of first issue: 08/27/2020

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

: Keep only in the original container in a cool, dry, wellventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : No applicable information available.





Version 2.0

Revision Date: 04/05/2021

SDS Number: 000000837745 Date of last issue: 08/27/2020 Date of first issue: 08/27/2020

Further information on stor- : No data available

age stability

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------------|------------|---------------------------------------|--|--------------------------------------|
| Limestone | 1317-65-3 | REL value (Respirable) | 5 mg/m3 | NIOSH |
| | | REL value (Total) | 10 mg/m3 | NIOSH |
| | | PEL (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | PEL (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value (Respirable fraction) | 5 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA value (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m3 | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m3 | OSHA P0 |
| | | TWA (Respirable) | 5 mg/m3 (Calcium car- bonate) | NIOSH REL |
| | | TWA (total) | 10 mg/m3 (Calcium car- bonate) | NIOSH REL |
| Titanium dioxide | 13463-67-7 | TWA value | 10 mg/m3 | ACGIHTLV |
| | | PEL (Total dust) | 15 mg/m3 | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value (Total dust) | 10 mg/m3 | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (Total | 10 mg/m3 | OSHA P0 |



PEBBLETEX ULTRA SMOOTH COL MAXI WHITE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/27/2020

 2.0
 04/05/2021
 000000837745
 Date of first issue: 08/27/2020

| | 1 | l duat\ | 1 | |
|--|------------|---------------------------------------|------------------------------------|------------------------------|
| | | dust) TWA | 10 mg/m3 (Titanium dioxide) | ACGIH |
| cristobalite | 14464-46-1 | TWA value (Respirable fraction) | 0.025 mg/m3 | ACGIHTLV |
| | | TWA (Respirable dust) | 0.05 mg/m3 | OSHA Z-1 |
| | | TWA (respirable dust fraction) | 0.05 mg/m3 | OSHA P0 |
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH |
| | | PEL (respir- able) | 0.05 mg/m3 | OSHA CARC |
| | | TWA (Respirable dust) | 0.05 mg/m3 (Silica) | NIOSH REL |
| Quartz (SiO2) | 14808-60-7 | TWA value (Respirable fraction) | 0.025 mg/m3 | ACGIHTLV |
| | | TWA value | 0.05 mg/m3 (Respirable dust) | 29 CFR 1910.1001- 1050 |
| | | OSHA Action level | 0.025 mg/m3 (Respirable dust) | 29 CFR 1910.1001- 1050 |
| | | REL value (Respirable dust) | 0.05 mg/m3 | NIOSH |
| | | TWA (Respirable dust) | 0.05 mg/m3 | OSHA Z-1 |
| | | TWA (respirable) | 10 mg/m3 / %SiO2+2 | OSHA Z-3 |
| | | TWA (respir- able) | 250 mppcf / %SiO2+5 | OSHA Z-3 |
| | | TWA (respirable dust fraction) | 0.1 mg/m3 | OSHA P0 |
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH |
| | | PEL (respir- able) | 0.05 mg/m3 | OSHA CARC |
| | | TWA (Respirable dust) | 0.05 mg/m3 (Silica) | NIOSH REL |
| Kieselguhr, soda ash flux- calcined | 68855-54-9 | REL value | 6 mg/m3 | NIOSH |
| | | TWA value | 20 millions of particles per cubic | 29 CFR 1910.1000 |

PEBBLETEX ULTRA SMOOTH COL MAXI WHITE



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/27/2020

 2.0
 04/05/2021
 000000837745
 Date of first issue: 08/27/2020

| | foot of air | (Table Z-3) |
|----------------------|--|------------------------------|
| TWA value | 0.8 mg/m3 | 29 CFR 1910.1000 |
| | | (Table Z-3) |
| OSHA Action level | 0.025 mg/m3 (Respirable dust) | 29 CFR 1910.1001- 1050 |
| TWA value | 0.05 mg/m3 (Respirable dust) | 29 CFR 1910.1001- 1050 |
| TWA (Dust) | 20 Million parti- cles per cubic foot (Silica) | OSHA Z-3 |
| TWA (Dust) | 80 mg/m3 / %SiO2 (Silica) | OSHA Z-3 |
| TWA | 6 mg/m3 (Silica) | NIOSH REL |

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Wear a NIOSH-certified (or equivalent) organic va-

pour/particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste





Version 2.0

Revision Date: 04/05/2021

SDS Number: 000000837745

Date of last issue: 08/27/2020 Date of first issue: 08/27/2020

Color : white

Odor : moderate odour

Odor Threshold : No data available

pH : 9.5 (approx. 73.40 °F / 23.00 °C)

Melting point : No applicable information available.

Boiling point : No applicable information available.

Flash point : approx. 201.20 °F / 94.00 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : Based on the structure or composition there is no indication of

flammability

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure : No applicable information available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : approx. 1.8000 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : No applicable information available.

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No applicable information available.

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

PEBBLETEX ULTRA SMOOTH COL MAXI WHITE



Version Revision Date: SDS Number: Date of last issue: 08/27/2020 2.0 04/05/2021 000000837745 Date of first issue: 08/27/2020

Viscosity, kinematic : No applicable information available.

Oxidizing properties : Not an oxidizer.

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

PEBBLETEX ULTRA SMOOTH COL MAXI WHITE



Version 2.0

Revision Date: 04/05/2021

SDS Number: 000000837745

Date of last issue: 08/27/2020 Date of first issue: 08/27/2020

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer by inhalation.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Kieselguhr, soda ash flux-calcined:

Partition coefficient: n-

Remarks: Not applicable

octanol/water

Mobility in soil

No data available

PEBBLETEX ULTRA SMOOTH COL MAXI WHITE



Version 2.0

Revision Date: 04/05/2021

SDS Number: 000000837745

Date of last issue: 08/27/2020 Date of first issue: 08/27/2020

Other adverse effects

Product:

Additional ecological infor-

mation

There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

 Limestone
 1317-65-3

 Titanium dioxide
 13463-67-7

 cristobalite
 14464-46-1

 Quartz (SiO2)
 14808-60-7

 Kieselguhr, soda ash flux-calcined
 68855-54-9

New Jersey Right To Know

PEBBLETEX ULTRA SMOOTH COL MAXI WHITE



Version Revision Date: SDS Number: Date of last issue: 08/27/2020 2.0 04/05/2021 000000837745 Date of first issue: 08/27/2020

Limestone 1317-65-3 Titanium dioxide 13463-67-7 cristobalite 14464-46-1

California Prop. 65

WARNING: This product can expose you to chemicals including ethylene oxide, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION


Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1910.1000

1-A

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

l)

29 CFR 1910.1000 (Table Z-

OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

3)

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

PEBBLETEX ULTRA SMOOTH COL MAXI WHITE



Version Revision Date: SDS Number: Date of last issue: 08/27/2020 2.0 04/05/2021 000000837745 Date of first issue: 08/27/2020

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

3) / TWA value

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/27/2020

 2.0
 04/05/2021
 000000837745
 Date of first issue: 08/27/2020

Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 04/05/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN