

Revision Date 04/04/2018

Print Date 04/04/2018

1. Identification

Product name : LITHOCHROME® Chemstain® Classic (Antique Amber)

Supplier : Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

Recommended use of the chemical and restrictions on

cnemical and restruse

For further information, refer to product data sheet.

2. Hazards identification

GHS Classification

Corrosive to Metals, Category 1 H290: May be corrosive to metals. Skin irritation, Category 2 H315: Causes skin irritation. Serious eye damage, Category 1 H318: Causes serious eye damage.

GHS label elements

Hazard pictograms

Signal Word : Danger

Hazard Statements : H290 May be corrosive to metals.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary Statements : **Prevention:**

P234 Keep only in original container. P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.



Revision Date 04/04/2018 Print Date 04/04/2018

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P390 Absorb spillage to prevent material damage.

See Section 11 for more detailed information on health effects and symptoms.

There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

3. Composition/information on ingredients

Hazardous ingredients

Chemical name	CAS-No.	Concentration (%)
iron dichloride	7758-94-3	>= 5 - < 10 %
hydrogen chloride	7647-01-0	>= 2 - < 3 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

: irritant effects

Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects



Revision Date 04/04/2018

Print Date 04/04/2018

and symptoms.

Causes skin irritation.

Causes serious eye damage.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment. Deny access to unprotected persons.

: Try to prevent the material from entering drains or water

courses.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. Handling and storage

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated



Revision Date 04/04/2018 Print Date 04/04/2018

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

Materials to avoid : No data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
iron dichloride	7758-94-3	ACGIH	TWA	1 mg/m3
		OSHA P0	TWA	1 mg/m3
hydrochloric acid	7647-01-0	ACGIH	С	2 ppm
		OSHA Z-1	С	5 ppm 7 mg/m3
		OSHA P0	С	5 ppm 7 mg/m3

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**Basis

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk

assessment indicates this is necessary.

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection

Safety Data Sheet

LITHOCHROME® Chemstain® Classic (Antique Amber)



Revision Date 04/04/2018 Print Date 04/04/2018

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

9. Physical and chemical properties

Appearance : liquid

Color : amber

Odor : pungent

Odor Threshold : No data available

Flash point : Note: Not applicable

Ignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

pH : 0-2

Melting point/range /

Freezing point

Density

: No data available

Boiling point/boiling range : 212 °F (100 °C)

Vapor pressure : 17 mmHg (23 hpa)

: 1.1 - 1.5 g/cm3

at 73 °F (23 °C)

Water solubility : Note: soluble



Revision Date 04/04/2018

Print Date 04/04/2018

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic

: No data available

Viscosity, kinematic

: > 20.5 mm2/s at 104 °F (40 °C)

Relative vapor density

: No data available

Evaporation rate

No data available

Burning rate

No data available

Volatile organic compounds

(VOC) content

: 0 g/l

10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid

: No data available

Incompatible materials

: No data available

11. Toxicological information

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.



Revision Date 04/04/2018

Print Date 04/04/2018

Aspiration toxicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information. **IARC** Not applicable

NTP Not applicable

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

13. Disposal considerations

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

14. Transport information

DOT

UN number 3264

Description of the goods Corrosive, liquid, acidic, inorganic, n.o.s.

(iron dichloride, hydrochloric acid)

Class 8
Packing group II
Labels 8
Emergency Response 154

Guidebook Number

IATA

UN number 3264

Description of the goods Corrosive liquid, acidic, inorganic, n.o.s.

(iron dichloride, hydrochloric acid)

Class 8
Packing group II
Labels 8

855



Revision Date 04/04/2018

Print Date 04/04/2018

Packing instruction (cargo

aircraft)

Packing instruction 851

(passenger aircraft)

Packing instruction Y840

(passenger aircraft)

IMDG

UN number 3264

Description of the goods CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(iron dichloride, hydrochloric acid)

Class 8
Packing group II
Labels 8
EmS Number 1 F-A
EmS Number 2 S-B
Marine pollutant no

DOT: For Limited Quantity exceptions reference 49 CFR 173.154 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Corrosive to Metals

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section

302 EHS TPQ.



Revision Date 04/04/2018 Print Date 04/04/2018

SARA 313 : This material does not contain any chemical components with

> known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion This product neither contains, nor was manufactured with a Potential

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR

61):

hydrochloric acid 7647-01-0 2.82 %

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental

Release Prevention (40 CFR 68.130, Subpart F):

hydrochloric acid 7647-01-0 2.82 %

California Prop 65 This product does not contain any chemicals known to the State

of California to cause cancer, birth, or any other reproductive

defects.

16. Other information

HMIS Classification



Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT

Safety Data Sheet

LITHOCHROME® Chemstain® Classic (Antique Amber)



Revision Date 04/04/2018

Print Date 04/04/2018

BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 04/04/2018

Material number: 540685