



# MATERIAL SAFETY DATA SHEET

## Contractor's Choice SikaLatex

### HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

### 1. Product And Company Identification

<u>Supplier</u> Sika Corporation 201 Polito Ave Lyndhurst, NJ 07071  Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com	<u>Manufacturer</u> Sika Corporation 201 Polito Ave Lyndhurst, NJ 07071  Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com
<u>Supplier Emergency Contacts &amp; Phone Number</u> CHEMTREC: 800-424-9300 INTERNATIONAL: 706-527-3887	<u>Manufacturer Emergency Contacts &amp; Phone Number</u> CHEMTREC: 800-424-9300 INTERNATIONAL: 706-527-3887

Issue Date: 07/07/2003  
Product Name: Contractor's Choice SikaLatex  
CAS Number: Not Established  
Chemical Family: Acrylic Aqueous Emulsion  
MSDS Number: 2767  
Product Code: 0747130

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
ACRYLIC POLYMER	TradeSecret	

### 3. Hazards Identification

Eye Hazards  
May cause eye irritation.

Skin Hazards  
May cause skin irritation.

Ingestion Hazards  
May be harmful if swallowed.

Inhalation Hazards  
May cause nose, throat, and lung irritation.

## Contractor's Choice SikaLatex

### 4. First Aid Measures

#### Eye

In case of contact, immediately flush eyes with plenty of water. Get medical attention immediately if irritation develops and persists.

#### Skin

In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

#### Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.

#### Inhalation

Remove to fresh air.

### 5. Fire Fighting Measures

**Flash Point:** >200 °F

**Autoignition Point:** N/AV °F

#### Fire And Explosion Hazards

Material can splatter above 100C / 212F.

#### Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

#### Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

### 6. Accidental Release Measures

Avoid release to the environment. Use appropriate personal protective equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Ventilate enclosed area.

### 7. Handling And Storage

#### Handling And Storage Precautions

Keep containers tightly closed. Keep out of reach of children.

#### Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use with adequate general and local exhaust ventilation.

#### Eye/Face Protection

Safety glasses with side shields or goggles.

#### Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing. Launder before reuse.

#### Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use.

#### Other/General Protection

Wash thoroughly after handling.

#### Ingredient(s) - Exposure Limits

ACRYLIC POLYMER

OSHA PEL: NOT ESTABLISHED

## Contractor's Choice SikaLatex

### 8. Exposure Controls/Personal Protection - Continued

#### Ingredient(s) - Exposure Limits - Continued

ACGIH TLV: NOT ESTABLISHED  
IARC: NO  
NTP: NO

### 9. Physical And Chemical Properties

#### Appearance

Milky white liquid

#### Odor

Ammonia odor

**Chemical Type:** Mixture

**Physical State:** Liquid

**Melting Point:** 32 °F 0 °C

**Boiling Point:** 212 °F 100 °C

**Specific Gravity:** 1.0-1.2

**Percent Volatiles:** 71-73 (water)

**Packing Density:** 1.0-1.2

**Vapor Pressure:** 17mm Hg at 20C water

**Vapor Density:** <1 WATER

**pH Factor:** N/AV

**Solubility:** N/AV

**Evaporation Rate:** < 1 WATER

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

#### Conditions To Avoid (Stability)

Avoid freezing

#### Incompatible Materials

None known

#### Hazardous Decomposition Products

None known

### 11. Toxicological Information

#### Conditions Aggravated By Exposure

None known

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

### 14. Transport Information

No Data Available...

# MATERIAL SAFETY DATA SHEET

## Contractor's Choice SikaLatex

### 14. Transport Information - Continued

#### Proper Shipping Name

Not regulated by the USDOT.

### 15. Regulatory Information

#### U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

### 16. Other Information

#### HMIS Rating

Health: 1

Fire: 0

Reactivity: 0

PPE: B

#### Revision/Preparer Information

MSDS Preparer: EHS Department

This MSDS Supercedes A Previous MSDS Dated: 01/17/2003

### Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION