

Safety Data Sheet

U-148CA

SDS Revision Date: 03/12/2025

Section 1. Identification

Product identifier

Product Identity

STABOND U-148CA

Other means of identification

U-148CA

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name

STABOND CORPORATION

1722 W. 139th Street, GARDENA CA. 90249

Customer Service: STABOND CORPORATION

(310) 380-6168 Mon. to Fri. 07:00 – 15:30 PT

Emergency Contact: CHEMTREC

(800) 424-9300 24-hour

Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Flammable Liquid, category 2;H225

Highly Flammable liquid and vapor.

Serious eye damage / eye irritation, category 2A;H319

Causes serious eye irritation.

Reproductive toxicity, category 2;H361D

Suspected of damaging the unborn child.

Specific target organ toxicity, Single exposure category 3;H336

May cause drowsiness or dizziness.

Aquatic toxicity (acute), category 3;H402

Harmful to aquatic life.

Aquatic toxicity (chronic), category 3;H412

Harmful to aquatic life with long lasting effects.

Label elements



Danger

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H412 Harmful to aquatic life with long lasting effects.

[Prevention]

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P233 Keep container tightly closed.
 P240 Ground, bond container and receiving equipment.
 P241 Use explosion-proof electrical, ventilating, light, equipment.
 P242 Use only non-sparking tools.
 P243 Take action to prevent static discharges.
 P261 Avoid breathing dust, fume, gas, mist, vapors, spray.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves, eye protection, and face protection.

[Response]

P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.
 P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+313 IF exposed or concerned: Get medical advice or attention.
 P312 Call a POISON CENTER, doctor or physician if you feel unwell.
 P337+313 If eye irritation persists: Get medical advice or attention.
 P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]

P403+233 Store in a well ventilated place. Keep container tightly closed.
 P403+235 Store in a well ventilated place. Keep cool.
 P405 Store locked up.

[Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does not contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per US or Canadian regulations.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acetone CAS Number: 67-64-1 Synonyms: 2-Propanone	65 - 85	Flammable Liquid, category 2;H225 Serious eye damage / eye irritation, category 2;H319 Specific target organ toxicity, Single exposure category 3;H336	-----
Petroleum Resin CAS Number: 64742-16-1 Synonyms: No available information	7 - 13	Not Classified	-----
Salicylic acid CAS Number: 69-72-7 Synonyms: No available information	1 - 5	Acute toxicity(oral), category 4;H302 Serious eye damage / eye irritation, category 1;H318 Reproductive toxicity, category 2;H361D	-----

Ethanol, 2-butoxy-, phosphate (3:1) CAS Number: 78-51-3 Synonyms: Tributyoxyethyl phosphate	0.5 - 1.5	Not Classified	----
--	-----------	----------------	------

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Contains aquatic toxins below 1% which lead to GHS classification: Zinc oxide (0001314-13-2)

Section 4. First aid measures

Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. If vomiting should occur spontaneously keep victims head below knees to prevent aspiration into the lungs.

Most important symptoms and effects, both acute and delayed

Overview	No specific symptom data available. No chronic toxicity or long term toxicity information available. Treat symptomatically. See section 2 for further details.
Inhalation	May cause drowsiness or dizziness.
Eyes	Causes serious eye irritation.
Chronic effects	Moderate CNS depression may be shown by giddiness, headache, dizziness and nausea. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs, which can cause severe lung damage. Aspiration pneumonitis may be evidenced by coughing and cyanosis.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO², powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: Burning may produce fumes of carbon dioxide, carbon monoxide, hydrogen cyanide, phenols and nitrous oxides.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Keep container tightly closed.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Avoid breathing dust, fume, gas, mist, vapors, spray.

Advice for fire-fighters

Volatile solvent constituent can readily form explosive or flammable mixtures in air. Vapors can flow along surfaces to distant ignition sources and flash back.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. 127

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Methods and material for containment and cleaning up

Soak up wet material on a non-combustible absorbent and place in a closed metal container.

Section 7. Handling and storage

Precautions for safe handling

Ground and bond metal containers when dispensing. Not smoking in areas of use or storage. Use only non-sparking tools near wet adhesive or solvent vapors. Solvent vapor is much heavier than air and can collect in dangerous concentrations in floor drains or low areas.

Store in cool, well ventilated area away from any ignition sources and strong oxidizing agents. Keep containers tightly closed when not in use. Do not transfer to plastic containers.

See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents can cause spontaneous combustion.

See section 2 for further details. - [Storage]

Specific end use(s)

No data available.

Section 8. Exposure controls / personal protection

Control parameters**Exposure Limits**

CAS No.	Ingredient	Source	Value
67-64-1	Acetone	OSHA	1000 ppm, 2400 mg/m ³
		ACGIH	250 ppm 500 ppm
		NIOSH	250 ppm (590 mg/m ³) TWA
69-72-7	Salicylic acid	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
78-51-3	Ethanol, 2-butoxy-, phosphate (3:1)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
64742-16-1	Petroleum Resin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

Exposure controls**Respiratory**

Atmospheric levels should be maintained below the exposure guideline. Use an approved, full-face, supplied air respirator or a NIOSH approved positive pressure, self-contained breathing apparatus if these levels are exceeded.

Eyes

Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.

Skin

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Use neoprene, vinyl or natural rubber gloves.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Eye wash fountain or bottles. Solvent insoluble barrier hand cream. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties**Physical State**

Liquid

Color	Low Viscosity
Odor	Acetone
Melting point / freezing point	Not Available
Initial boiling point and boiling range	133 F
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 2.2% Upper Explosive Limit: 13.0%
Flash Point	-4 F
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
pH	Not Available
Viscosity (cSt)	1,500 cps
Solubility in Water	Nil
Partition coefficient n-octanol/water (Log Kow)	Not Available
Vapor pressure (Pa)	Not Available
Relative Density	0.85 (H2O=1)
Vapor Density	HEAVIER THAN AIR
Evaporation rate (Ether = 1)	SLOWER THAN ETHER
VOC Content	COATING V.O.C.: 0 LB/GAL (0 G/L), MATERIAL V.O.C.: 0 LB/GAL (0 G/L)
Other information	
No other relevant information.	

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No data available.

Conditions to avoid

Keep away from all sources of ignition or heat.

Incompatible materials

Strong oxidizing agents can cause spontaneous combustion.

Hazardous decomposition products

Burning may produce fumes of carbon dioxide, carbon monoxide, hydrogen cyanide, phenols and nitrous oxides.

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Rabbit - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available.
Petroleum Resin - (64742-16-1)	> 2,000.00, Mammal - Category: NA	No data available.	No data available.	No data available.	No data available.
Salicylic acid - (69-72-7)	891.00, Rat - Category: 4	10,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Ethanol, 2-butoxy-, phosphate (3:1) - (78-51-3)	No data available.	No data available.	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
67-64-1	Acetone	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	A4
69-72-7	Salicylic acid	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit
78-51-3	Ethanol, 2-butoxy-, phosphate (3:1)	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit
64742-16-1	Petroleum Resin	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging the unborn child.
STOT-single exposure	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.

STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry: No available information

Symptoms and effects, both acute and delayed:

No specific symptom data available.

No chronic toxicity or long term toxicity information available. Treat symptomatically.

Inhalation May cause drowsiness or dizziness.

Eyes Causes serious eye irritation.

Chronic effects Moderate CNS depression may be shown by giddiness, headache, dizziness and nausea. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs, which can cause severe lung damage. Aspiration pneumonitis may be evidenced by coughing and cyanosis.

Section 12. Ecological information

Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Acetone - (67-64-1)	8,120.00, Pimephales promelas	8,800.00, Daphnia pulex	7,000.00, Pseudokirchneriella subcapitata
Petroleum Resin - (64742-16-1)	No data available.	No data available.	No data available.
Salicylic acid - (69-72-7)	90.00, Leuciscus idus	105.00, Daphnia magna	No data available.
Ethanol, 2-butoxy-, phosphate (3:1) - (78-51-3)	No data available.	No data available.	No data available.

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

Not Available

Mobility in soil

No data available.

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No data available.

Section 13. Disposal considerations

Waste treatment methods

Waste should not be released to sewers. Observe all federal, state, and local regulations when disposing of this substance.

Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	UN 1090	UN1090	UN1090
UN proper shipping name	Acetone	Acetone	Acetone
Transport hazard class(es)	Class: 3 Sub Class: Not Applicable	Class: 3 Sub Class: Not Applicable	Class: 3 Sub Class: Not Applicable
Packing group	II	II	II
Environmental hazards	Marine Pollutant: No;		
Special precautions for user	Not Applicable		

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0000067-64-1	Acetone	Yes		ACTIVE
0000078-51-3	Ethanol, 2-butoxy-, phosphate (3:1)	Yes		ACTIVE
0064742-16-1	Petroleum Resin	Yes	UVCB	ACTIVE
0000069-72-7	Salicylic acid	Yes		ACTIVE

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

1,3-Butadiene
4-Vinylcyclohexene
Acrylonitrile
Benzene

Proposition 65 - Developmental Toxins (>0.0%):

1,3-Butadiene

Benzene

Proposition 65 - Female Repro Toxins (>0.0%):

1,3-Butadiene

4-Vinylcyclohexene

Proposition 65 - Male Repro Toxins (>0.0%):

1,3-Butadiene

Benzene

Proposition 65 Label Warning:

WARNING: This product can expose you to chemicals including [1,3-Butadiene, 4-Vinylcyclohexene, Acrylonitrile, Benzene], which are known to the State of California to cause cancer, and [1,3-Butadiene, 4-Vinylcyclohexene, Benzene], which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16. Other information

Revision Date 03/12/2025

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H361 Suspected of damaging fertility or the unborn child.

ALL INFORMATION IS BASED UPON DATA FROM MFG'S AND/OR TECHNICAL SOURCE, & IS BELIEVED TO BE ACCURATE. CONDITIONS OF USE ARE BEYOND OUR CONTROL & THEREFORE USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN CONDITIONS TO DETERMINE SUITABILITY FOR THEIR PURPOSE, & THEY ASSUME ALL RISKS OF USE, HANDLING, & DISPOSAL, OR FROM USE OF INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH OTHER MATERIAL OR IN ANY OTHER PROCESS.

End of Document