BUILDING TRUST

PRODUCT DATA SHEET

SikaWall® Superhold

Formerly LaHabra® Superhold / Merlex Superhold.

PRODUCT DESCRIPTION

SikaWall® Superhold is an ethylene vinyl acetate emulsion that is ready-to-use, high build, film forming and re-emulsfiable. It has a blue tint so the area of application can be easily identified.

USES

SikaWall® Superhold may be used for interior or exterior applications for bonding new portland cement to existing structurally sound substrates. May be used on substrates such as portland cement stucco, cement stucco color coats, concrete, concrete block, brick, tile, and stone.

CHARACTERISTICS / ADVANTAGES

- Ready to use, no mixing.
- Simple application.
- Not affected by high alkalinity associated with lime plasters and portland cement.
- Resistant to humidity, may be used over damp or dry surfaces.
- Non-flammable.
- Economical, saves time.

PRODUCT INFORMATION

Packaging	5 gallon pail (19 liter pail).
Shelf Life	Two years with proper storage.
Storage Conditions	Do not store in direct sunlight. Storage temperature is between 10° C (50° F) and 32° C (90° F). Protect from freezing.

APPLICATION INFORMATION

Coverage	One pail covers approximately 115 to 138 m^2 (1,250 to 1,500 sq. ft.).

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

USES

Do not use in areas which are continually exposed to water or where hydrostatic pressure is present, such as swimming pools, spas, and so on. Do not allow SikaWall® Superhold to freeze. Do not apply over frozen or frost filled surfaces. Do not use when ambient temperature

will fall below 4° C (40° F). Do not dilute. Do not apply over water soluble materials.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The receiving surface must be clean, free of dust, dirt, oil, grease, loose stone, loose sand, deteriorating paint or other foreign materials which could impair bonding ability. Smooth surfaces shall be abraded before application. On porous surfaces, lightly dampen before applying SikaWall® Superhold.
Apply a test patch and allow to dry for 24 hours.
If SikaWall® Superhold curls or cracks, the surface must be cleaned thoroughly prior to application.

APPLICATION

SikaWall® Superhold is ready to use. No mixing or stirring is needed. Do not dilute. It may be applied by hand with brush or roller, or spray applied using an airless sprayer delivering at least 2.8 kg/cm² (40 psi), with an orifice size no smaller than 0.5 mm (0.02 inch). A larger orifice may be necessary. Spray approximately 46 cm (18 inches) from surface in a crisscross pattern. Apply new material to be bonded to SikaWall® Superhold within 72 hours of the application of SikaWall® Superhold.
For maximum adhesion of new cementitous materials, use SikaWall®-73 Adacryl Admix & Bonder as an admix (1 part SikaWall®-73 Adacryl Admix & Bonder to 3 parts water) plus SikaWall® Superhold (undiluted) on the substrate.

CLEANING OF TOOLS

Clean all tools and equipment with detergent and water immediately after use. Clean up spills, splatters and overspray before it is allowed to dry.

LEGAL DISCLAIMER

- **KEEP CONTAINER TIGHTLY CLOSED**
- **KEEP OUT OF REACH OF CHILDREN**
- **NOT FOR INTERNAL CONSUMPTION**
- **FOR INDUSTRIAL USE ONLY**
- **FOR PROFESSIONAL USE ONLY**

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at https://usa.sika.com/en/about-us/terms-conditions-of-sale.html or by calling 1-800-933-7452.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com