



## 1. Identification

Product name	:	SCOFIELD® Integral Color SG
Supplier	:	Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

## 2. Hazards identification

### GHS Classification

Eye irritation, Category 2A	H319: Causes serious eye irritation.
Carcinogenicity, Category 1A (Inhalation)	H350i: May cause cancer by inhalation.
Specific target organ systemic toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ systemic toxicity - repeated exposure, Category 1, Lungs	H372: Causes damage to organs through prolonged or repeated exposure.

### GHS label elements

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H319 Causes serious eye irritation. H335 May cause respiratory irritation. H350i May cause cancer by inhalation. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.
Precautionary Statements	:	<b>Prevention:</b> P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read



and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

P281 Use personal protective equipment as required.

**Response:**

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### 3. Composition/information on ingredients

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration (%)
Pozzolans, coal-ash	71243-67-9	$\geq 25 - < 50$ %
Quartz (SiO <sub>2</sub> ) <5 $\mu$ m	14808-60-7	$\geq 2 - < 5$ %
calcium oxide	1305-78-8	$\geq 1 - < 2$ %
titanium dioxide	13463-67-7	$< 1$ %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.



- |   |   |
|---|---|
| In case of eye contact                                      | : Immediately flush eye(s) with plenty of water.<br>Remove contact lenses.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.  |
| If swallowed  | : Clean mouth with water and drink afterwards plenty of water.<br>Do not induce vomiting without medical advice.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.  |
| Most important symptoms and effects, both acute and delayed | : irritant effects<br>carcinogenic effects<br><br>Prolonged exposure can cause silicosis.<br><br>Cough<br>Respiratory disorder<br>Excessive lachrymation<br>See Section 11 for more detailed information on health effects and symptoms.<br><br>Causes serious eye irritation.<br>May cause respiratory irritation.<br>May cause cancer by inhalation.<br>Causes damage to organs through prolonged or repeated exposure. |
| Protection of first-aiders                                  | : Move out of dangerous area.<br>Consult a physician.<br>Show this material safety data sheet to the doctor in attendance.  |
| Notes to physician  | : Treat symptomatically.  |

**5. Fire-fighting measures**

- |  |   |
|--|---|
| Suitable extinguishing media                   | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.   |
| Specific extinguishing methods                 | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus.  |

**6. Accidental release measures**

- |   |  |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Avoid breathing dust.<br>Deny access to unprotected persons. |
|---|--|



- Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

**7. Handling and storage**

- Advice on safe handling : Avoid formation of respirable particles. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Prevent unauthorized access. Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.
- Materials to avoid : No data available

**8. Exposure controls/personal protection**

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
diiron trioxide	1309-37-1	ACGIH	TWA	5 mg/m3 Respirable fraction
		OSHA P0	TWA	10 mg/m3
		OSHA Z-1	TWA	10 mg/m3 Fumes
		OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA Z-1	TWA	5 mg/m3 respirable fraction
		OSHA P0	TWA	10 mg/m3 Fumes
		NIOSH REL	TWA	5 mg/m3 dust and fume
		CAL PEL	PEL	10 mg/m3



				Total dust
		CAL PEL	PEL	5 mg/m3 respirable dust fraction
		CAL PEL	PEL	5 mg/m3 Fumes
C.I. PIGMENT GREEN 17	1308-38-9	OSHA Z-1	TWA	0.5 mg/m3
		ACGIH	TWA	0.5 mg/m3
		OSHA P0	TWA	1 mg/m3
		OSHA Z-1	TWA	1 mg/m3
		OSHA Z-1	TWA	1 mg/m3
Quartz (SiO2) <5µm	14808-60-7	OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-1	TWA	0.05 mg/m3 Respirable dust
calcium oxide	1305-78-8	ACGIH	TWA	2 mg/m3
		OSHA Z-1	TWA	5 mg/m3
		OSHA P0	TWA	5 mg/m3
		NIOSH REL	TWA	2 mg/m3
		CAL PEL	PEL	2 mg/m3
titanium dioxide	13463-67-7	OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA P0	TWA	10 mg/m3 Total dust
		ACGIH	TWA	10 mg/m3



		ACGIH	TWA	10 mg/m3
--	--	-------	-----	----------

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**\*\*Basis**

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection**  
**Remarks** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Avoid breathing dust.

**9. Physical and chemical properties**

Appearance	: powder
Color	: various
Odor	: odorless
Odor Threshold	: No data available
Flash point	: Note: Not applicable
Ignition temperature	: No data available
Decomposition temperature	: No data available
Lower explosion limit (Vol%)	: No data available
Upper explosion limit (Vol%)	: No data available
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
pH	: Note: Not applicable
Melting point/freezing point	: Note: Not applicable
Boiling point/boiling range	: Note: Not applicable
Vapor pressure	: No data available
Density	: 2.8 - 4.5 g/cm <sup>3</sup> at 73 °F (23 °C)
Water solubility	: Note: slightly soluble
Partition coefficient: n- octanol/water	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: Note: Not applicable
Relative vapor density	: No data available
Evaporation rate	: No data available
Burning rate	: No data available
Volatile organic compounds (VOC) content	: Not applicable

---

**10. Stability and reactivity**

Reactivity	: No dangerous reaction known under conditions of normal use.
------------	---



Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available

## 11. Toxicological information

### Acute toxicity

Not classified based on available information.

### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.  
Prolonged exposure can cause silicosis.

### Aspiration toxicity

Not classified based on available information.

### Carcinogenicity

May cause cancer by inhalation.

#### IARC

Group 1: Carcinogenic to humans

Quartz (SiO<sub>2</sub>) <5µm 14808-60-7

Group 2B: Possibly carcinogenic to humans

#### NTP

titanium dioxide 13463-67-7

Known to be human carcinogen

Quartz (SiO<sub>2</sub>) <5µm 14808-60-7

Titanium dioxide (13463-67-7)

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have been shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these





adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that cause lung cancer. Epidemiology studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

---

## 12. Ecological information

Other information	Do not empty into drains; dispose of this material and its container in a safe way.
-------------------	---

---

## 13. Disposal considerations

### Disposal methods

Waste from residues	: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## 14. Transport information

### DOT

Not dangerous goods

### IATA

Not dangerous goods

### IMDG

Not dangerous goods

### Special precautions for user

No data available

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

---

## 15. Regulatory information

TSCA list	: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory
-----------	--



exemption.

**EPCRA - Emergency Planning and Community Right-to-Know**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA304 Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Carcinogenicity  
 Specific target organ toxicity (single or repeated exposure)  
 Serious eye damage or eye irritation

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:  
 C.I. PIGMENT GREEN 17 1308-38-9 >= 5 - < 10 %

**Clean Air Act**

**Ozone-Depletion Potential** This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

C.I. PIGMENT GREEN 17 1308-38-9 >= 5 - < 10 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

**California Prop 65**  **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**16. Other information**

**HMIS Classification**

<b>Health</b>	*	3
<b>Flammability</b>	0	
<b>Physical Hazard</b>	0	
<b>Personal Protection</b>	X	

**Caution:** HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating

**SCOFIELD® Integral Color SG**



Revision Date 02/20/2018

Print Date 02/27/2018

is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

---

**Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 02/20/2018

Material number: 561299