



Flooring Name: Sikafloor® 260 ESD, Sikafloor® 264 ECF

Description: Sikafloor®- 260 ESD and Sikafloor®- 264 ECF are pigmented, electrostatically dissipative, self-smoothing coatings.

Properties: Smooth, glossy, electrostatically dissipative.

Initial Treatment		
Method	Tool	Product
None	None	None

Maintenance Cleaning		
Method	Tool	Product
Dust Mopping	TASKI Ultra Mop Frame, TASKI Large Handle, TASKI Micro Blue Pad	None
Wet Mopping	Mop System	Stride Citrus
Scrubber Drying Direct Method	Red or Contact Pad	Stride Citrus

Interim Cleaning		
Method	Tool	Product
Maintenance Cleaning	Red Pad	Snapback TM/MC Spray Buff
Scrubber Drying Indirect Method	Red or Contact Pad	Speedtrack

Deep Cleaning		
Method	Tool	Product
Wet Scrubbing and Wet Vacuum Indirect Method	Scrubber Dryer or Single Disc Machine with Blue Pad and Wet Vacuum	Prominence

©2023 Sika Corporation All Rights Reserved

Product Dosing: Refer to Diversey Data Sheet

When cleaning ESD control floor coatings, always follow cleaning procedure with clear water rinse to remove cleaner residue, which can inhibit electrical performance. Wash water containing high levels of dissolved minerals (hard water) may leave a residue that may reduce the effectiveness of ESD grounding of personnel.

