Revision Date 06/08/2022



SECTION 1. IDENTIFICATION

Product name	:	Rut-Mix
Other means of identification	:	Rut-Mix SY
Company name	:	Sika Corporation
		201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion	:	Category 1C
Serious eye damage	:	Category 1
Skin sensitization	:	Category 1
Carcinogenicity (Inhalation)	:	Category 1A
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure	:	Category 1 (Lungs)
Specific target organ toxicity - repeated exposure	:	Category 2

GHS label elements

Revision Date 06/08/2022



Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	 H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H350 May cause cancer by inhalation. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary Statements	:	 Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
		 Response: P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse.
		Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

Revision Date 06/08/2022



Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
Quartz (SiO2) >5µm	14808-60-7	Carc. 1A; H350i STOT RE 1; H372 STOT SE 3; H335	>= 70 - < 90
Calcium Sulfoaluminate cement	960375-09-1	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT RE 2; H373	>= 10 - < 20
Cement	65997-15-1	Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335	>= 5 - < 10
Cristobalite	14464-46-1	Carc. 1A; H350	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attend- ance.				
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.				
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.				
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.				
	3/12					

Revision Date 06/08/2022



		Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	Health injuries may be delayed. corrosive effects irritant effects sensitizing effects Prolonged exposure can cause silicosis. Cough Respiratory disorder Allergic reactions Dermatitis May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure. Causes severe burns.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages



Revision Date 06/08/2022

cannot be contained.

Methods and materials for	:	Pick up and arrange disposal without creating dust.
containment and cleaning up		Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
Advice on safe handling	:	 Avoid formation of respirable particles. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	:	Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.
Materials to avoid	:	Explosives Oxidizing agents Poisonous gases Dangerous when wet Flammable solids Organic peroxides Poisonous liquids Spontaneously Combustible Substances
Further information on stor- age stability	:	Keep in a dry place. No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Quartz (SiO2) >5µm	14808-60-7	TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH

Revision Date 06/08/2022



		TWA (Res- pirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respir- able)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respir- able)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respir- able dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respir- able)	0.05 mg/m3	OSHA CAR
		TWA (respir- able dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
Cement	65997-15-1	TWA (Res- pirable par- ticulate mat- ter)	1 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respir- able fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respir- able dust fraction)	5 mg/m3	OSHA P0
		TWA (Dust)	50 Million parti- cles per cubic foot	OSHA Z-3
		TWA (Total)	10 mg/m3	OSHA P0
		TWA (Res- pirable frac- tion)	5 mg/m3	OSHA P0
Cristobalite	14464-46-1	TWA (Res- pirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respir- able dust fraction)	0.05 mg/m3	OSHA P0
		TWA (Res- pirable par- ticulate mat-	0.025 mg/m3 (Silica)	ACGIH

Safety Data Sheet

Rut-Mix



Revision Date 06/08/2022

t t	er)	1
I	/	

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Particles of nuisance dust

Form of exposure	Value type	Control parameters	Basis
total dust	TWA	15 mg/m3	OSHA Z-3
respirable fraction	TWA	5 mg/m3	OSHA Z-3
Engineering measures :	Use of adequate ventila worker exposure to airb product generates dust, cess enclosures, local e ing controls to keep wor ed or statutory limits.	orne contaminants. If th fumes, gas, vapor or m xhaust ventilation or oth	e use of this list, use pro- ner engineer-
Personal protective equipmen	t		
Respiratory protection :	Use a properly fitted NIC respirator complying wit sessment indicates this The filter class for the re imum expected contami (gas/vapor/aerosol/parti dling the product. If this contained breathing app	h an approved standard is necessary. espirator must be suitab nant concentration culates) that may arise concentration is exceed	l if a risk as- le for the max- when han-
Hand protection :	Chemical-resistant, imp approved standard shou chemical products if a ri essary.	Ild be worn at all times	when handling
Eye protection :	Safety eyewear complyi be used when a risk ass		
Skin and body protection :	Choose body protection tration and amount of da cific work-place.		
Hygiene measures :	Avoid contact with skin, Wash hands before breat the product. Remove contaminated of before entering eating a Wash thoroughly after h Avoid breathing dust.	aks and immediately aft clothing and protective e reas.	Ū

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

:

Appearance

7/12

Revision Date 06/08/2022



Color	:	various
Odor	:	odorless
Odor Threshold	:	No data available
рН	:	No data available
Melting point/range / Freezing	:	No data available
point Boiling point/boiling range	:	No data available
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	ca. 2.5 g/l (68 °F / 20 °C)
Solubility(ies) Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-	:	No data available
octanol/water Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	Not applicable

Revision Date 06/08/2022



SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Not classified b	ased on available information.				
Skin corrosion					
_	amage/eye irritation				
Causes serious	, ,				
Respiratory or	skin sensitization				
Skin sensitizat	tion				
May cause an a	allergic skin reaction.				
Respiratory se	ensitization				
Not classified b	ased on available information.				
Germ cell muta	agenicity				
Not classified b	ased on available information.				
Carcinogenicit	ty				
May cause cancer by inhalation.					
IARC	Group 1: Carcinogenic to humans Quartz (SiO2)	14808-60-7			
	(Silica dust, crystalline)	14000-00-7			
	Group 1: Carcinogenic to humans				
	cristobalite	14464-46-1			
(Silica dust, crystalline)					
OSHA	OSHA specifically regulated carcinogen				
Quartz (SiO2) 14808-60					
	(crystalline silica)				
NTP	Known to be human carcinogen				
Quartz (SiO2) 148					
	(Silica, Crystalline (Respirable Size))				

Revision Date 06/08/2022



Known to be human carcinogen cristobalite (Silica, Crystalline (Respirable Size))

14464-46-1

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Prolonged exposure can cause silicosis.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity	
No data available	
Persistence and degradability	
No data available	
Bioaccumulative potential	
No data available	
Mobility in soil	
No data available	
Other adverse effects	
Product:	
Additional ecological infor- : mation	Do not empty into drains; dispose of this material and its con- tainer in a safe way.

Disposal methods

Waste from residues	:	Disposal of this product, solutions and any by-products should
		at all times comply with the requirements of environmental



Revision Date 06/08/2022			Print Date 06/08
		protection and waste disposal legislation and any local authority requirements.	regional
Contaminated packaging	:	Empty containers should be taken to an approved dling site for recycling or disposal.	d waste han-

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	Respiratory or skin sensitization Carcinogenicity Specific target organ toxicity (single or repeated exposure) Skin corrosion or irritation Serious eye damage or eye irritation
SARA 313 :	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

▲ WARNING: This product can expose you to chemicals including Quartz (SiO2) >5µm, which is known to the State of California to cause cancer, and Cement, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to

Revision Date 06/08/2022



www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviation	ons	
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 06/08/2022

100000036934 US / Z8