

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

### 1 Identification

- **Product identifier**
- **Trade name:** Micro-Ultra 15-3 Filler
- **Article number:** 1015088
- **Application of the substance / the mixture**  
Polyester resin  
Flame-retardant filler
- **Details of the supplier of the safety data sheet**  
Sika Advanced Resins, US  
EHS Department
- **Manufacturer/Supplier:**  
Manufacturer:  
Sika Advanced Resins  
30800 Stephenson Hwy  
Madison Heights  
MI 48071  
USA
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (248) 588-2270  
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 1B H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Styrene*

*antimony trioxide*

· **Hazard statements**

*Flammable liquid and vapor.*

*Causes skin irritation.*

*Causes serious eye irritation.*

*May cause cancer.*

*Suspected of damaging fertility or the unborn child.*

*Causes damage to the hearing organs through prolonged or repeated exposure.*

· **Precautionary statements**

*Avoid breathing dust/fume/gas/mist/vapors/spray*

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Keep container tightly closed.*

*Ground/bond container and receiving equipment.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Do not breathe dust/fume/gas/mist/vapors/spray.*

*Wash thoroughly after handling.*

*Do not eat, drink or smoke when using this product.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*IF exposed or concerned: Get medical advice/attention.*

*Specific treatment (see on this label).*

*Get medical advice/attention if you feel unwell.*

*Take off contaminated clothing and wash it before reuse.*

*If skin irritation occurs: Get medical advice/attention.*

*If eye irritation persists: Get medical advice/attention.*

*In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*

*Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 100-42-5 EINECS: 202-851-5	Styrene	10-20%
CAS: 1309-64-4 EINECS: 215-175-0	antimony trioxide	1-5%
CAS: 78-40-0 EINECS: 201-114-5	triethyl phosphate	1-5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**  
Mouth respiratory protective device.  
Wear self-contained respiratory protective device.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

100-42-5	Styrene	20 ppm
1309-64-4	antimony trioxide	1.8 mg/m <sup>3</sup>
78-40-0	triethyl phosphate	23 mg/m <sup>3</sup>

· **PAC-2:**

100-42-5	Styrene	130 ppm
1309-64-4	antimony trioxide	16 mg/m <sup>3</sup>
78-40-0	triethyl phosphate	250 mg/m <sup>3</sup>

(Contd. on page 5)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 4)

<b>· PAC-3:</b>		
100-42-5	Styrene	1100* ppm
1309-64-4	antimony trioxide	96 mg/m <sup>3</sup>
78-40-0	triethyl phosphate	320 mg/m <sup>3</sup>

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

<b>100-42-5 Styrene</b>	
ACGIH TLV	Short-term value: 170 at 40 ppm mg/m <sup>3</sup> Long-term value: 85 at 20 ppm mg/m <sup>3</sup>
OSHA PEL	Long-term value: 100 ppm mg/m <sup>3</sup> Ceiling limit value: 200 ppm mg/m <sup>3</sup>
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs

(Contd. on page 6)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 5)

REL	Short-term value: 425 mg/m <sup>3</sup> , 100 ppm Long-term value: 215 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 20 ppm Long-term value: 10 ppm BEI, OTO
<b>78-40-0 triethyl phosphate</b>	
WEEL	Long-term value: 7.45 mg/m <sup>3</sup>

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

US

(Contd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

Trade name: Micro-Ultra 15-3 Filler

(Contd. of page 6)

### 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Pasty
Color:	White
Odor:	Pungent
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145 °C (293 °F)

· **Flash point:** 31 °C (87.8 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 490 °C (914 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	0.9 Vol %
Upper:	6.8 Vol %

· **Vapor pressure at 20 °C (68 °F):** 6 hPa (4.5 mm Hg)

· **Density at 20 °C (68 °F):** 1.13 g/cm<sup>3</sup> (9.43 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic at 20 °C (68 °F): >5,000 mPas

Kinematic at 40 °C (104 °F): >1,000 mm<sup>2</sup>/s

· **Solvent content:**

Organic solvents: 1.6 %

VOC content: 21.49 %

242.9 g/l / 2.03 lb/gal

(Contd. on page 8)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 7)

**Solids content:** 41.8 %

· **Other information** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

#### 100-42-5 Styrene

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	11.8 mg/l (rat)

#### 1309-64-4 antimony trioxide

Oral	LD50	>20,000 mg/kg (rat)
------	------	---------------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc (Mg3H2(SiO3)4)	3
100-42-5	Styrene	2A
13463-67-7	titanium dioxide	2B
112926-00-8	Precipitated silica (Silica-Amorphous)	3
1309-64-4	antimony trioxide	2B
64-17-5	ethanol	1

(Contd. on page 9)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 8)

7631-86-9	silicon dioxide, chemically prepared	3
· <b>NTP (National Toxicology Program)</b>		
None of the ingredients is listed.		
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
7440-38-2	arsenic	

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

\* **13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

**14 Transport information**

· <b>UN-Number</b>	
· <b>DOT, IMDG, IATA</b>	UN1866
· <b>UN proper shipping name</b>	
· <b>DOT</b>	Resin solution
· <b>IMDG, IATA</b>	RESIN SOLUTION

(Contd. on page 10)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 9)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids  
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids  
· **Label** 3

· **Packing group**  
· **DOT, IMDG, IATA** III

· **Environmental hazards:**  
· **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids  
· **Hazard identification number (Kemler code):** 39  
· **EMS Number:** F-E, S-E  
· **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**  
· **Quantity limitations** On passenger aircraft/rail: 60 L  
On cargo aircraft only: 220 L

· **IMDG**

· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1866 RESIN SOLUTION, 3, III

(Contd. on page 11)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 10)

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

100-42-5	Styrene
----------	---------

1309-64-4	antimony trioxide
-----------	-------------------

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

· **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

· **Hazardous Air Pollutants**

100-42-5	Styrene
----------	---------

1309-64-4	antimony trioxide
-----------	-------------------

108-10-1	4-methylpentan-2-one
----------	----------------------

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-42-5	Styrene
----------	---------

13463-67-7	titanium dioxide
------------	------------------

1309-64-4	antimony trioxide
-----------	-------------------

108-10-1	4-methylpentan-2-one
----------	----------------------

7439-92-1	lead
-----------	------

7440-38-2	arsenic
-----------	---------

· **Chemicals known to cause reproductive toxicity for females:**

7439-92-1	lead
-----------	------

· **Chemicals known to cause reproductive toxicity for males:**

7439-92-1	lead
-----------	------

· **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
---------	---------

108-10-1	4-methylpentan-2-one
----------	----------------------

7439-92-1	lead
-----------	------

(Contd. on page 12)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 11)

· **Carcinogenic categories**

· **TLV (Threshold Limit Value established by ACGIH)**

1309-64-4	antimony trioxide	A2
-----------	-------------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide	
------------	------------------	--

· **Listed in CWC Regulations**

None of the ingredients is listed.
------------------------------------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02    GHS07    GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Styrene

antimony trioxide

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

(Contd. on page 13)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2021

Reviewed on 04/20/2021

**Trade name: Micro-Ultra 15-3 Filler**

(Contd. of page 12)

Get medical advice/attention if you feel unwell.  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.  
 Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 04/20/2021 / 16

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
 Carc. 1B: Carcinogenicity – Category 1B  
 Repr. 2: Reproductive toxicity – Category 2  
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

· **\* Data compared to the previous version altered.**